




**ELECTRONICS, INC.**  
44 FARRAND STREET  
BLOOMFIELD, NJ 07003  
(973) 748-5089

电子市场网  
WWW.DZSC.COM



维库电子市场网  
WWW.DZSC.COM

## NTE14 Silicon PNP Transistor High Power, Low Frequency Driver

**Features:**

- High Power Compact FTR Package:  $P_C = 750\text{mW}$
- High Breakdown Voltage:  $V_{CEO} = 80\text{V}$

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Collector–Base Voltage, $V_{CBO}$ .....	80V
Collector–Emitter Voltage, $V_{CEO}$ .....	80V
Emitter–Base Voltage, $V_{EBO}$ .....	5V
Collector Current, $I_C$ .....	700mA
Collector Dissipation, $P_C$ .....	750mW
Junction Temperature, $T_J$ .....	+135°C
Storage Temperature Range, $T_{stg}$ .....	–55° to +135°C

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector–Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 2\text{mA}$	80	–	–	V
Collector–Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 50\mu\text{A}$	80	–	–	V
Emitter–Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 50\mu\text{A}$	5	–	–	V
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = 50\text{V}$	–	–	0.5	$\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = 4\text{V}$	–	–	0.5	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE} = 3\text{V}, I_C = 100\text{mA}$	120	–	270	–
Collector Saturation Voltage	$V_{CE(sat)}$	$I_C = 500\text{mA}, I_B = 50\text{mA}$	–	0.2	0.4	V
Transition Frequency	$f_T$	$V_{CE} = 10\text{V}, I_E = 50\text{mA}$	–	100	–	MHz
Output Capacitance	$C_{ob}$	$V_{CB} = 10\text{V}, I_E = 0, f = 1\text{MHz}$	–	14	20	pF



