


InGaAsP STRAINED DC-PBH LASER DIODE MODULE
1 625 nm TELEMETRY APPLICATION

DESCRIPTION


The NX7660JC is a 1 625 nm newly developed Strained Multiple Quantum Well (St-MQW) structure laser diode DIP module with single mode fiber and internal thermoelectric cooler. It is designed for light sources of telemetry equipment.

FEATURES

- ★ Output power $P_r = 5 \text{ mW MIN. @ } I_F = 65 \text{ mA CW}$
- Long Wavelength $\lambda_c = 1\,625 \text{ nm}$
- ★ Wide operating temperature range $T_c = -5 \text{ to } +70 \text{ }^\circ\text{C}$
- Internal thermoelectric cooler, thermistor
- Hermetically sealed 14-pin DIP package
- Single mode fiber pigtail



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.



ORDERING INFORMATION

Part Number	Available Connector
NX7660JC	Without Connector
NX7660JC-BA	With FC-PC Connector
NX7660JC-CA	With SC-PC Connector

★ ABSOLUTE MAXIMUM RATINGS ($T_c = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Forward Current of LD	I_F	200	mA
Reverse Voltage of LD	V_R	2.0	V
Forward Current of PD	I_F	10	mA
Reverse Voltage of PD	V_R	20	V
Cooler Current	I_c	1.2	A
Cooler Voltage	V_c	2.5	V
Operating Case Temperature	T_c	-5 to +70	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-40 to +85	$^{\circ}\text{C}$
Lead Soldering Temperature (10 s)	T_{sld}	260	$^{\circ}\text{C}$

★ ELECTRO-OPTICAL CHARACTERISTICS ($T_{LD} = 25\text{ }^{\circ}\text{C}$, $T_c = -5\text{ to }+70\text{ }^{\circ}\text{C}$)


Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Forward Voltage	V_F	$P_f = 5\text{ mW}$		1.1	1.5	V
Threshold Current	I_{th}			15	30	mA
Optical Output Power from Fiber	P_f	$I_F = 65\text{ mA}$	5			mW
Operating Current	I_{op}	$P_f = 5\text{ mW}$		65	75	mA
Differential Efficiency form Fiber	η_d		0.08	0.15		W/A
Center Wavelength	λ_c	$P_f = 5\text{ mW}$, RMS	1 615	1 625	1 635	nm
Spectral Width	σ	$P_f = 5\text{ mW}$, RMS		2.5	5	nm

★ ELECTRO-OPTICAL CHARACTERISTICS

(Applicable to Monitor PD: $T_{LD} = 25\text{ °C}$, $T_C = -5\text{ to }+70\text{ °C}$)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Monitor Current	I_m	$V_R = 5\text{ V}$, $P_f = 5\text{ mW}$	50	150	260	μA
Monitor Dark Current	I_D	$V_R = 5\text{ V}$		1.0	10	nA
Tracking Error	γ^{*1}	$I_m = \text{const.}$			0.5	dB

$$*1 \gamma = \left| 10 \log \frac{P_f}{5\text{ mW}} \right|$$



★ ELECTRO-OPTICAL CHARACTERISTICS


(Applicable to Thermistor and TEC: $T_{LD} = 25\text{ °C}$, $T_C = -5\text{ to }+70\text{ °C}$)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Thermistor Resistance	R		9.5	10.0	10.5	$\text{k}\Omega$
B Constant	B		3 300	3 400	3 500	K
Cooler Current	I_c	$\Delta T = 45\text{ K}$		0.6	1.0	A
Cooler Voltage	V_c	$\Delta T = 45\text{ K}$		1.4	2.0	V
Cooling Capacity	ΔT^{*1}	$I_c = 1.0\text{ A}$	45			K


$$*1 \Delta T = |T_C - T_{LD}|$$

★ TYPICAL CHARACTERISTICS ($T_{LD} = 25\text{ }^{\circ}\text{C}$, $T_C = -5\text{ to }+70\text{ }^{\circ}\text{C}$)


OUTPUT POWER FROM FIBER vs.
FORWARD CURRENT




FORWARD CURRENT vs.
FORWARD VOLTAGE




OUTPUT POWER FROM FIBER vs.
LD MONITOR CURRENT



LONGITUDINAL MODE FROM FIBER



TYPICAL THERMISTOR RESISTANCE vs.
AMBIENT TEMPERATURE



Remark The graphs indicate nominal characteristics.

LD FAMILY FOR DENSE WDM APPLICATION

	Part Number	Absolute Maximum Ratings		Typical Characteristics			Description	Package
		T _c (°C)	T _{stg} (°C)	I _{th} (mA)	P _r (mW)	λ _c (nm)		
				TYP.	MIN.	TYP.		
★	NX7460LE	−20 to +65	−40 to +85	25	120	1 480	1 480 nm pump LD module	BFY
	NX8501 Series	0 to +65	−40 to +85	20	2	1 510	Telemetry	Coaxial
	NX8561JC ^{*1}	0 to +65	−40 to +85	20	3	1 510	Telemetry	DIP
★	NX7660JC	−5 to +70	−40 to +85	15	5	1 625	Telemetry	DIP
	NDL7910P	−20 to +70	−40 to +85	7	0.5	1 550 ^{*2}	2.5 G EA modulator integrated module	BFY
	NX8562LB	−20 to +65	−40 to +85	20	20	1 550 ^{*2}	1 550 CW LD module	BFY
	NX8563LB	−20 to +65	−40 to +85	20	10	ITU-T ^{*3}	1 550 CW LD module	BFY

*1 Under development

*2 Wavelength selectable for ITU-T standards upon request

*3 Wavelength selectable for ITU-T standards

REFERENCE

	Document Name	Document No.
	NEC semiconductor device reliability/quality control system	C11159E
	Quality grades on NEC semiconductor devices	C11531E
	Semiconductor device mounting technology manual	C10535E
★	SEMICONDUCTOR SELECTION GUIDE Products & Packages (CD-ROM)	X13769X


[MEMO]

[MEMO]


[MEMO]

CAUTION

Within this device there exists GaAs (Gallium Arsenide) material which is a harmful substance if ingested. Please do not under any circumstances break the hermetic seal.



SEMICONDUCTOR LASER



AVOID EXPOSURE-Invisible
Laser Radiation is emitted from
this aperture

NEC Corporation

NEC Building, 7-1, Shiba 5-chome,
Minato-ku, Tokyo 108-01, Japan

Type number: _____

Manufactured: _____

Serial Number: _____

This product conforms to FDA
regulations as applicable
to standards 21 CFR Chapter 1.
Subchapter J.

The export of this product from Japan is prohibited without governmental license. To export or re-export this product from a country other than Japan may also be prohibited without a license from that country. Please call an NEC sales representative.

- **The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.**
 - No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.
 - NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.
 - Descriptions of circuits, software, and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software, and information in the design of the customer's equipment shall be done under the full responsibility of the customer. NEC Corporation assumes no responsibility for any losses incurred by the customer or third parties arising from the use of these circuits, software, and information.
 - While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.
 - NEC devices are classified into the following three quality grades:
 "Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.
 - Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 - Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 - Specific: Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.
- The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.