

DIODE MODULE 200A/1600V

PD20116




OUTLINE DRAWING

FEATURES

- * 108mm Short Size Case
- * Isolated Base
- * Dual Diodes Cascaded Circuit
- * High Surge Capability

TYPICAL APPLICATIONS

- * Rectified For General Use



Maximum Ratings

Approx Net Weight:280g

Parameter	Symbol	Type / Grade	Unit
		PD20116	
Repetitive Peak Reverse Voltage *1	V_{RRM}	1600	V
Non Repetitive Peak Reverse Voltage *1	V_{RSM}	1700	




Parameter	Symbol	Conditions	Max Rated Value	Unit
Average Rectified Output Current *1	$I_{O(AV)}$	50 Hz Half Sine Wave condition $T_c=98^{\circ}C$	200	A
RMS Forward Current *1	$I_{F(RMS)}$		314	A
Surge Forward Current *1	I_{FSM}	50 Hz Half Sine Wave, 1cycle, Non-Repetitive	4500	A
I Squared t *1	I^2t	2msec to 10msec	101250	A^2s
Operating Junction Temperature Range	T_{jw}		-40 to +150	$^{\circ}C$
Storage Temperature Range	T_{stg}		-40 to +125	$^{\circ}C$
Isolation Voltage	V_{iso}	Base Plate to Terminals, AC1min	2500	V
Mounting Torque	Case Mounting	F_{tor}	M6 Screw	N.m
	Terminals		M6 Screw	

Electrical • Thermal Characteristics

Characteristics	Symbol	Test Conditions	Max.	Unit
Peak Reverse Current *1	I_{RM}	$V_{RM}= V_{RRM}, T_j= 150^{\circ}C$	30	mA
Peak Forward Voltage *1	V_{FM}	$I_{FM}= 600A, T_j=25^{\circ}C$	1.33	V
Thermal Resistance *1	$R_{th(j-c)}$	Junction to Case	0.2	$^{\circ}C/W$
	$R_{th(c-f)}$	Case to Fin, Greased	0.15	


*1: Value Per 1Arm


PD20116 OUTLINE DRAWING (Dimensions in mm)





FORWARD CURRENT VS. VOLTAGE

PD20116 (Per 1 Arm.)






AVERAGE FORWARD POWER DISSIPATION




AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE



SURGE CURRENT RATINGS

f=50Hz, Half Sine Wave, Non-Repetitive, Tj=150

PD20116 (Per 1 Arm.)



MAXIMUM TRANSIENT THERMAL IMPEDANCE
Junction to Case

