查询PHB101NQ04T供应商

PHP/PHB101NQ04T

N-channel TrenchMOS™ standard level FET

Rev. 01 — 12 May 2004 Product data

1. Product profile

1.1 Description

N-channel enhancement mode field-effect power transistor in a plastic package using TrenchMOS™ technology.

1.2 Features

- Standard level threshold
- Very low on-state resistance.

1.3 Applications

- Motors, lamps, solenoids
- DC-to-DC converters
- Uninterruptible power supplies
- General industrial applications.

1.4 Quick reference data

- $V_{DS} \leq 40$ V
- $I_D \leq 75$ A
- $P_{tot} \leq 157$ W
- $R_{DSon} \leq 8$ mΩ.

2. Pinning information

Table 1: Pinning - SOT78 (TO-220AB) and SOT404 (D^2-PAK), simplified outline and symbol

Pin	Description	Simplified outline	Symbol
1	gate (g)		
2	drain (d) [1]		
3	source (s)		
mb	mounting base; connected to drain (d)		



SOT78 (TO-220AB)



SOT404 (D^2-PAK)



[1] It is not possible to make connection to pin 2 of the SOT404 package.

PHILIPS

3. Ordering information

Table 2: Ordering information

Type number	Package		
	Name	Description	Version
PHP101NQ04T	TO-220AB	Plastic single-ended package; heatsink mounted; 1 mounting hole; 3 leads	SOT78
PHB101NQ04T	D^2-PAK	Plastic single-ended surface mounted package; 3 leads (one lead cropped)	SOT404

4. Limiting values

Table 3: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage (DC)	25 °C ≤ T_j ≤ 175 °C	-	40	V
V_{DGR}	drain-gate voltage (DC)	25 °C ≤ T_j ≤ 175 °C; R_{GS} = 20 kΩ	-	40	V
V_{GS}	gate-source voltage (DC)		-	±20	V
I_D	drain current (DC)	T_{mb} = 25 °C; V_{GS} = 10 V; Figure 2 and 3	-	75	A
		T_{mb} = 100 °C; V_{GS} = 10 V; Figure 2	-	71	A
I_{DM}	peak drain current	T_{mb} = 25 °C; pulsed; t_p ≤ 10 µs; Figure 3	-	240	A
P_{tot}	total power dissipation	T_{mb} = 25 °C; Figure 1	-	157	W
T_{stg}	storage temperature		–55	+175	°C
T_j	junction temperature		–55	+175	°C
Source-drain diode					
I_S	source (diode forward) current (DC)	T_{mb} = 25 °C	-	75	A
I_{SM}	peak source (diode forward) current	T_{mb} = 25 °C; pulsed; t_p ≤ 10 µs	-	240	A
Avalanche ruggedness					
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	unclamped inductive load; I_D = 45 A; t_p = 0.17 ms; V_{DD} ≤ 55 V; R_{GS} = 50 Ω; V_{GS} = 10 V; starting at T_j = 25 °C	-	200	mJ

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.



$$P_{der} = \frac{P_{tot}}{P_{tot(25^{\circ}C)}} \times 100\%$$

Fig 1. Normalized total power dissipation as a function of mounting base temperature.



$$I_{der} = \frac{I_D}{I_{D(25^{\circ}C)}} \times 100\%$$

Fig 2. Normalized continuous drain current as a function of mounting base temperature.



T_{mb} = 25 °C; I_{DM} is single pulse; V_{GS} = 10 V.

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage.

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

5. Thermal characteristics

Table 4: Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-mb)}$	thermal resistance from junction to mounting base	Figure 4	-	-	0.95	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient					
	SOT78	vertical in still air	-	60	-	K/W
	SOT404	mounted on a printed-circuit board; vertical in still air; minimum footprint.	-	50	-	K/W

5.1 Transient thermal impedance



Fig 4. Transient thermal impedance from junction to mounting base as a function of pulse duration.

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

6. Characteristics

Table 5: Characteristics

T_j = 25 °C unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = 250 µA; V_{GS} = 0 V				
		T_j = 25 °C	40	-	-	V
		T_j = –55 °C	36	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	I_D = 1 mA; V_{DS} = V_{GS}; Figure 9 and 10				
		T_j = 25 °C	2	3	4	V
		T_j = 175 °C	1	-	-	V
		T_j = –55 °C	-	-	4.4	V
I_{DSS}	drain-source leakage current	V_{DS} = 40 V; V_{GS} = 0 V				
		T_j = 25 °C	-	-	1	µA
		T_j = 175 °C	-	-	500	µA
I_{GSS}	gate-source leakage current	V_{GS} = ±20 V; V_{DS} = 0 V	-	2	100	nA
R_{DSon}	drain-source on-state resistance	V_{GS} = 10 V; I_D = 25 A; Figure 7 and 8				
		T_j = 25 °C	-	6.6	8	mΩ
		T_j = 175 °C	-		15.2	mΩ
Dynamic characteristics						
$Q_{g(tot)}$	total gate charge	I_D = 25 A; V_{DD} = 32 V; V_{GS} = 10 V; Figure 13	-	36.6	-	nC
Q_{gs}	gate-source charge		-	9.8	-	nC
Q_{gd}	gate-drain (Miller) charge		-	12.6	-	nC
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = 25 V; f = 1 MHz; Figure 11	-	2020	-	pF
C_{oss}	output capacitance		-	485	-	pF
C_{rss}	reverse transfer capacitance		-	215	-	pF
$t_{d(on)}$	turn-on delay time	V_{DD} = 30 V; R_L = 1.2 Ω; V_{GS} = 10 V; R_G = 10 Ω	-	20	-	ns
t_r	rise time		-	51	-	ns
$t_{d(off)}$	turn-off delay time		-	51	-	ns
t_f	fall time		-	33	-	ns
Source-drain diode						
V_{SD}	source-drain (diode forward) voltage	I_S = 25 A; V_{GS} = 0 V; Figure 12	-	0.85	1.2	V
t_{rr}	reverse recovery time	I_S = 20 A; dI_S/dt = –100 A/µs; V_{GS} = 0 V	-	53	-	ns
Q_r	recovered charge		-	44	-	nC

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.



T_j = 25 °C

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values.



T_j = 25 °C and 175 °C; V_{DS} > I_D x R_{DSon}

Fig 6. Transfer characteristics: drain current as a function of gate-source voltage; typical values.



T_j = 25 °C

Fig 7. Drain-source on-state resistance as a function of drain current; typical values.



$$a = \frac{R_{DSon}}{R_{DSon(25^\circ C)}}$$

Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature.

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.



I_D = 1 mA; V_{DS} = V_{GS}

Fig 9. Gate-source threshold voltage as a function of junction temperature.



T_j = 25 °C; V_{DS} = 5 V

Fig 10. Sub-threshold drain current as a function of gate-source voltage.



V_{GS} = 0 V; f = 1 MHz

Fig 11. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values.

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.



T_j = 25 °C and 175 °C; V_{GS} = 0 V

Fig 12. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values.



I_D = 25 A; V_{DD} = 14 V and 32 V

Fig 13. Gate-source voltage as a function of gate charge; typical values.

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

7. Package outline

Plastic single-ended package; heatsink mounted; 1 mounting hole; 3-lead TO-220AB **SOT78**



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1	b	b_1	c	D	D_1	E	e	L	L_1(1)	L_2 max.	p	q	Q
mm	4.5 4.1	1.39 1.27	0.9 0.7	1.3 1.0	0.7 0.4	15.8 15.2	6.4 5.9	10.3 9.7	2.54	15.0 13.5	3.30 2.79	3.0	3.8 3.6	3.0 2.7	2.6 2.2

Note

1. Terminals in this zone are not tinned.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT78		3-lead TO-220AB	SC-46			~~00-09-07~~ 01-02-16

Fig 14. SOT78 (TO-220AB).

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

Plastic single-ended surface mounted package (Philips version of D^2-PAK); 3 leads (one lead cropped)

SOT404



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1	b	c	D max.	D_1	E	e	L_p	H_D	Q
mm	4.50 4.10	1.40 1.27	0.85 0.60	0.64 0.46	11	1.60 1.20	10.30 9.70	2.54	2.90 2.10	15.80 14.80	2.60 2.20

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT404						~~99-06-25~~ 01-02-12

Fig 15. SOT404 (D^2-PAK)

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

8. Revision history

Table 6: Revision history

Rev	Date	CPCN	Description
01	20040512	-	Product data (9397 750 13167).

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

9. Data sheet status

Level	Data sheet status[1]	Product status[2][3]	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

Contact information

For additional information, please visit **http://www.semiconductors.philips.com**.
For sales office addresses, send e-mail to: **sales.addresses@www.semiconductors.philips.com**.

Fax: +31 40 27 24825

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

Contents

1 Product profile 1
1.1 Description 1
1.2 Features 1
1.3 Applications 1
1.4 Quick reference data. 1
2 Pinning information 1
3 Ordering information 2
4 Limiting values 2
5 Thermal characteristics. 4
5.1 Transient thermal impedance 4
6 Characteristics 5
7 Package outline 9
8 Revision history 11
9 Data sheet status 12
10 Definitions 12
11 Disclaimers 12
12 Trademarks 12

© Koninklijke Philips Electronics N.V. 2004.
Printed in The Netherlands

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 12 May 2004 **Document order number: 9397 750 13167**

PHILIPS

Let's make things better.