



PI3A3159

3.0V, SOTiny™ 0.4Ω SPDT Analog Switch

Features

- CMOS Technology for Bus and Analog Applications
- Low ON-Resistance: 0.4Ω (+2.7V Supply)
- Wide V_{CC} Range: +1.5V to +3.6V
- Low Power Consumption : 5μW
- Rail-to-Rail switching throughout Signal Range
- Fast Switching Speed: 20ns max. at 3.3V
- High Off Isolation: -27dB at 100 KHz
- -41dB (100KHz) Crosstalk Rejection Reduces Signal Distortion
- Extended Industrial Temperature Range: -40°C to 85°C
- Packaging (Pb-free & Green available):
 - 6-pin Small Compact SOT-23 (T)
 - 6-pin Ultra Compact (ZC)

Applications

- Cell Phones
- PDAs
- Portable Instrumentation
- Battery Powered Communications
- Computer Peripherals

Pin Description

| Pin Number | Name | Description |
|------------|-----------------|-----------------------------|
| 1 | NO | Data Port (Normally Open) |
| 2 | GND | Ground |
| 3 | NC | Data Port (Normally Closed) |
| 4 | COM | Common Output/Data Port |
| 5 | V _{CC} | Positive Power Supply |
| 6 | IN | Logic Control |

Logic Function Table

| Logic Input | Function |
|-------------|---------------------|
| 0 | NC Connected to COM |
| 1 | NO Connected to COM |


Description

The PI3A3159 is a, fast single-pole double-throw (SPDT) CMOS switch. It can be used as an analog switch or as a low-delay bus switch. Specified over a wide operating power supply voltage range, +1.5V to +3.6V, the PI3A3159 has an On-Resistance of 0.4Ω at 3.0V.

Control input, IN, tolerates input drive signals up to 3.3V, independent of supply voltage.

PI3A3159 is a lower voltage and On-Resistance replacement for the PI5A3159.

Connection Diagram





Absolute Maximum Ratings

Voltages Referenced to GND

V_{CC} -0.5V to +3.6V

V_{IN}, V_{COM}, V_{NC}, V_{NO} (Note 1) -0.5V to V_{CC} +0.3V
or 30mA, whichever occurs first

Current (any terminal)..... ±200mA

Peak Current, COM, NO, NC

(Pulsed at 1ms, 10% duty cycle)..... ±400mA

Thermal Information

Continuous Power Dissipation

SOT23-6 (derate 7.1mW/°C above +70°C)..... 0.5W

Storage Temperature -65°C to +150°C

Lead Temperature (soldering, 10s) +300°C

Note:

1. Signals on NC, NO, COM, or IN exceeding V_{CC} or GND are clamped by internal diodes. Limit forward diode current to 30mA.

Caution: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied.

Electrical Specifications - Single +3.3V Supply

(V_{CC} = +3.3V ± 10%, GND = 0V, V_{IH} = 1.4V, V_{IL} = 0.5V)

| Parameter | Symbol | Conditions | Package | Temp. (°C) | Min. ⁽¹⁾ | Typ. ⁽²⁾ | Max. ⁽¹⁾ | Units |
|--|---|---|---------|------------|---------------------|---------------------|---------------------|-------|
| Analog Switch | | | | | | | | |
| Analog Signal Range ⁽³⁾ | V _{ANALOG} | | | Full | 0 | | V _{CC} | V |
| On Resistance | R _{ON} | V _{CC} = 2.7V, I _{COM} = 100mA, V _{NO} or V _{NC} = +1.5V | | 25 | | | 0.4 | Ω |
| | | | SOT-23 | Full | | | 0.5 | |
| | | | TDFN | | | | 0.6 | |
| On-Resistance Match Between Channels ⁽⁴⁾ | ΔR _{ON} | | | 25 | | | 0.08 | |
| | | | | Full | | | 0.09 | |
| On-Resistance Flat- ness ⁽⁵⁾ | R _{FLAT(ON)} | V _{CC} = 2.7V, I _{COM} = 100mA, V _{NO} or V _{NC} = 0.8V, 2.0V | | 25 | | | 0.1 | nA |
| | | | | Full | | | 0.1 | |
| NO or NC Off Leak- age Current ⁽⁶⁾ | I _{NO(OFF)} or I _{NC(OFF)} | V _{CC} = 3.3V, V _{COM} = 0V V _{NO} or V _{NC} = +2.0V | | 25 | -1 | | 1 | |
| | | | | Full | -10 | | 10 | |
| COM On Leakage Current ⁽⁶⁾ | I _{COM(ON)} | V _{CC} = 3.3V, V _{COM} = +2.0V V _{NO} or V _{NC} = +2.0V | | 25 | -2 | | 2 | |
| | | | | Full | -20 | | 20 | |



Electrical Specifications - Single +3.3V Supply (continued)

(V_{CC} = +3.3V ± 10%, GND = 0V, V_{IH} = 1.4V, V_{IL} = 0.5V)

| Parameter | Symbol | Conditions | Temp. (°C) | Min. ⁽¹⁾ | Typ. ⁽²⁾ | Max. ⁽¹⁾ | Units |
|--------------------------------------|--------------------------|---|------------|---------------------|---------------------|---------------------|-------|
| Logic Input | | | | | | | |
| Input High Voltage | V _{IH} | Guaranteed Logic High Level | Full | 1.4 | | | V |
| Input Low Voltage | V _{IL} | Guaranteed Logic LowLevel | | | | 0.5 | |
| Input Current with Volt- age High | I _{INH} | V _{IN} = 1.4V, all others = 0.5V | | −1 | | 1 | μA |
| Input Current with Volt- age Low | I _{INL} | V _{IN} = 0.5V, all others = 1.4V | | −1 | | 1 | |
| Dynamic | | | | | | | |
| Turn-On-Time | t _{ON} | V _{CC} = 3.3V, V _{NO} or V _{NC} = 2.0V, Figure 1 | 25 | | | 20 | ns |
| | | | Full | | | 20 | |
| Turn-Off-Time | t _{OFF} | | 25 | | | 10 | |
| | | | Full | | | 15 | |
| Charge Injection ⁽³⁾ | Q | C _L = 1nF, V _{GEN} = 0V, R _{GEN} = 0Ω, Figure 2 | 25 | | 40 | | pC |
| Off Isolation ⁽⁷⁾ | O _{IRR} | R _L = 50Ω, f = 100 KHz, Figure 3 | | | -27 | | dB |
| CrossTalk ⁽⁸⁾ | X _{TALK} | R _L = 50Ω f = 100 KHz, Figure 4 | | | -41 | | |
| NC or NO Capacitance | C _{NC/NO (OFF)} | f = 1MHz, Figure 5 | | | 90 | | pF |
| COM Off Capacitance | C _{COM(OFF)} | | | | 90 | | |
| COM On Capacitance | C _{COM(ON)} | f = 1MHz, Figure 6 | | | 240 | | |
| Supply | | | | | | | |
| Power-Supply Range | V _{CC} | | Full | 1.5 | | 3.6 | V |
| Positive Supply Current | I _{CC} | V _{CC} = 3.6V, V _{IN} = 0V or V _{CC} | | | | 100 | nA |

Notes:

1. The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4. DR_{ON} = R_{ON} max. - R_{ON} min.
5. Flatness is defined as the difference between the maximum and minimum value of On-Resistance measured.
6. Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
7. Off Isolation = 20log₁₀ [V_{COM} / (V_{NO} or V_{NC})]. See Figure 4.
8. Between any two switches. See Figure 5.



Electrical Specifications - Single +2.5V Supply ($V_{CC} = +2.5V \pm 10\%$, $GND = 0V$, $V_{IH} = 1.4V$, $V_{IL} = 0.5V$)

| Parameter | Symbol | Conditions | Temp. (°C) | Min. ⁽¹⁾ | Typ. ⁽²⁾ | Max. ⁽¹⁾ | Units |
|---|-----------------------|---|------------|---------------------|---------------------|---------------------|-------|
| Analog Switch | | | | | | | |
| Analog Signal Range ⁽³⁾ | V _{ANALOG} | | | 0 | | V _{CC} | V |
| On-Resistance | R _{ON} | V _{CC} = 2.5V, I _{COM} = −8mA, V _{NO} or V _{NC} = 1.8V | 25 | | | 0.5 | Ω |
| | | | Full | | | 0.55 | |
| On-Resistance Match Between Channels ⁽⁴⁾ | ΔR _{ON} | V _{CC} = 2.5V, I _{COM} = −8mA, V _{NO} or V _{NC} = 0.8V, 1.8V | 25 | | | 0.09 | |
| | | | Full | | | 0.09 | |
| On-Resistance Flatness ⁽⁵⁾ | R _{FLAT(ON)} | | 25 | | | 0.02 | |
| | | | Full | | | 0.02 | |
| Dynamic | | | | | | | |
| Turn-On-Time | t _{ON} | V _{CC} = 2.5V, V _{NO} or V _{NC} = 1.8V, Figure 1 | 25 | | | 30 | ns |
| | | | Full | | | 30 | |
| Turn-Off-Time | t _{OFF} | | 25 | | | 15 | |
| | | | Full | | | 15 | |
| Charge Injection ⁽³⁾ | Q | C _L = 1nF, V _{GEN} = 0V, R _{GEN} = 0Ω, Figure 2 | 25 | | 40 | | pC |
| Logic Input | | | | | | | |
| Input High Voltage | V _{IH} | Guaranteed Logic High Level | Full | 1.4 | | | V |
| Input Low Voltage | V _{IL} | Guaranteed Logic LowLevel | Full | | | 0.5 | |
| Input High Current | I _{INH} | V _{IN} = 1.4V, all others = 0.5V | Full | −1 | | 1 | μA |
| Input Low Current | I _{INL} | V _{IN} = 0.5V, all others = 1.4V | Full | −1 | | 1 | |

Notes:

1. The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4. $\Delta R_{ON} = R_{ON} \text{ max.} - R_{ON} \text{ min.}$
5. Flatness is defined as the difference between the maximum and minimum value of On-Resistance measured.



Electrical Specifications - Single +1.8V Supply

(V_{CC} = +1.8V ± 10%, GND = 0V, V_{IH} = 1.4V, V_{IL} = 0.5V)

| Parameter | Symbol | Conditions | Temp. (°C) | Min.(1) | Typ. (2) | Max. (1) | Units |
|---|-----------------------|--|------------|---------|----------|-----------------|-------|
| Analog Switch | | | | | | | |
| Analog Signal Range ⁽³⁾ | V _{ANALOG} | | | 0 | | V _{CC} | V |
| On-Resistance | R _{ON} | V _{CC} = 1.8V, I _{COM} = −4mA, V _{NO} or V _{NC} = 1.5V | 25 | | | 0.6 | Ω |
| | | | Full | | | 0.6 | |
| On-Resistance Match Between Channels ⁽⁴⁾ | ΔR _{ON} | V _{CC} = 1.8V, I _{COM} = −4mA, V _{NO} or V _{NC} = 0.8V, 1.5V | 25 | | | 0.07 | |
| | | | Full | | | 0.09 | |
| On-Resistance Flatness ⁽⁵⁾ | R _{FLAT(ON)} | | 25 | | | 0.8 | |
| | | | Full | | | 0.8 | |
| Dynamic | | | | | | | |
| Turn-On-Time | t _{ON} | V _{CC} = 1.8V, V _{NO} or V _{NC} = 1.5V, Figure 1 | 25 | | | 50 | ns |
| | | | Full | | | 50 | |
| Turn-Off-Time | t _{OFF} | | 25 | | | 25 | |
| | | | Full | | | 25 | |
| Charge Injection ⁽³⁾ | Q | C _L = 1nF, V _{GEN} = 0V, R _{GEN} = 0Ω, Figure 2 | 25 | | 36 | | pC |
| Logic Input | | | | | | | |
| Input High Voltage | V _{IH} | Guaranteed Logic High Level | Full | 1.4 | | | V |
| Input Low Voltage | V _{IL} | Guaranteed Logic LowLevel | Full | | | 0.5 | |
| Input High Current | I _{INH} | V _{IN} = 1.4V, all others = 0.5V | Full | −1 | | 1 | μA |
| Input Low Current | I _{INL} | V _{IN} = 0.5V, all others = 1.4V | Full | −1 | | 1 | |

Notes:

1. The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4. ΔR_{ON} = R_{ON} max. - R_{ON} min.
5. Flatness is defined as the difference between the maximum and minimum value of On-Resistance measured.

Test Circuits/Timing Diagrams




Figure 1. Switching Time




Figure 2. Charge Injection




Figure 3. Off Isolation








Figure 4. Crosstalk

Test Circuits/Timing Diagrams (continued)

Figure 5. Channel-Off Capacitance

Figure 6. Channel-On Capacitance
Packaging Mechanical: 6-Pin TDFN (ZC)


Packaging Mechanical: 6-Pin SOT-23 (T)

Ordering Information

| Ordering Code | Package Code | Package Description | Top Mark |
|---------------|--------------|----------------------------------|----------|
| PI3A3159TX | T | 6-pin, SOT-23 | ZG |
| PI3A3159TEX | T | Pb-free & Green, 6-pin, SOT-23 | ZG |
| PI3A3159ZCEX | ZC | Pb-free & Green, 6-contact, TDFN | ZG |

Notes:

- Thermal characteristics can be found on the company web site at <http://www.pericom.com/packaging/>
- X = Tape/Reel