

Technical drawings of a cable assembly, showing side, end, and detail views with dimensions and labels.

Side View (Left): Shows the cable profile with dimensions $B \pm .010 (.25)$ and $F \text{ REF.}$. Labels **E** and **D** are present.

End View (Middle): Shows the cable cross-section with dimensions $A \pm .010 (.25)$ and G . Label **C** is present.

Detail "A" (Right): Shows the cable cross-section with dimensions $18.0 (482.6)$ and H . Labels **PANDUIT** and **DETAIL "A"** are present.

PANDUIT * PART NO.	BUNDLE DIA.		A	B	C	D	E	F	G	H	MINIMUM LOOP TENSILE lbs. (N)	CROSS SECTION	WEIGHT (W/O RIBBON) lbs (g)/100 pcs
	MIN. IN. (mm)	MAX. IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)	IN. (mm)			
PLT1M-XMR	.02 (.5)	.82 (20.8)	.036 (.9)	.100 (2.5)	.175 (4.4)	.154 (3.9)	.185 (4.7)	4.0 (102)	4.5 (114)	5.25 (133)	18 (80)	MINIATURE	.06 (29)
PLT1.5M-XMR	.02 (.5)	1.31 (33.3)	.036 (.9)	.100 (2.5)	.175 (4.4)	.154 (3.9)	.185 (4.7)	5.6 (142)	6.0 (152)	6.8 (173)	18 (80)	MINIATURE	.08 (38)

- *1) SEE CURRENT PRICE SHEET FOR PART MATERIAL & COLOR SUFFIX DESIGNATIONS.
- 2) STANDARD PACKAGING: 5000 STRAPS PER REEL, 2 REELS PER CARTON.
- 3) PACKAGED FOR USE WITH FULLY AUTOMATIC CABLE TIE INSTALLATION SYSTEMS.
- 4) RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORIES INC.

PANDUIT CORP. TINLEY PARK, ILLINOIS

XMR PAN-TY CABLE TIES
PACKAGED FOR AUTOMATIC TOOLS

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) $\pm .10$ (.5) (.XXX) $\pm .020$ (.51)
(.XX) $\pm .02$ (.5) ANGLES $\pm$ -----

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
KJL

MAT'L:

SCALE

NONE

DATE	6/16/88
------	---------

NYLON 6.6

DRAFTING NO.

SS - 18422

DWG
A
SIZE

10	3/29/05	ERW		CORRECTED PLT1.5M WEIGHT. WAS .09 (38)	18422	10				
--	----	--		UPDATED ROLL ARTWORK	----	--				
9	10/19/04	ERW	JVL	UPDATED NOTE 3	18422	9	JVL			
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP		