



DATA SHEET

PS200~PS2010

PLASTIC SILICON RECTIFIER


VOLTAGE 50 to 1000 Volts CURRENT - 2.0 Amperes

FEATURES

- Low cost
- High current capability
- Plastic package has Underwriters Laboratories Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- 2.0 ampere operation at $T_A = 55^\circ\text{C}$ with no thermal runaway
- Exceeds environmental standards of MIL-S-19500/228
- Low leakage

MECHANICAL DATA

Case: Molded plastic, DO-15
 Terminals: Axial leads, solderable to MIL-STD-202, Method 208
 Polarity: Color Band denotes cathode end
 Mounting Position: Any
 Weight: 0.015 ounce, 0.4 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Resistive or inductive load, 60Hz.

	PS200	PS201	PS202	PS204	PS206	PS208	PS2010	UNIT
Maximum Recurrent Peak Reverse Voltage	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	50	100	200	400	600	800	1000	V
Maximum Average Forward Current .375"(9.5mm) lead length at $T_A = 60^\circ\text{C}$	2.0							A
Peak Forward Surge Current, IFM (surge): 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	70.0							A
Maximum Forward Voltage at 2.0A DC	1.10							V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_A = 25^\circ\text{C}$	5.0							μA
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_A = 100^\circ\text{C}$	500							μA
Typical Junction capacitance (Note 1)	25.0							pF
Typical Junction Resistance (Note 2) $R_{\theta JA}$	25.0							$^\circ\text{C}/\text{W}$
Operating and Storage Temperature Range T_J, T_{STG}	-55 to +150							$^\circ\text{C}$

NOTES: 1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC

2. Thermal resistance from junction to ambient and from junction to lead length 0.375"(9.5mm) P.C.B. mounted



RATING AND CHARACTERISTIC CURVES




Fig.2- TYPICAL FORWARD CHARACTERISTICS




Fig.2- PEAK FORWARD SURGE CURRENT




Fig.3- FORWARD CURRENT DERATING CURVE




Fig.4- TYPICAL JUNCTION CAPACITANCE