



 Select Your Country/Region 

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

APC PROTECTNET RS232 9 PIN MALE TO FEMALE

Standalone data-line surge suppression for network, telecommunication and PC system protection.

Includes: User Manual

Part Number : **PS9-DCE**

 [Compare Models](#)

 [Email Technical Specifications](#)

 [Printer Friendly](#)

Additional Information

[Product Overview](#)

[Product Distribution](#)



Technical Specifications

Surge Protection and Filtering

Peak Current Common Mode	0.20 kAmps
NM Surge Response Time (ns)	1 ns
Data Lines Protected (multi-line only)	1-9
Let Through Voltage Rating	< 30

Features:

- Catastrophic Event Protection

Physical

Net Weight	0.13 lbs. (0.06 kg)
Maximum Height	3.00 inches (76 mm)
Maximum Width	1.40 inches (36 mm)
Maximum depth	0.60 inches (15 mm)
Shipping Weight	0.22 lbs. (0.10 kg)
Shipping Height	6.50 inches (165 mm)
Shipping Width	1.75 inches (44 mm)
Shipping Depth	6.50 inches (165 mm)

Master Carton Units	40.00
SCC Codes	10731304000515
Color	Beige

Environmental

Operating Environment	-15 - 45 °C (5 - 113 °F)
Operating Relative Humidity	0 - 95%
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%

Conformance

Regulatory Approvals	UL 497B,UL Listed
Standard Warranty	Lifetime

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)