



 Select Your Country/Region 

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

APC PROTECTNET RS232 9 PIN MALE TO FEMALE

Standalone data-line surge suppression for network, telecommunication and PC system protection.

Includes: User Manual

Part Number : **PS9-DCE**

 [Compare Models](#)

 [Email Technical Specifications](#)

 [Printer Friendly](#)

Additional Information

[Product Overview](#)

[Product Distribution](#)



Technical Specifications

Surge Protection and Filtering

| | |
|---|------------|
| Peak Current Common Mode | 0.20 kAmps |
| NM Surge Response Time (ns) | 1 ns |
| Data Lines Protected (multi-line only) | 1-9 |
| Let Through Voltage Rating | < 30 |

Features:

- Catastrophic Event Protection

Physical

| | |
|-----------------|----------------------|
| Net Weight | 0.13 lbs. (0.06 kg) |
| Maximum Height | 3.00 inches (76 mm) |
| Maximum Width | 1.40 inches (36 mm) |
| Maximum depth | 0.60 inches (15 mm) |
| Shipping Weight | 0.22 lbs. (0.10 kg) |
| Shipping Height | 6.50 inches (165 mm) |
| Shipping Width | 1.75 inches (44 mm) |
| Shipping Depth | 6.50 inches (165 mm) |

| | |
|---------------------|----------------|
| Master Carton Units | 40.00 |
| SCC Codes | 10731304000515 |
| Color | Beige |

Environmental

| | |
|-----------------------------|--------------------------|
| Operating Environment | -15 - 45 °C (5 - 113 °F) |
| Operating Relative Humidity | 0 - 95% |
| Storage Temperature | -15 - 45 °C (5 - 113 °F) |
| Storage Relative Humidity | 0 - 95% |

Conformance

| | |
|----------------------|-------------------|
| Regulatory Approvals | UL 497B,UL Listed |
| Standard Warranty | Lifetime |

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)