



 Select Your Country/Region 

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

APC PROTECTNET RS232 SER/PAR 25 PIN

Standalone data-line surge suppression for network, telecommunication and PC system protection.

Includes: User Manual

Part Number : **PSP25**

 [Compare Models](#)

 [Email Technical Specifications](#)

 [Printer Friendly](#)

Additional Information

[Product Overview](#)

[User Manual & Installation Guides](#)

[Product Distribution](#)



Technical Specifications

Surge Protection and Filtering

Peak Current Normal Mode	0.20 kAmps
Peak Current Common Mode	0.20 kAmps
NM Surge Response Time (ns)	1 ns
Dataline protection	DB25
Data Lines Protected (multi-line only)	1-25
Let Through Voltage Rating	< 40

Features:

- Catastrophic Event Protection

Physical

Net Weight	0.11 lbs. (0.05 kg)
Maximum Height	2.45 inches (62 mm)
Maximum Width	2.22 inches (56 mm)
Maximum depth	0.65 inches (17 mm)
Shipping Weight	0.23 lbs. (0.10 kg)
Shipping Height	4.10 inches (104 mm)
Shipping Width	3.55 inches (90 mm)
Shipping Depth	1.15 inches (29 mm)
Master Carton Units	144.00

Master Carton Weight	13.20 lbs.
SCC Codes	1073130440000
Color	Beige
Units per Pallet	750.00

Environmental

Operating Environment	-15 - 45 °C (5 - 113 °F)
Operating Relative Humidity	0 - 95%
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%

Conformance

Regulatory Approvals	UL 497B,UL Listed
Standard Warranty	Lifetime

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)