

Sensors

Phototransistor, surface mount type

RPM-075PT

Quite new phototransistor which peak sensitivity is designed as same level as human eye. Best sensor to detect illuminance. (Peak sensitivity is 600nm.) Small and light weight package which can be used for reflow soldering and Pd free soldering.


●Application

Control of lighting cellular phones, LCD displays, etc.
Control of strobe. (DSC, camcorder, etc.)

●Features

- 1) Best sensor to detect illuminance.
(Peak sensitivity is 600nm.)
- 2) Small (2125) and light weight package (3mg) which can be used for reflow soldering and Pd free soldering.
- 3) Linear against wide range of illuminance from a few Lx to 10000Lx over.
- 4) Use Si good for an environ ment. (not CdS)

●External dimensions (Units : mm)



●Absolute maximum ratings (Ta=25°C)

| Parameter | Symbol | Limits | Unit |
|-----------------------------|------------------|----------|------|
| Collector-emitter voltage | V _{CEO} | 20 | V |
| Emitter-collector voltage | V _{ECO} | 5 | V |
| Collector current | I _c | 10 | mA |
| Collector power dissipation | P _c | 50 | mW |
| Operating temperature | T _{opr} | -30~+85 | °C |
| Storage temperature | T _{stg} | -40~+100 | °C |

●Electrical and optical characteristics (Ta=25°C)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Conditions |
|--------------------------------------|----------------------|------|------|------|------|--|
| Light current | I _c | 0.25 | 0.4 | 0.6 | mA | V _{CE} =5V, E=500Lx |
| Dark current | I _{CEO} | - | - | 0.5 | μA | V _{CE} =10V (Black box) |
| Peak sensitivity wavelength | λ _p | - | 600 | - | nm | - |
| Collector-emitter saturation voltage | V _{CE(sat)} | - | - | 0.4 | V | I _c =0.1mA, E=500Lx |
| Half-angle | θ _{1/2} | - | ±60 | - | deg | - |
| Response time | tr-tf | - | 10 | - | μs | V _{CC} =5V, I _c =1mA, R _L =100Ω |

Sensors

●Electrical and optical characteristic curves




Fig.1 Collector current-Illuminance




Fig.2 Output characteristics




Fig.3 Relative output-Ambient temperature




Fig.4 Dark current-Ambient temperature




Fig.7 Spectral sensitivity characteristics




Fig.6 Collector dissipation-Ambient temperature




Fig.7 Response time-Collector current




Fig.8 Directional pattern




Fig.9 Directional pattern

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document use silicon as a basic material.
Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.