



FEATURES

Power dissipation


$P_{CM} : 0.625 \text{ W} (T_{amb}=25^{\circ}\text{C})$

Collector current

$I_{CM} : 0.5 \text{ A}$

Collector-base voltage

$V_{(BR)CBO} : 40 \text{ V}$



ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100 \mu\text{A}, I_E=0$	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=0.1 \text{ mA}, I_B=0$	25			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100 \mu\text{A}, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=40 \text{ V}, I_E=0$			0.1	μA
Collector cut-off current	I_{CEO}	$V_{CE}=20 \text{ V}, I_B=0$			0.2	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=3 \text{ V}, I_C=0$			0.1	μA
DC current gain(note)	$H_{FE(1)}$	$V_{CE}=1 \text{ V}, I_C=50\text{mA}$	85		300	
	$H_{FE(2)}$	$V_{CE}=1 \text{ V}, I_C=500\text{mA}$	50			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=500\text{mA}, I_B=50 \text{ mA}$			0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=500\text{mA}, I_B=50 \text{ mA}$			1.2	V
Base-emitter voltage	V_{BE}	$I_E=100\text{mA}$			1.4	V
Transition frequency	f_T	$V_{CE}=6 \text{ V}, I_C=20\text{mA}$ $f=30\text{MHz}$	150			MHz

CLASSIFICATION OF $H_{FE(1)}$

Rank	B	C	D
Range	85-160	120-200	160-300

