查询SB8100CT供应商 捷多邦，专业PCB打样工厂，24小时加急出货

PANJIT SEMI CONDUCTOR

DATA SHEET

SB820CT~SB8100CT

SCHOTTKY BARRIER RECTIFIERS

VOLTAGE 20 to 100 Volts CURRENT - 8 Ampere

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency.
- Low forwrd voltge, high current capability
- High surge capacity.
- For use in low voltage,high frequency inverters free wheeling , and polarlity protection applications.

MECHANICAL DATA

Case: TO-220AB full molded plastic package

Terminals: Lead solderable per MIL-STD-202, Method 208

Polarity: As marked.

Mounting Position: Any

Weight: 0.08 ounces, 2.24grams.

TO-220AB

Unit: inch (mm)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

	SB820CT	SB830CT	SB840CT	SB850CT	SB860CT	SB880CT	SB8100CT	UNITS
Maximum Recurrent Peak Reverse Voltage	20	30	40	50	60	80	100	V
Maximum RMS Voltage	14	21	28	35	42	56	70	V
Maximum DC Blocking Voltage	20	30	40	50	60	80	100	V
Maximum Average Forward Rectified Current at Tc=100°C	8							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	150							A
Maximum Forward Voltage at 4.0A per element	0.55			0.75		0.85		V
Maximum DC Reverse Current at Tc=25°C DC Blocking Voltage per element Tc=100°C	0.5 50							mA
Typical Thermal Resistance Note RθJA	60							°C/W
Operating and Storage Temperature Range	-50 to +125							°C

NOTES:

1. Thermal Resistance Junction to Ambient .

找PDF 维库一下 pdf.dzsc.com

RATING AND CHARACTERISTIC CURVES



Fig.1- FORWARD CURRENT DERATING CURVE



Fig.2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC



Fig.3- TYPICAL REVERSE CHARACTERISTIC



Fig.4- MAXIMUM NON-REPETITIVE SURGE CURRENT



Fig.5- TYPICAL JUNCTION CAPACITANCE