



---

# ***DISCRETE POWER DIODES and THYRISTORS***

## **DATA BOOK**

---



## SD703C..L SERIES

### FAST RECOVERY DIODES

### Hockey Puk Version

#### Features

- High power FAST recovery diode series
- 2.0 to 3.0  $\mu$ s recovery time
- High voltage ratings up to 2500V
- High current capability
- Optimized turn on and turn off characteristics
- Low forward recovery
- Fast and soft reverse recovery
- Press-puk encapsulation
- Case style conform to JEDEC DO-200AB (B-PUK)
- Maximum junction temperature 150°C

700A  
790A

#### Typical Applications

- Snubber diode for GTO
- High voltage free-wheeling diode
- Fast recovery rectifier applications



case style DO-200AB (B-PUK)

#### Major Ratings and Characteristics

| Parameters       | SD703C..L    |              | Units   |
|------------------|--------------|--------------|---------|
|                  | S20          | S30          |         |
| $I_{F(AV)}$      | 700          | 790          | A       |
| @ $T_{hs}$       | 55           | 55           | °C      |
| $I_{F(RMS)}$     | 1320         | 1470         | A       |
| $I_{FSM}$ @ 50Hz | 9300         | 9600         | A       |
| @ 60Hz           | 9730         | 10050        | A       |
| $V_{RRM}$ range  | 1200 to 2500 | 1200 to 2500 | V       |
| $t_{rr}$         | 2.0          | 3.0          | $\mu$ s |
| @ $T_J$          | 25           | 25           | °C      |
| $T_J$            | - 40 to 150  |              | °C      |

## SD703C..L Series

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

| Type number | Voltage Code | $V_{RRM}$ , maximum repetitive peak reverse voltage<br>V | $V_{RSM}$ , maximum non-repetitive peak rev. voltage<br>V | $I_{RRM}$ max.<br>@ $T_J = T_J$ max.<br>mA |
|-------------|--------------|----------------------------------------------------------|-----------------------------------------------------------|--------------------------------------------|
| SD703C..L   | 12           | 1200                                                     | 1300                                                      | 50                                         |
|             | 16           | 1600                                                     | 1700                                                      |                                            |
|             | 20           | 2000                                                     | 2100                                                      |                                            |
|             | 25           | 2500                                                     | 2600                                                      |                                            |

#### Forward Conduction

| Parameter           |                                                               | SD703C..L |           | Units              | Conditions                                                                                           |                       |                                                                           |  |
|---------------------|---------------------------------------------------------------|-----------|-----------|--------------------|------------------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------|--|
|                     |                                                               | S20       | S30       |                    |                                                                                                      |                       |                                                                           |  |
| I <sub>F(AV)</sub>  | Max. average forward current<br>@ case temperature            | 700 (365) | 790 (400) | A                  | 180° conduction, half sine wave                                                                      |                       |                                                                           |  |
|                     |                                                               | 55 (85)   | 55 (85)   | °C                 | Double side (single side) cooled                                                                     |                       |                                                                           |  |
| I <sub>F(RMS)</sub> | Max. RMS forward current                                      | 1320      | 1470      | A                  | @ 25°C heatsink temperature double side cooled                                                       |                       |                                                                           |  |
| I <sub>FSM</sub>    | Max. peak, one-cycle forward,<br>non-repetitive surge current | 9300      | 9600      | A                  | t = 10ms                                                                                             | No voltage            | Sinusoidal half wave,<br><br>Initial T <sub>j</sub> = T <sub>j</sub> max. |  |
|                     |                                                               | 9730      | 10050     |                    | t = 8.3ms                                                                                            | reapplied             |                                                                           |  |
|                     |                                                               | 7820      | 8070      |                    | t = 10ms                                                                                             | 100% V <sub>RRM</sub> |                                                                           |  |
|                     |                                                               | 8190      | 8450      |                    | t = 8.3ms                                                                                            | reapplied             |                                                                           |  |
| I <sup>2</sup> t    | Maximum I <sup>2</sup> t for fusing                           | 432       | 460       | KA <sup>2</sup> s  | t = 10ms                                                                                             | No voltage            |                                                                           |  |
|                     |                                                               | 395       | 420       |                    | t = 8.3ms                                                                                            | reapplied             |                                                                           |  |
|                     |                                                               | 306       | 326       |                    | t = 10ms                                                                                             | 100% V <sub>RRM</sub> |                                                                           |  |
|                     |                                                               | 279       | 297       |                    | t = 8.3ms                                                                                            | reapplied             |                                                                           |  |
| I <sup>2</sup> √t   | Maximum I <sup>2</sup> √t for fusing                          | 4320      | 4600      | KA <sup>2</sup> √s | t = 0.1 to 10ms, no voltage reapplied                                                                |                       |                                                                           |  |
| V <sub>F(TO)1</sub> | Low level value of threshold<br>voltage                       | 1.00      | 0.95      | V                  | (16.7% × π × I <sub>F(AV)</sub> < I < π × I <sub>F(AV)</sub> ), T <sub>j</sub> = T <sub>j</sub> max. |                       |                                                                           |  |
| V <sub>F(TO)2</sub> | High level value of threshold<br>voltage                      | 1.11      | 1.05      |                    | (I > π × I <sub>F(AV)</sub> ), T <sub>j</sub> = T <sub>j</sub> max.                                  |                       |                                                                           |  |
| r <sub>f1</sub>     | Low level value of forward<br>slope resistance                | 0.80      | 0.60      | mΩ                 | (16.7% × π × I <sub>F(AV)</sub> < I < π × I <sub>F(AV)</sub> ), T <sub>j</sub> = T <sub>j</sub> max. |                       |                                                                           |  |
| r <sub>f2</sub>     | High level value of forward<br>slope resistance               | 0.76      | 0.56      |                    | (I > π × I <sub>F(AV)</sub> ), T <sub>j</sub> = T <sub>j</sub> max.                                  |                       |                                                                           |  |
| V <sub>FM</sub>     | Max. forward voltage drop                                     | 2.20      | 1.85      | V                  | I <sub>pk</sub> = 1500A, T <sub>j</sub> = T <sub>j</sub> max, t <sub>p</sub> = 10ms sinusoidal wave  |                       |                                                                           |  |

#### Recovery Characteristics

| Code | $T_J = 25^\circ\text{C}$<br>typical $t_{rr}$<br>@ 25% $I_{RRM}$<br>(μs) | Test conditions                 |                   |              |                                     | Max. values @ $T_J = 150^\circ\text{C}$ |                 |  |
|------|-------------------------------------------------------------------------|---------------------------------|-------------------|--------------|-------------------------------------|-----------------------------------------|-----------------|--|
|      |                                                                         | $I_{pk}$<br>Square Pulse<br>(A) | $di/dt$<br>(A/μs) | $V_r$<br>(V) | $t_{rr}$<br>@ 25% $I_{RRM}$<br>(μs) | $Q_{rr}$<br>(μC)                        | $I_{rr}$<br>(A) |  |
| S20  | 2.0                                                                     | 1000                            | 50                | -50          | 3.5                                 | 240                                     | 110             |  |
| S30  | 3.0                                                                     | 1000                            | 50                | -50          | 5.0                                 | 380                                     | 130             |  |




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Current Ratings Characteristics




Fig. 6 - Current Ratings Characteristics




Fig. 7 - Current Ratings Characteristics




Fig. 8 - Current Ratings Characteristics




Fig. 9 - Forward Power Loss Characteristics




Fig. 10 - Forward Power Loss Characteristics




Fig. 11 - Forward Power Loss Characteristics




Fig. 12 - Forward Power Loss Characteristics




Fig. 13 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 14 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 15 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 16 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 17 - Forward Voltage Drop Characteristics




Fig. 18 - Forward Voltage Drop Characteristics




Fig. 19 - Thermal Impedance  $Z_{thj-hs}$  Characteristic

SD703C..L Series




Fig. 20 - Typical Forward Recovery Characteristics




Fig. 21 - Typical Forward Recovery Characteristics




Fig. 22 - Recovery Time Characteristics




Fig. 23 - Recovery Charge Characteristics




Fig. 24 - Recovery Current Characteristics




Fig. 25 - Recovery Time Characteristics




Fig. 26 - Recovery Charge Characteristics




Fig. 27 - Recovery Current Characteristics




Fig. 28 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 29 - Frequency Characteristics




Fig. 30 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 31 - Frequency Characteristics




Fig. 32 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 33 - Frequency Characteristics

## SD703C..L Series

---




Fig. 34 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 35 - Frequency Characteristics




Fig. 36 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 37 - Frequency Characteristics




Fig. 38 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 39 - Frequency Characteristics

## Thermal and Mechanical Specifications

| Parameter           |                                                    | SD703C...L       |     | Units     | Conditions                                                       |
|---------------------|----------------------------------------------------|------------------|-----|-----------|------------------------------------------------------------------|
|                     |                                                    | S20              | S30 |           |                                                                  |
| T <sub>j</sub>      | Max. junction operating temperature range          | -40 to 150       |     | °C        |                                                                  |
| T <sub>stg</sub>    | Max. storage temperature range                     | -40 to 150       |     |           |                                                                  |
| R <sub>thj-hs</sub> | Max. thermal resistance, case junction to heatsink | 0.092<br>0.046   |     | K/W       | DCoperation single side cooled<br>DCoperation double side cooled |
| F                   | Mounting force, ± 10%                              | 9800<br>(1000)   |     | N<br>(Kg) |                                                                  |
| wt                  | Approximate weight                                 | 250              |     | g         |                                                                  |
| Case style          |                                                    | DO-200AB (B-PUK) |     |           | See Outline Table                                                |

 $\Delta R_{thJ-hs}$  Conduction

(The following table shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction |             | Rectangular conduction |             | Units | Conditions               |
|------------------|-----------------------|-------------|------------------------|-------------|-------|--------------------------|
|                  | Single Side           | Double Side | Single Side            | Double Side |       |                          |
| 180°             | 0.011                 | 0.011       | 0.008                  | 0.008       | K/W   | $T_J = T_J \text{ max.}$ |
| 120°             | 0.013                 | 0.014       | 0.013                  | 0.013       |       |                          |
| 90°              | 0.017                 | 0.017       | 0.018                  | 0.018       |       |                          |
| 60°              | 0.024                 | 0.025       | 0.026                  | 0.026       |       |                          |
| 30°              | 0.043                 | 0.043       | 0.043                  | 0.044       |       |                          |

## Ordering Information Table

| Device Code |                                                                    |          |          |           |            |          |
|-------------|--------------------------------------------------------------------|----------|----------|-----------|------------|----------|
| <b>SD</b>   | <b>70</b>                                                          | <b>3</b> | <b>C</b> | <b>25</b> | <b>S20</b> | <b>L</b> |
| ①           | ②                                                                  | ③        | ④        | ⑤         | ⑥          | ⑦        |
| <b>1</b>    | - Diode                                                            |          |          |           |            |          |
| <b>2</b>    | - Essential part number                                            |          |          |           |            |          |
| <b>3</b>    | - 3 = Fast recovery                                                |          |          |           |            |          |
| <b>4</b>    | - C = Ceramic Puk                                                  |          |          |           |            |          |
| <b>5</b>    | - Voltage code: Code x 100 = $V_{RRM}$ (See Voltage Ratings table) |          |          |           |            |          |
| <b>6</b>    | - $t_{rr}$ code                                                    |          |          |           |            |          |
| <b>7</b>    | - L = Puk Case DO-200AB (B-PUK)                                    |          |          |           |            |          |

SD703C..L Series

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics