









## Standard Soldering Tip Cartridges

- Used with the MFR-HPS Soldering Hand-piece & PS-800 CA2
- Designed to deliver outstanding performance for point-to-point production soldering applications.
- The two part hand piece - heater coil and tip design provides a low cost solution to demanding production soldering applications

SFV-CH10	Chisel Solder Tip, 30° 1.0mm (.04")	 <p>0.04" 1.0mm</p> <p>0.43" 11.0mm</p>
SFV-CN05	Conical Solder Tip, 0.5mm (.02")	 <p>0.02" 0.5mm</p> <p>0.34" 8.5mm</p>
SFV-CH20	Chisel Solder Tip, 30° 2.0mm (.08")	 <p>0.8" 2.0mm</p> <p>0.39" 10.0mm</p>
SFV-CH25	Chisel Solder Tip, 30° 2.5mm (.10")	 <p>0.1" 2.5mm</p> <p>0.43" 11.0mm</p>
SFV-CH50	Chisel Solder Tip, 30° 5.0mm (.20")	 <p>0.2" 5.0mm</p> <p>0.4" 10.0mm</p>
SFV-CHL14	Conical Solder Tip, 60° Long Reach 1.4mm (0.56")	 <p>0.056" 1.4mm</p> <p>0.59" 15.0mm</p>
SFV-CNL10	Conical Solder Tip Long Reach, 1.0mm (.04")	 <p>0.04" 1.0mm</p> <p>0.51" 13.0mm</p>
SFV-CNL04	Conical solder Tip Long Reach, 0.4mm (.016")	 <p>0.016" 0.4mm</p> <p>0.53" 13.6mm</p>

Soldering Tip Cartridges "F" series are designed for lead free solder , the system delivers power according to demand , light load or heavy thermal load with "Metcal Smart heat Technology" . Whilst keeping the temperature constant at nominally 380 C