



New Product

Si3473DV
Vishay Siliconix

P-Channel 12-V (D-S) MOSFET



PRODUCT SUMMARY		
V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A)
-12	0.023 @ V _{GS} = -4.5 V	-7.9
	0.029 @ V _{GS} = -2.5 V	-7.0
	0.041 @ V _{GS} = -1.8 V	-5.9

FEATURES

- TrenchFET® Power MOSFET: 1.8-V Rated
- Ultra Low On-Resistance

APPLICATIONS

- Load Switch
- PA Switch



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T _A = 25°C UNLESS OTHERWISE NOTED)					
Parameter	Symbol	5 secs	Steady State	Unit	
Drain-Source Voltage	V _{DS}	-12		V	
Gate-Source Voltage	V _{GS}	± 8			
Continuous Drain Current (T _J = 150°C) ^a	I _D	T _A = 25°C	- 7.9	-5.9	A
		T _A = 85°C	- 5.7	-4.3	
Pulsed Drain Current	I _{DM}	-20			
Continuous Diode Current (Diode Conduction) ^a	I _S	-1.7	-0.9		
Maximum Power Dissipation ^a	P _D	T _A = 25°C	2.0	1.1	W
		T _A = 85°C	1.0	0.6	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55 to 150		°C	

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient ^a	R _{thJA}	t ≤ 5 sec	45	62.5	°C/W
		Steady State	90	110	
Maximum Junction-to-Foot (Drain)	R _{thJF}	25	30		

Notes:
a. Surface Mounted on 1" x 1" FR4 Board.

Si3473DV

Vishay Siliconix

New Product





SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-0.40		-1	V
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -9.6 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -9.6 V, V _{GS} = 0 V, T _J = 85 °C			-5	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -5 V, V _{GS} = -4.5 V	-20			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = -4.5 V, I _D = -7.9 A		0.019	0.023	Ω
		V _{GS} = -2.5 V, I _D = -7.0 A		0.024	0.029	
		V _{GS} = -1.8 V, I _D = -3 A		0.033	0.041	
Forward Transconductance ^a	g _{fs}	V _{DS} = -5 V, I _D = -7.9 A		28		S
Diode Forward Voltage ^a	V _{SD}	I _S = -1.7 A, V _{GS} = 0 V		-0.7	-1.2	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = -6 V, V _{GS} = -4.5 V, I _D = -7.9 A		22	33	nC
Gate-Source Charge	Q _{gs}			3.2		
Gate-Drain Charge	Q _{gd}			5.8		
Turn-On Delay Time	t _{d(on)}	V _{DD} = -6 V, R _L = 6 Ω I _D ≅ -1 A, V _{GEN} = -4.5 V, R _G = 6 Ω		25	40	ns
Rise Time	t _r			50	75	
Turn-Off Delay Time	t _{d(off)}			130	200	
Fall Time	t _f			110	165	
Source-Drain Reverse Recovery Time	t _{rr}		I _F = -1.7 A, di/dt = 100 A/μs		65	

Notes







- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)









TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





New Product

Si3473DV
Vishay Siliconix

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

