查询SI7858DP供应商 捷多邦，专业PCB打样工厂，24小时加急出货

N-Channel 12-V (D-S) MOSFET

CHARACTERISTICS

- N-Channel Vertical DMOS
- Macro Model (Subcircuit Model)
- Level 3 MOS
- Apply for both Linear and Switching Application
- Accurate over the –55 to 125°C Temperature Range
- Model the Gate Charge, Transient, and Diode Reverse Recovery Characteristics

DESCRIPTION

The attached spice model describes the typical electrical characteristics of the n-channel vertical DMOS. The subcircuit model is extracted and optimized over the –55 to 125°C temperature ranges under the pulsed 0-to-5V gate drive. The saturated output impedance is best fit at the gate bias near the threshold voltage.

A novel gate-to-drain feedback capacitance network is used to model the gate charge characteristics while avoiding convergence difficulties of the switched C_{gd} model. All model parameter values are optimized to provide a best fit to the measured electrical data and are not intended as an exact physical interpretation of the device.

SUBCIRCUIT MODEL SCHEMATIC



This document is intended as a SPICE modeling guideline and does not constitute a commercial product data sheet. Designers should refer to the appropriate data sheet of the same number for guaranteed specification limits.

SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)					
Parameter	**Symbol**	**Test Conditions**	**Simulated Data**	**Measured Data**	**Unit**
Static					
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, I_D = 250µA	0.91		V
On-State Drain Current[a]	$I_{D(on)}$	$V_{DS} \geq 5V$, V_{GS} = 4.5V	1265		A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = 4.5V, I_D = 25A	0.0019	0.0024	Ω
		V_{GS} = 2.5V, I_D =20A	0.0031	0.0031	
Forward Transconductance[a]	g_{fs}	V_{DS} = 6V, I_D = 25A	142	130	S
Diode Forward Voltage[a]	V_{SD}	I_S = 2.9A, V_{GS} = 0V	0.76	0.75	V
Dynamic[b]					
Total Gate Charge	Q_g	V_{DS} = 6V, V_{GS} = 4.5V, I_D = 25A	42	40	nC
Gate-Source Charge	Q_{gs}		6.7	6.7	
Gate-Drain Charge	Q_{gd}		9.2	9.2	
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 6V, R_L = 6Ω $I_D \cong$ 1A, V_{GEN} = 4.5V, R_G = 6Ω	41	40	ns
Rise Time	t_r		58	40	
Turn-Off Delay Time	$t_{d(off)}$		66	140	
Fall Time	t_f		118	70	
Source-Drain Reverse Recovery Time	t_{rr}	I_F = 2.9A, di/dt = 100 A/µs	39	50	

Notes
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.

COMPARISON OF MODEL WITH MEASURED DATA (T_J=25°C UNLESS OTHERWISE NOTED)













Note: Dots and squares represent measured data.