



Specification Comparison

Vishay Siliconix

Si7900AEDN vs. Si7900EDN

Description: Dual N-Channel, 20-V (D-S) MOSFET with Common Drain
Package: PowerPAK® 1212
Pin Out: Identical

Part Number Replacements:

Si7900AEDN-T1 Replaces Si7900EDN-T1
 Si7900AEDN-T1—E3 (Lead Free version) Replaces Si7900EDN-T1

Summary of Performance:

The Si7900AEDN is the replacement for the original Si7900EDN; both parts perform identically including limits to the parametric tables below.

ABSOLUTE MAXIMUM RATINGS (T _A = 25 °C UNLESS OTHERWISE NOTED)					
Parameter	Symbol	Si7900AEDN	Si7900EDN	Unit	
Drain-Source Voltage	V _{DS}	20	20	V	
Gate-Source Voltage	V _{GS}	± 12	± 12		
Continuous Drain Current	T _A = 25 °C	I _D	8.5	9	A
	T _A = 85 °C		6.4	6.4	
Pulsed Drain Current	I _{DM}	30	30		
Continuous Source Current (MOSFET Diode Conduction)	I _S	2.9	2.9		
Power Dissipation	T _A = 25 °C	P _D	2.9	3.2	W
	T _A = 85 °C		3.1	1.7	
Operating Junction and Storage Temperature Range	T _J and T _{stg}	-55 to 150	-55 to 150	°C	
Maximum Junction-to-Ambient	R _{thJA}	40	38	°C/W	

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)									
Parameter	Symbol	Si7900AEDN			Si7900EDN			Unit	
		Min	Typ	Max	Min	Typ	Max		
Static									
Gate-Threshold Voltage	V _{G(th)}	0.4		0.9	0.4				V
Gate-Body Leakage	V _{GS} = 12 V	I _{GSS}		± 1			± 1		µA
	V _{GS} = 4.5 V			± 10			± 10		mA
Zero Gate Voltage Drain Current	I _{DSS}			1			1		µA
On-State Drain Current	V _{GS} = 4.5 V	I _{D(on)}	20		20				A
Drain-Source On-Resistance	V _{GS} = 4.5 V	r _{DS(on)}		0.020	0.026		0.020	0.026	Ω
	V _{GS} = 2.5 V			0.022	0.030		0.025	0.031	
	V _{GS} = 1.8 V			0.026	0.036		0.031	0.039	
Forward Transconductance	g _{fs}		25			25			S
Diode Forward Voltage	V _{SD}		0.65	1.1		0.65	1.1		V
Dynamic									
Total Gate Charge	Q _g		10.5	16		12.5	18		nC
Gate-Source Charge	Q _{gs}		1.9			2.7			
Gate-Drain Charge	Q _{gd}		1.8			2.7			
Switching									
Turn-On Time	t _{d(on)}		0.85	1.25		0.7	1.0		µs
	t _r		1.3	2.0		1.3	2.0		
Turn-Off Time	t _{d(off)}		8.6	13		5.5	8.0		
	t _f		4.29	6.5		5.5	8.0		