





SKW07N120

Fast IGBT in NPT-technology with soft, fast recovery anti-parallel EmCon diode

- 40lower  $E_{\text{off}}$  compared to previous generation
- Short circuit withstand time – 10  $\mu\text{s}$
- Designed for:
  - Motor controls
  - Inverter
  - SMPS
- NPT-Technology offers:
  - very tight parameter distribution
  - high ruggedness, temperature stable behaviour
  - parallel switching capability



- Complete product spectrum and PSpice Models : <http://www.infineon.com/igbt/>

Type	$V_{\text{CE}}$	$I_C$	$E_{\text{off}}$	$T_j$	Package	Ordering Code
SKW07N120	1200V	8A	0.7mJ	150°C	TO-247AC	Q67040-S4280

#### Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	$V_{\text{CE}}$	1200	V
DC collector current	$I_C$		A
$T_C = 25^\circ\text{C}$		16.5	
$T_C = 100^\circ\text{C}$		7.9	
Pulsed collector current, $t_p$ limited by $T_{j\max}$	$I_{C\text{puls}}$	27	
Turn off safe operating area	-	27	
$V_{\text{CE}} \leq 1200\text{V}, T_j \leq 150^\circ\text{C}$			
Diode forward current	$I_F$		
$T_C = 25^\circ\text{C}$		13	
$T_C = 100^\circ\text{C}$		7	
Diode pulsed current, $t_p$ limited by $T_{j\max}$	$I_{F\text{puls}}$	27	
Gate-emitter voltage	$V_{\text{GE}}$	$\pm 20$	V
Short circuit withstand time <sup>1)</sup>	$t_{\text{SC}}$	10	$\mu\text{s}$
$V_{\text{GE}} = 15\text{V}, 100\text{V} \leq V_{\text{CC}} \leq 1200\text{V}, T_j \leq 150^\circ\text{C}$			
Power dissipation	$P_{\text{tot}}$	125	W
$T_C = 25^\circ\text{C}$			
Operating junction and storage temperature	$T_j, T_{\text{stg}}$	-55...+150	$^\circ\text{C}$
Soldering temperature, 1.6mm (0.063 in.) from case for 10s	-	260	



SKW07N120

### Thermal Resistance

Parameter	Symbol	Conditions	Max. Value	Unit
<b>Characteristic</b>				
IGBT thermal resistance, junction – case	$R_{thJC}$		1	K/W
Diode thermal resistance, junction – case	$R_{thJCD}$		2.5	
Thermal resistance, junction – ambient	$R_{thJA}$	TO-247AC	40	

**Electrical Characteristic**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
<b>Static Characteristic</b>						
Collector-emitter breakdown voltage	$V_{(BR)CES}$	$V_{GE}=0\text{V}, I_C=500\mu\text{A}$	1200	-	-	V
Collector-emitter saturation voltage	$V_{CE(\text{sat})}$	$V_{GE} = 15\text{V}, I_C=8\text{A}$ $T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	2.5 -	3.1 3.7	3.6 4.3	
Diode forward voltage	$V_F$	$V_{GE}=0\text{V}, I_F=7\text{A}$ $T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	-	2.0 1.75	2.4	
Gate-emitter threshold voltage	$V_{GE(\text{th})}$	$I_C=350\mu\text{A}, V_{CE}=V_{GE}$	3	4	5	
Zero gate voltage collector current	$I_{CES}$	$V_{CE}=1200\text{V}, V_{GE}=0\text{V}$ $T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	- -	-	100 400	$\mu\text{A}$
Gate-emitter leakage current	$I_{GES}$	$V_{CE}=0\text{V}, V_{GE}=20\text{V}$	-	-	100	nA
Transconductance	$g_{fs}$	$V_{CE}=20\text{V}, I_C=8\text{A}$		6	-	S

### Dynamic Characteristic

Input capacitance	$C_{iss}$	$V_{CE}=25\text{V},$ $V_{GE}=0\text{V},$ $f=1\text{MHz}$	-	720	870	pF
Output capacitance	$C_{oss}$		-	90	110	
Reverse transfer capacitance	$C_{rss}$		-	40	50	
Gate charge	$Q_{\text{Gate}}$	$V_{CC}=960\text{V}, I_C=8\text{A}$ $V_{GE}=15\text{V}$	-	70	90	nC
Internal emitter inductance measured 5mm (0.197 in.) from case	$L_E$	TO-247AC	-	13	-	nH
Short circuit collector current <sup>1)</sup>	$I_{C(\text{SC})}$	$V_{GE}=15\text{V}, t_{sc}\leq 10\mu\text{s}$ $100\text{V}\leq V_{CC}\leq 1200\text{V},$ $T_j \leq 150^\circ\text{C}$	-	75	-	A

<sup>1)</sup> Allowed number of short circuits: <1000; time between short circuits: >1s.



SKW07N120

**Switching Characteristic, Inductive Load, at  $T_j=25\text{ }^\circ\text{C}$**

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
<b>IGBT Characteristic</b>						
Turn-on delay time	$t_{d(on)}$	$T_j=25\text{ }^\circ\text{C}$ , $V_{CC}=800\text{V}$ , $I_C=8\text{A}$ , $V_{GE}=15\text{V}/0\text{V}$ , $R_G=47\Omega$ , $L_\sigma^{(1)}=180\text{nH}$ , $C_\sigma^{(1)}=40\text{pF}$ Energy losses include “tail” and diode reverse recovery.	-	27	35	ns
Rise time	$t_r$		-	29	38	
Turn-off delay time	$t_{d(off)}$		-	440	570	
Fall time	$t_f$		-	21	27	
Turn-on energy	$E_{on}$		-	0.6	0.8	mJ
Turn-off energy	$E_{off}$		-	0.4	0.55	
Total switching energy	$E_{ts}$		-	1.0	1.35	

**Anti-Parallel Diode Characteristic**

Diode reverse recovery time	$t_{rr}$	$T_j=25\text{ }^\circ\text{C}$ , $V_R=800\text{V}$ , $I_F=8\text{A}$ , $di_F/dt=400\text{A}/\mu\text{s}$	-	60		ns
	$t_S$		-			
	$t_F$		-			
Diode reverse recovery charge	$Q_{rr}$		-	0.3		$\mu\text{C}$
Diode peak reverse recovery current	$I_{rrm}$		-	9		A
Diode peak rate of fall of reverse recovery current during $t_F$	$di_{rr}/dt$		-	400		$\text{A}/\mu\text{s}$





**Switching Characteristic, Inductive Load, at  $T_j=150\text{ }^\circ\text{C}$**


Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
<b>IGBT Characteristic</b>						
Turn-on delay time	$t_{d(on)}$	$T_j=150\text{ }^\circ\text{C}$ , $V_{CC}=800\text{V}$ , $I_C=8\text{A}$ , $V_{GE}=15\text{V}/0\text{V}$ , $R_G=47\Omega$ , $L_\sigma^{(1)}=180\text{nH}$ , $C_\sigma^{(1)}=40\text{pF}$ Energy losses include “tail” and diode reverse recovery.	-	30	36	ns
Rise time	$t_r$		-	26	31	
Turn-off delay time	$t_{d(off)}$		-	490	590	
Fall time	$t_f$		-	30	36	
Turn-on energy	$E_{on}$		-	1.0	1.2	mJ
Turn-off energy	$E_{off}$		-	0.7	0.9	
Total switching energy	$E_{ts}$		-	1.7	2.1	

**Anti-Parallel Diode Characteristic**


Diode reverse recovery time	$t_{rr}$	$T_j=150\text{ }^\circ\text{C}$ , $V_R=800\text{V}$ , $I_F=8\text{A}$ , $di_F/dt=500\text{A}/\mu\text{s}$	-	170		ns
	$t_S$		-			
	$t_F$		-			
Diode reverse recovery charge	$Q_{rr}$		-	1.1		$\mu\text{C}$
Diode peak reverse recovery current	$I_{rrm}$		-	15		A
Diode peak rate of fall of reverse recovery current during $t_F$	$di_{rr}/dt$		-	110		$\text{A}/\mu\text{s}$

<sup>1)</sup> Leakage inductance  $L_\sigma$  and stray capacity  $C_\sigma$  due to dynamic test circuit in figure E.







**Figure 5. Typical output characteristics**  
( $T_j = 25^\circ\text{C}$ )







**Figure 6. Typical output characteristics**  
( $T_j = 150^\circ\text{C}$ )




**Figure 7. Typical transfer characteristics**  
( $V_{CE} = 20\text{V}$ )




**Figure 8. Typical collector-emitter saturation voltage as a function of junction temperature**  
( $V_{GE} = 15\text{V}$ )







**Figure 13. Typical switching energy losses as a function of collector current**  
 (inductive load,  $T_j = 150^\circ\text{C}$ ,  
 $V_{CE} = 800\text{V}$ ,  $V_{GE} = +15\text{V}/0\text{V}$ ,  $R_G = 47\Omega$ ,  
 dynamic test circuit in Fig.E )




**Figure 14. Typical switching energy losses as a function of gate resistor**  
 (inductive load,  $T_j = 150^\circ\text{C}$ ,  
 $V_{CE} = 800\text{V}$ ,  $V_{GE} = +15\text{V}/0\text{V}$ ,  $I_C = 8\text{A}$ ,  
 dynamic test circuit in Fig.E )




**Figure 15. Typical switching energy losses as a function of junction temperature**  
 (inductive load,  $V_{CE} = 800\text{V}$ ,  
 $V_{GE} = +15\text{V}/0\text{V}$ ,  $I_C = 8\text{A}$ ,  $R_G = 47\Omega$ ,  
 dynamic test circuit in Fig.E )




**Figure 16. IGBT transient thermal impedance as a function of pulse width**  
 $(D = t_p / T)$




**Figure 17. Typical gate charge**  
( $I_C = 8A$ )




**Figure 18. Typical capacitance as a function of collector-emitter voltage**  
( $V_{GE} = 0V, f = 1MHz$ )




**Figure 19. Short circuit withstand time as a function of gate-emitter voltage**  
( $V_{CE} = 1200V$ , start at  $T_j = 25^\circ C$ )




**Figure 20. Typical short circuit collector current as a function of gate-emitter voltage**  
( $100V \leq V_{CE} \leq 1200V, T_C = 25^\circ C, T_j \leq 150^\circ C$ )




**Figure 21. Typical reverse recovery time as a function of diode current slope**  
 $(V_R = 800\text{ V}, T_j = 150^\circ\text{C}$ ,  
dynamic test circuit in Fig.E )




**Figure 22. Typical reverse recovery charge as a function of diode current slope**  
 $(V_R = 800\text{ V}, T_j = 150^\circ\text{C}$ ,  
dynamic test circuit in Fig.E )




**Figure 23. Typical reverse recovery current as a function of diode current slope**  
 $(V_R = 800\text{ V}, T_j = 150^\circ\text{C}$ ,  
dynamic test circuit in Fig.E )




**Figure 24. Typical diode peak rate of fall of reverse recovery current as a function of diode current slope**  
 $(V_R = 800\text{ V}, T_j = 150^\circ\text{C}$ ,  
dynamic test circuit in Fig.E )




**Figure 25.** Typical diode forward current as a function of forward voltage





**Figure 26.** Typical diode forward voltage as a function of junction temperature




**Figure 27.** Diode transient thermal impedance as a function of pulse width  
( $D = t_p / T$ )




symbol	dimensions			
	[mm]		[inch]	
	min	max	min	max
A	4.78	5.28	0.1882	0.2079
B	2.29	2.51	0.0902	0.0988
C	1.78	2.29	0.0701	0.0902
D	1.09	1.32	0.0429	0.0520
E	1.73	2.06	0.0681	0.0811
F	2.67	3.18	0.1051	0.1252
G	0.76 max		0.0299 max	
H	20.80	21.16	0.8189	0.8331
K	15.65	16.15	0.6161	0.6358
L	5.21	5.72	0.2051	0.2252
M	19.81	20.68	0.7799	0.8142
N	3.560	4.930	0.1402	0.1941
ØP	3.61		0.1421	
Q	6.12	6.22	0.2409	0.2449




SIS00053



**Figure D. Thermal equivalent circuit**



SIS00050



**Figure E. Dynamic test circuit**  
Leakage inductance  $L_\sigma=180\text{nH}$ ,  
and stray capacity  $C_\sigma=40\text{pF}$ .



SKW07N120

**Published by**  
Infineon Technologies AG i Gr.,  
Bereich Kommunikation  
St.-Martin-Strasse 53,  
D-81541 München  
© Infineon Technologies AG 1999  
All Rights Reserved.

**Attention please!**

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

**Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

**Warnings**

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.