


SML1001R1AN	1000V	9.5A	1.10Ω
SML901R1AN	900V	9.5A	1.10Ω
SML1001R3AN	1000V	8.5A	1.30Ω
SML901R3AN	900V	8.5A	1.30Ω


TO3 Package Outline.

Dimensions in mm (Inches)



POWER MOS IV™

N-CHANNEL ENHANCEMENT MODE HIGH VOLTAGE POWER MOSFETS



MAXIMUM RATINGS (T_{case} = 25°C unless otherwise stated)

Parameter		SML				Unit
		901R1AN	1001R1AN	901R3AN	1001R3AN	
V _{DSS}	Drain - Source Voltage	900	1000	900	1000	V
I _D	Continuous Drain Current	9.5		8.5		A
I _{DM}	Pulsed Drain Current ¹	38		34		A
V _{GS}	Gate - Source Voltage	±30				V
P _D	Total Power Dissipation @ T _{case} = 25°C Derate above 25°C	230				W
T _J , T _{STJ}	Operating and Storage Junction Temperature Range	-55 to 150				°C


STATIC ELECTRICAL RATINGS (T_{case} = 25°C unless otherwise stated)

	Characteristic / Test Conditions / Part Number	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain - Source Breakdown Voltage (V _{GS} = 0V, I _D = 250μA)	SML1001R1AN / SML1001R3AN	1000		V
		SML901R1AN / SML901R3AN	900		
I_{DSS}	Zero Gate Voltage Drain Current (V _{GS} = 0V, V _{DS} = V _{DSS}) (V _{GS} = 0V, V _{DS} = 0.8V _{DSS} , T _C = 125°C)			250 1000	μA
I_{GSS}	Gate - Source Leakage Current (V _{GS} = ±30V, V _{DS} = 0V)			±100	nA
I_{D(ON)}	On State Drain Current ² (V _{DS} > I _{D(ON)} × R _{DS(ON)} Max, V _{GS} = 10V)	SML1001R1AN / SML901R1AN	9.5		A
		SML1001R1AN / SML901R3AN	8.5		
V_{GS(TH)}	Gate Threshold Voltage	2		4	V
R_{DS(ON)}	Static Drain - Source On State Resistance ² (V _{GS} = 10V, I _D = 0.5 I _D [Cont.])	SML1001R1AN / SML901R1AN		1.1	Ω
		SML1001R3AN / SML901R3AN		1.3	

1) Repetitive Rating: Pulse Width limited by maximum junction temperature.

2) Pulse Test: Pulse Width < 380μS, Duty Cycle < 2%

SML1001R1AN 1000V 9.5A 1.10Ω
SML901R1AN 900V 9.5A 1.10Ω
SML1001R3AN 1000V 8.5A 1.30Ω
SML901R3AN 900V 8.5A 1.30Ω



DYNAMIC CHARACTERISTICS

	Characteristic	Test Conditions.	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{GS} = 0V$ $V_{DS} = 25V$ $f = 1MHz$		2460	2950	pF
C_{oss}	Output capacitance			360	500	
C_{rss}	Reverse transfer capacitance			105	160	
Q_g	Total Gate Charge ³	$V_{GS} = 10V$ $I_D = I_D [Cont.]$ $V_{DD} = 0.5 V_{DSS}$		90	130	nC
Q_{gs}	Gate - Source Charge			9.3	14	
Q_{gd}	Gate - Drain ("Miller") Charge			47	70	
$t_{d(on)}$	Turn-on Delay Time	$V_{DD} = 0.5 V_{DSS}$ $I_D = I_D [Cont.]$ $V_{GS} = 15V$ $R_G = 1.8\Omega$		15	30	ns
t_r	Rise Time			16	32	
$t_{d(off)}$	Turn-off Delay Time			64	95	
t_f	Fall Time			24	48	

SOURCE - DRAIN DIODE RATINGS AND CHARACTERISTICS

	Characteristic / Test Conditions.	Part Number	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current (Body Diode)	SML1001R1AN / SML901R1AN			9.5	A
		SML901R3AN / SML901R3AN			8.5	
I_{SM}	Pulsed Source Current ¹ (Body Diode)	SML1001R1AN / SML901R1AN			38	A
		SML1001R3AN / SML901R3AN			34	
V_{SD}	Diode Forward Voltage ² ($V_{GS} = 0V$, $I_S = -I_D [Cont.]$)				1.3	V
t_{rr}	Reverse Recovery Time ($I_S = -I_D [Cont.]$, $dI_S / dt = 100A/\mu s$)		320	636	1200	ns
Q_{rr}	Reverse Recovery Charge		2.2	4.5	9	μC

SAFE OPERATING AREA CHARACTERISTICS

	Characteristic / Test Conditions / Part Number	Min.	Typ.	Max.	Unit
SOA1	Safe Operating Area $V_{DS} = 0.4 V_{DSS}$, $I_{DS} = P_D / 0.4 V_{DSS}$, $t = 1 \text{ Sec}$	230			W
SOA2	Safe Operating Area $I_{DS} = I_{DS} [Cont.]$, $V_{DS} = P_D / I_D [Cont.]$, $t = 1 \text{ Sec}$	230			
I_{LM}	Inductive Current Clamped	SML1001R1AN / SML901R1AN	38		A
		SML1001R3AN / SML901R3AN	34		

THERMAL CHARACTERISTICS ($T_{case} = 25^\circ C$ unless otherwise stated)

	Characteristic / Test Conditions.	Min.	Typ.	Max.	Unit
$R_{\theta JC}$	Junction to Case			0.53	$^\circ C/W$
$R_{\theta JA}$	Junction to Ambient			30	$^\circ C/W$
T_L	Max. Lead Temperature for Soldering Conditions: 0.065" from Case for 10 sec.			300	$^\circ C$

1) Repetitive Rating: Pulse Width limited by maximum junction temperature.

2) Pulse Test: Pulse Width $< 380\mu s$, Duty Cycle $< 2\%$

3) See MIL-STD-750 Method 3471

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com