



SOT-227 Package Outline.

Dimensions in mm (inches)



N-CHANNEL ENHANCEMENT MODE HIGH VOLTAGE POWER MOSFETS

V_{DSS} 1000V

I_{D(cont)} 34A

R_{DS(on)} 0.250Ω

- **Faster Switching**
- **Lower Leakage**
- **100% Avalanche Tested**
- **Popular SOT-227 Package**

StarMOS is a new generation of high voltage N-Channel enhancement mode power MOSFETs. This new technology minimises the JFET effect, increases packing density and reduces the on-resistance. StarMOS also achieves faster switching speeds through optimised gate layout.

ABSOLUTE MAXIMUM RATINGS (T_{case} = 25°C unless otherwise stated)

V _{DSS}	Drain – Source Voltage	1000	V
I _D	Continuous Drain Current	34	A
I _{DM}	Pulsed Drain Current ¹	136	A
V _{GS}	Gate – Source Voltage	±30	V
V _{GSM}	Gate – Source Voltage Transient	±40	
P _D	Total Power Dissipation @ T _{case} = 25°C	700	W
	Derate Linearly	5.6	W/°C
T _J , T _{STG}	Operating and Storage Junction Temperature Range	–55 to 150	°C
T _L	Lead Temperature : 0.063” from Case for 10 Sec.	300	
I _{AR}	Avalanche Current ¹ (Repetitive and Non-Repetitive)	34	A
E _{AR}	Repetitive Avalanche Energy ¹	50	mJ
E _{AS}	Single Pulse Avalanche Energy ²	3600	

1) Repetitive Rating: Pulse Width limited by maximum junction temperature.

2) Starting $T_J = 25^\circ\text{C}$, $L = 6.23\text{mH}$, $R_G = 25\Omega$, Peak $I_1 = 34\text{A}$

STATIC ELECTRICAL RATINGS ($T_{case} = 25^{\circ}\text{C}$ unless otherwise stated)

	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain – Source Breakdown Voltage	$V_{GS} = 0V$, $I_D = 250\mu A$	1000			V
I_{DSS}	Zero Gate Voltage Drain Current ($V_{GS} = 0V$)	$V_{DS} = V_{DSS}$			100	μA
		$V_{DS} = 0.8V_{DSS}$, $T_C = 125^{\circ}\text{C}$			500	
I_{GSS}	Gate – Source Leakage Current	$V_{GS} = \pm 30V$, $V_{DS} = 0V$			± 100	nA
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 5mA$	2		4	V
$I_{D(ON)}$	On State Drain Current ²	$V_{DS} > I_{D(ON)} \times R_{DS(ON)}$ Max $V_{GS} = 10V$	34			A
$R_{DS(ON)}$	Drain – Source On State Resistance ²	$V_{GS} = 10V$, $I_D = 0.5 I_D$ [Cont.]			0.250	Ω

DYNAMIC CHARACTERISTICS

	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0V$		15000		pF
C_{oss}	Output Capacitance	$V_{DS} = 25V$		1360		
C_{rss}	Reverse Transfer Capacitance	$f = 1MHz$		710		
Q_g	Total Gate Charge ³	$V_{GS} = 10V$		660		nC
Q_{gs}	Gate – Source Charge	$V_{DD} = 0.5 V_{DSS}$		51		
Q_{gd}	Gate – Drain (“Miller”) Charge	$I_D = I_D$ [Cont.] @ 25°C		250		
$t_{d(on)}$	Turn-on Delay Time	$V_{GS} = 15V$		22		ns
t_r	Rise Time	$V_{DD} = 0.5 V_{DSS}$		20		
$t_{d(off)}$	Turn-off Delay Time	$I_D = I_D$ [Cont.] @ 25°C		97		
t_f	Fall Time	$R_G = 0.6\Omega$		16		

SOURCE – DRAIN DIODE RATINGS AND CHARACTERISTICS

	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	(Body Diode)			34	A
I_{SM}	Pulsed Source Current ¹	(Body Diode)			136	
V_{SD}	Diode Forward Voltage ²	$V_{GS} = 0V$, $I_S = -I_D$ [Cont.]			1.3	V
t_{rr}	Reverse Recovery Time	$I_S = -I_D$ [Cont.], $dI_S / dt = 100A/\mu s$		1300		ns
Q_{rr}	Reverse Recovery Charge	$I_S = -I_D$ [Cont.], $dI_S / dt = 100A/\mu s$		38		μC

THERMAL CHARACTERISTICS

	Characteristic	Min.	Typ.	Max.	Unit
$R_{\theta JC}$	Junction to Case			0.18	$^{\circ}\text{C/W}$
$R_{\theta JA}$	Junction to Ambient			40	

1) Repetitive Rating: Pulse Width limited by maximum junction temperature.

2) Pulse Test: Pulse Width < 380 μs , Duty Cycle < 2%

3) See MIL–STD–750 Method 3471



CAUTION — Electrostatic Sensitive Devices. Anti-Static Procedures Must Be Followed.

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com