查询SR110供应商 捷多邦，专业PCB打样工厂，24小时加急出货

MOSPEC

SR17 Thru SR110

Suface Mount
Schottky Barrier Rectifiers

Using the Schottky Barrier principle with a Molybdenum barrier metal. These state-of-the-art geometry features epitaxial construction with oxide passivation and metal overlay contact. Ideally suited for low voltage, high frequency rectification, or as free wheeling and polarity protection diodes, in surface mount applications where compact size and weight are critical to the system.

* Low Forward Voltag.
* Low Switching noise.
* High Current Capacity
* Guarantee Reverse Avalance.
* Guard-Ring for Stress Protection.
* Low Power Loss & High efficiency.
* 125 °C Operating Junction Temperature
* Low Stored Charge Majority Carrier Cnduction.
* Plastic Material used Carries Underwriters Laboratory Flammability Classification 94V-O

SCHOTTKY BARRIER RECTIFIERS

1.0 AMPERES
70 -100 VOLTS



DO-214AA(SMB)





DIM	MILLMETERS	
	MIN	MAX
A	3.30	3.90
B	4.20	4.60
C	1.80	2.20
D	4.90	5.60
E	1.90	2.50
F	---	1.30
G	---	0.22
H	0.85	1.45

CASE---
Transfer molded plastic

POLARITY---
Cathode indicated polarity band

MAXIMUM RATINGS

Characteristic	Symbol	SR17	SR18	SR19	SR110	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	70	80	90	100	V
RMS Reverse Voltage	$V_{R(RMS)}$	49	56	63	70	V
Average Rectifier Forward Current	I_O	1.0				A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfware,single phase,60Hz)	I_{FSM}	25				A
Operating and Storage Junction Temperature Range	T_J , T_{stg}	- 65 to + 125				°C

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	SR17	SR18	SR19	SR110	Unit
Maximum Instantaneous Forward Voltage (I_F=1.0 Amp)	V_F	0.75		0.85		V
Maximum Instantaneous Reverse Current (Rated DC Voltage, T_C = 25 °C) (Rated DC Voltage, T_C = 100 °C)	I_R	1.0 30				mA
Typical Junction Capacitance (Reverse Voltage of 4 volts & f=1 MHz)	C_P	70		60		pF

找PDF 维库一下 pdf.dzsc.com

SR17 , SR18

FIG-1 FORWARD CURRENT DERATING CURVE



FIG-2 TYPICAL FORWARD CHARACTERISTICS



FIG-3 TYPICAL REVERSE CHARACTERISTICS



FIG-4 TYPICAL JUNCTION CAPACITANCE



FIG-5 PEAK FORWARD SURGE CURRENT



SR19 , SR110

FIG-1 FORWARD CURRENT DERATING CURVE



FIG-2 TYPICAL FORWARD CHARACTERISTICS



FIG-3 TYPICAL REVERSE CHARACTERISTICS



FIG-4 TYPICAL JUNCTION CAPACITANCE



FIG-5 PEAK FORWARD SURGE CURRENT