



# SRA2207EF

PNP Silicon Transistor

## Descriptions

- Switching application
- Interface circuit and driver circuit application

## Features

- With built-in bias resistors
- Simplify circuit design
- Reduce a quantity of parts and manufacturing process
- High packing density

## Ordering Information

Type NO.	Marking	Package Code
SRA2207EF	7R	SOT-523F

## Outline Dimensions

unit : mm

Dimensions shown in drawing:

- Top width:  $1.60 \pm 0.1$
- Internal width:  $0.88 \pm 0.1$
- Left height:  $1.60 \pm 0.1$
- Internal left height:  $1.00 \pm 0.1$
- Right lead length:  $0.25 \sim 0.30$
- Bottom lead length:  $1.11 \pm 0.05$
- Bottom lead width:  $0 - 0.1$
- Bottom lead thickness:  $0.68 - 0.05$

• Equivalent Circuit

Labels in circuit: B(IN), R<sub>1</sub>, C(OUT), R<sub>2</sub>, E(COMMON)

PIN Connections

1. Base
2. Emitter
3. Collector

R <sub>1</sub>	R <sub>2</sub>
10KΩ	47KΩ



## Absolute maximum ratings

(Ta=25°C)

Characteristic	Symbol	Ratings	Unit
Out Voltage	$V_O$	-50	V
Input Voltage	$V_I$	-30	V
Out Current	$I_O$	-100	mA
Power Dissipation	$P_D$	150	mW
Junction Temperature	$T_J$	150	°C
Storage Temperature	$T_{STG}$	-55 ~ 150	°C

## Electrical Characteristics

(Ta=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Output Cut-off Current	$I_{O(OFF)}$	$V_O = -50V, V_I = 0$	-	-	-500	nA
DC Current Gain	$G_I$	$V_O = -5V, I_O = -10mA$	80	150	-	-
Output Voltage	$V_{O(ON)}$	$I_O = -10mA, I_I = -0.5mA$	-	-0.1	-0.3	V
Input Voltage (ON)	$V_{I(ON)}$	$V_O = -0.2V, I_O = -5mA$	-	-	-1.8	V
Input Voltage (OFF)	$V_{I(OFF)}$	$V_O = -5V, I_O = -0.1mA$	-0.5	-	-	V
Transition Frequency	$f_T^*$	$V_O = -10V, I_O = -5mA$	-	200	-	MHz
Input Current	$I_I$	$V_I = -5V$	-	-	-0.88	mA

\* : Characteristic of Transistor Only

Electrical Characteristic Curves

Fig. 1  $I_o - V_{I(ON)}$




Fig. 2  $I_o - V_{I(OFF)}$




Fig. 3  $G_1 - I_o$

