



---

***DISCRETE POWER DIODES and THYRISTORS***  
***DATA BOOK***

---

**PHASE CONTROL THYRISTORS**
**Hockey Puk Version**
**Features**


- Center amplifying gate
- Metal case with ceramic insulator
- International standard case TO-200AC (B-PUK)

**Typical Applications**

- DC motor controls
- Controlled DC power supplies
- AC controllers

**Major Ratings and Characteristics**

| Parameters        | ST300C..L     | Units             |
|-------------------|---------------|-------------------|
| $I_{T(AV)}$       | 560           | A                 |
|                   | @ $T_{hs}$ 55 | °C                |
| $I_{T(RMS)}$      | 1115          | A                 |
|                   | @ $T_{hs}$ 25 | °C                |
| $I_{TSM}$         | @ 50Hz 8000   | A                 |
|                   | @ 60Hz 8380   | A                 |
| $I^2t$            | @ 50Hz 320    | KA <sup>2</sup> s |
|                   | @ 60Hz 292    | KA <sup>2</sup> s |
| $V_{DRM}/V_{RRM}$ | 400 to 2000   | V                 |
| $t_q$ typical     | 100           | μs                |
| $T_J$             | - 40 to 125   | °C                |

**560A**


case style TO-200AC (B-PUK)

## ST300C..L Series

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

| Type number | Voltage Code | $V_{DRM}/V_{RRM}$ , max. repetitive peak and off-state voltage<br>V | $V_{RSM}$ , maximum non-repetitive peak voltage<br>V | $I_{DRM}/I_{RRM}$ max.<br>@ $T_J = T_J$ max<br>mA |
|-------------|--------------|---|--|---|
| ST300C..L   | 04           | 400   | 500  | 50  |
|             | 08           | 800   | 900  |   |
|             | 12           | 1200  | 1300   |   |
|             | 16           | 1600  | 1700   |   |
|             | 18           | 1800  | 1900   |   |
|             | 20           | 2000  | 2100   |   |

#### On-state Conduction

| Parameter  | ST300C..L | Units              | Conditions   |                       |
|--|-----------|--------------------|--|-----------------------|
| $I_{T(AV)}$ Max. average on-state current @ Heatsink temperature | 560 (275) | A                  | 180° conduction, half sine wave<br>double side (single side) cooled      |                       |
|  | 55 (75)   | °C                 |  |                       |
| $I_{T(RMS)}$ Max. RMS on-state current                           | 1115      | A                  | DC @ 25°C heatsink temperature double side cooled                        |                       |
| $I_{TSM}$ Max. peak, one-cycle non-repetitive surge current      | 8000      |                    | t = 10ms   | No voltage reappplied |
|  | 8380      |                    | t = 8.3ms  | reappplied            |
|  | 6730      |                    | t = 10ms   | 100% $V_{RRM}$        |
|  | 7040      | t = 8.3ms          | reappplied   |                       |
| $I^2t$ Maximum $I^2t$ for fusing                                 | 320       | KA <sup>2</sup> s  | t = 10ms   | No voltage reappplied |
|  | 292       |                    | t = 8.3ms  | reappplied            |
|  | 226       |                    | t = 10ms   | 100% $V_{RRM}$        |
|  | 207       |                    | t = 8.3ms  | reappplied            |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing                   | 3200      | KA <sup>2</sup> √s | t = 0.1 to 10ms, no voltage reappplied                                   |                       |
| $V_{T(TO)1}$ Low level value of threshold voltage                | 0.97      | V                  | (16.7% x $\pi$ x $I_{T(AV)} < I < \pi$ x $I_{T(AV)}$ ), $T_J = T_J$ max. |                       |
| $V_{T(TO)2}$ High level value of threshold voltage               | 0.98      |                    | ( $I > \pi$ x $I_{T(AV)}$ ), $T_J = T_J$ max.                            |                       |
| $r_{t1}$ Low level value of on-state slope resistance            | 0.74      | mΩ                 | (16.7% x $\pi$ x $I_{T(AV)} < I < \pi$ x $I_{T(AV)}$ ), $T_J = T_J$ max. |                       |
| $r_{t2}$ High level value of on-state slope resistance           | 0.73      |                    | ( $I > \pi$ x $I_{T(AV)}$ ), $T_J = T_J$ max.                            |                       |
| $V_{TM}$ Max. on-state voltage                                   | 2.18      | V                  | $I_{pk} = 1635A$ , $T_J = T_J$ max, $t_p = 10ms$ sine pulse              |                       |
| $I_H$ Maximum holding current                                    | 600       | mA                 | $T_J = 25^\circ C$ , anode supply 12V resistive load                     |                       |
| $I_L$ Typical latching current                                   | 1000      |                    |  |                       |

ST300C..L Series

---




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - On-state Power Loss Characteristics




Fig. 6 - On-state Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current  
Single and Double Side Cooled




Fig. 8 - Maximum Non-Repetitive Surge Current  
Single and Double Side Cooled




Fig. 9 - On-state Voltage Drop Characteristics




Fig. 10 - Thermal Impedance  $Z_{thJ-hs}$  Characteristics




Fig. 11 - Gate Characteristics

## ST300C..L Series

### Switching

| Parameter  | ST300C..L | Units | Conditions  |
|--|-----------|-------|---|
| di/dt<br>Max. non-repetitive rate of rise of turned-on current | 1000      | A/μs  | Gate drive 20V, 20Ω, $t_r \leq 1\mu s$<br>$T_J = T_J \text{ max}$ , anode voltage $\leq 80\% V_{DRM}$                                 |
| $t_d$<br>Typical delay time                                    | 1.0       | μs    | Gate current 1A, $di_g/dt = 1A/\mu s$<br>$V_d = 0.67\% V_{DRM}$ , $T_J = 25^\circ C$  |
| $t_q$<br>Typical turn-off time                                 | 100       |       | $I_{TM} = 550A$ , $T_J = T_J \text{ max}$ , $di/dt = 40A/\mu s$ , $V_R = 50V$<br>$dv/dt = 20V/\mu s$ , Gate 0V 100Ω, $t_p = 500\mu s$ |

### Blocking

| Parameter   | ST300C..L | Units | Conditions  |
|---|-----------|-------|---|
| dv/dt<br>Maximum critical rate of rise of off-state voltage               | 500       | V/μs  | $T_J = T_J \text{ max}$ , linear to 80% rated $V_{DRM}$   |
| $I_{RRM}$<br>$I_{DRM}$<br>Max. peak reverse and off-state leakage current | 50        | mA    | $T_J = T_J \text{ max}$ , rated $V_{DRM}/V_{RRM}$ applied |

### Triggering

| Parameter                                       | ST300C..L |      | Units | Conditions  |
|---|-----------|------|-------|---|
| $P_{GM}$<br>Maximum peak gate power             | 10.0      |      | W     | $T_J = T_J \text{ max}$ , $t_p \leq 5ms$  |
| $P_{G(AV)}$<br>Maximum average gate power       | 2.0       |      |       | $T_J = T_J \text{ max}$ , $f = 50Hz$ , $d\% = 50$   |
| $I_{GM}$<br>Max. peak positive gate current     | 3.0       |      | A     | $T_J = T_J \text{ max}$ , $t_p \leq 5ms$  |
| $+V_{GM}$<br>Maximum peak positive gate voltage | 20        |      | V     | $T_J = T_J \text{ max}$ , $t_p \leq 5ms$  |
| $-V_{GM}$<br>Maximum peak negative gate voltage | 5.0       |      |       |   |
| $I_{GT}$<br>DC gate current required to trigger | TYP.      | MAX. | mA    | $T_J = -40^\circ C$<br>$T_J = 25^\circ C$<br>$T_J = 125^\circ C$<br><br>Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 12V anode-to-cathode applied |
|   | 200       | -    |       |   |
|   | 100       | 200  |       |   |
| $V_{GT}$<br>DC gate voltage required to trigger | 2.5       | -    | V     | $T_J = -40^\circ C$<br>$T_J = 25^\circ C$<br>$T_J = 125^\circ C$  |
|   | 1.8       | 3.0  |       |   |
|   | 1.1       | -    |       |   |
| $I_{GD}$<br>DC gate current not to trigger      | 10.0      |      | mA    | $T_J = T_J \text{ max}$<br><br>Max. gate current/voltage not to trigger is the max. value which will not trigger any unit with rated $V_{DRM}$ anode-to-cathode applied                             |
| $V_{GD}$<br>DC gate voltage not to trigger      | 0.25      |      | V     |   |

## ST300C..L Series

### Thermal and Mechanical Specification

| Parameter  | ST300C..L          | Units     | Conditions                      |
|--|--------------------|-----------|---------------------------------|
| $T_J$ Max. operating temperature range                     | -40 to 125         | °C        |                                 |
| $T_{stg}$ Max. storage temperature range                   | -40 to 150         |           |                                 |
| $R_{thJ-hs}$ Max. thermal resistance, junction to heatsink | 0.11               | K/W       | DC operation single side cooled |
|  | 0.05               |           | DC operation double side cooled |
| $R_{thC-hs}$ Max. thermal resistance, case to heatsink     | 0.011              | K/W       | DC operation single side cooled |
|  | 0.006              |           | DC operation double side cooled |
| F Mounting force, $\pm 10\%$                               | 9800<br>(1000)     | N<br>(Kg) |                                 |
| wt Approximate weight                                      | 250                | g         |                                 |
| Case style   | TO - 200AC (B-PUK) |           | See Outline Table               |

### $\Delta R_{thJ-hs}$ Conduction

(The following table shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction |             | Rectangular conduction |             | Units | Conditions               |
|------------------|-----------------------|-------------|------------------------|-------------|-------|--------------------------|
|                  | Single Side           | Double Side | Single Side            | Double Side |       |                          |
| 180°             | 0.012                 | 0.010       | 0.008                  | 0.008       | K/W   | $T_J = T_J \text{ max.}$ |
| 120°             | 0.014                 | 0.015       | 0.014                  | 0.014       |       |                          |
| 90°              | 0.018                 | 0.018       | 0.019                  | 0.019       |       |                          |
| 60°              | 0.026                 | 0.027       | 0.027                  | 0.028       |       |                          |
| 30°              | 0.045                 | 0.046       | 0.046                  | 0.046       |       |                          |

### Ordering Information Table

| Device Code |   |          |   |  |  |   |  |
|-------------|---|----------|---|--|--|---|--|
| ST          | 30  | 0        | C   | 20                                       | L  | 1   |  |
| ①           | ②   | ③        | ④   | ⑤  | ⑥  | ⑦   | ⑧  |
| <b>1</b>    | - Thyristor   | <b>2</b> | - Essential part number                                   | <b>3</b>                                 | - 0 = Converter grade  | <b>4</b>  | - C = Ceramic Puk  |
| <b>5</b>    | - Voltage code: Code x 100 = $V_{RRM}$ (See Voltage Rating Table)   | <b>6</b> | - L = Puk Case TO-200AC (B-PUK)                           | <b>7</b>                                 | - 0 = Eyelet terminals (Gate and Auxiliary Cathode Unsoldered Leads) | 1 = Fast-on terminals (Gate and Auxiliary Cathode Unsoldered Leads) | 2 = Eyelet terminals (Gate and Auxiliary Cathode Soldered Leads) |
| <b>7</b>    | - 3 = Fast-on terminals (Gate and Auxiliary Cathode Soldered Leads) | <b>8</b> | - Critical dv/dt: None = 500V/ $\mu$ sec (Standard value) | L = 1000V/ $\mu$ sec (Special selection) |  |   |  |

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics