


SIEMENS

1550 nm Laser in Receptacle Package, Low Power

STL 81007X

- Designed for application in fiber-optic networks
- Laser diode with Multi-Quantum Well structure
- Suitable for bit rates up to 1 Gbit/s
- Ternary photodiode at rear mirror for monitoring and control of radiant power
- Hermetically sealed subcomponents, similar to TO 18
- SM Receptacle with 2- hole flange



Type	Ordering Code	Connector/Flange
STL 81007G	Q62702-P3042	FC, 2-hole

Maximum Ratings

Output power ratings refer to the SM fiber output. The operating temperature of the submount is identical to the case temperature.

Parameter	Symbol	Values	Unit
Module			
Operating temperature range at case	T_C	- 40 ... + 85	°C
Storage temperature range	T_{stg}	- 40 ... + 85	°C
Soldering temperature $t_{max} = 10$ s, 2 mm distance from bottom edge of case	T_S	260	°C

Laser Diode

Direct forward current	$I_{F max}$	120	mA
Radiant power CW	Φ_e	1	mW
Reverse voltage	$V_{R max}$	2	V

Monitor Diode

Reverse voltage	$V_{R max}$	10	V
-----------------	-------------	----	---

Characteristics

All optical data refer to a coupled 10/125 μm SM fiber, $T_C = 25\text{ }^\circ\text{C}$.

Parameter	Symbol	Values	Unit
-----------	--------	--------	------

Laser Diode


Optical output power	Φ_e	> 0.4	mW
Emission wavelength center of range $\Phi_e = 0.2\text{ mW}$	λ	1510 ... 1590	nm
Spectral bandwidth $\Phi_e = 0.2\text{ mW}$ (RMS)	$\Delta\lambda$	< 5	nm
Threshold current ($-40\text{ }^\circ\text{C}$... $+85\text{ }^\circ\text{C}$)	I_{th}	8 ... 60	mA
Forward voltage $\Phi_e = 0.2\text{ mW}$	V_F	< 1.5	V
Radiant power at threshold	Φ_{eth}	< 10	μW
Slope efficiency	η	8 ... 60	mW/A
Differential series resistance	r_S	< 8	Ω
Rise time/fall time	t_R, t_F	< 1	ns

Monitor Diode

Dark current, $V_R = 5\text{ V}$, $\Phi_e = 0$	I_R	< 500	nA
Photocurrent, $\Phi_e = 0.2\text{ mW}$	I_P	100 ... 1000	μA


Laser Diode

Radiant Power in Singlemode Fiber




Relative Radiant Power

$$\Phi_e = f(\lambda)$$




Laser Forward Current

$$I_F = f(V_F)$$




Monitor Diode Dark Current $I_R = f(T_A)$

$$\Phi_{\text{port}} = 0, V_R = 5 \text{ V}$$



Package Outlines (Dimensions in mm)



STL 81007X