



New Product

SUM110N04-04
Vishay Siliconix

N-Channel 40-V (D-S) 175°C MOSFET



PRODUCT SUMMARY		
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)
40	0.0035 @ $V_{GS} = 10$ V	110 ^a

FEATURES

- TrenchFET® Power MOSFETS: 1.8-V Rated
- 175°C Junction Temperature

APPLICATIONS

- Automotive
 - ABS
 - 12-V EPS
 - Motor Drivers



ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)			
Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$)	I_D	$T_C = 25^\circ\text{C}$	110 ^a
		$T_C = 125^\circ\text{C}$	107 ^a
Pulsed Drain Current	I_{DM}	350	A
Avalanche Current	I_{AR}	60	mJ
Repetitive Avalanche Energy ^b	E_{AR}	180	
Maximum Power Dissipation ^b	P_D	$T_C = 25^\circ\text{C}$	250 ^c
		$T_A = 25^\circ\text{C}$ ^d	3.75
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Junction-to-Ambient (PCB Mount) ^d	R_{thJA}	40	$^\circ\text{C/W}$
Junction-to-Case	R_{thJC}	0.6	

Notes

- a. Package limited.
- b. Duty cycle $\leq 1\%$.
- c. See SOA curve for voltage derating.
- d. When mounted on 1" square PCB (FR-4 material).

SUM110N04-04

Vishay Siliconix

New Product



SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{DS} = 0 V, I _D = 250 μA	40			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	2		4	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = 20 V			100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 40 V, V _{GS} = 0 V			1	μA
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 175 °C			250	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	120			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 30 A		0.0028	0.0035	Ω
		V _{GS} = 10 V, I _D = 30 A, T _J = 125 °C			0.0045	
		V _{GS} = 10 V, I _D = 30 A, T _J = 175 °C			0.006	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 30 A	30			S
Dynamic^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, f = 1 MHz		6800		pF
Output Capacitance	C _{oss}			1110		
Reverse Transfer Capacitance	C _{rss}			690		
Total Gate Charge ^c	Q _g	V _{DS} = 30 V, V _{GS} = 10 V, I _D = 110 A		140	200	nC
Gate-Source Charge ^c	Q _{gs}			35		
Gate-Drain Charge ^c	Q _{gd}			55		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 30 V, R _L = 0.47 Ω I _D ≅ 110 A, V _{GEN} = 10 V, R _G = 2.5 Ω		20	35	ns
Rise Time ^c	t _r			115	175	
Turn-Off Delay Time ^c	t _{d(off)}			75	115	
Fall Time ^c	t _f			85	130	
Source-Drain Diode Ratings and Characteristics (T_C = 25 °C)^b						
Continuous Current	I _S				110	A
Pulsed Current	I _{SM}				350	
Forward Voltage ^a	V _{SD}	I _F = 110 A, V _{GS} = 0 V		1.1	1.4	V
Reverse Recovery Time	t _{rr}	I _F = 110 A, di/dt = 100 A/μs		50	80	ns
Peak Reverse Recovery Current	I _{RM(REC)}			2	3	A
Reverse Recovery Charge	Q _{rr}			0.05	0.12	μC


Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




Transconductance




On-Resistance vs. Drain Current



Capacitance







Gate Charge






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)






THERMAL RATINGS

Maximum Avalanche and Drain Current vs. Case Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case

