



## N-Channel 200-V (D-S) 175°C MOSFET



PRODUCT SUMMARY		
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ ( $\Omega$ )	$I_D$ (A)
200	0.078 @ $V_{GS} = 10$ V	27
	0.083 @ $V_{GS} = 6$ V	26

### FEATURES

- TrenchFET® Power MOSFETS
- 175°C Junction Temperature
- New Low Thermal Resistance Package
- PWM Optimized for Fast Switching

### APPLICATIONS

- Isolated DC/DC converters
  - Primary-Side Switch



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter	Symbol	Limit	Unit	
Drain-Source Voltage	$V_{DS}$	200	V	
Gate-Source Voltage	$V_{GS}$	$\pm 20$		
Continuous Drain Current ( $T_J = 175^\circ\text{C}$ )	$I_D$	$T_C = 25^\circ\text{C}$	27	A
		$T_C = 125^\circ\text{C}$	15.5	
Pulsed Drain Current	$I_{DM}$	60		
Avalanche Current	$I_{AR}$	18		
Repetitive Avalanche Energy <sup>a</sup>	$E_{AR}$	L = 0.1 mH	16.2	mJ
Maximum Power Dissipation <sup>a</sup>	$P_D$	$T_C = 25^\circ\text{C}$	150 <sup>b</sup>	W
		$T_A = 25^\circ\text{C}$ <sup>c</sup>	3.75	
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to 175	$^\circ\text{C}$	

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Junction-to-Ambient	$R_{thJA}$	40	$^\circ\text{C}/\text{W}$
Junction-to-Case (Drain)	$R_{thJC}$	1.0	

Notes

- Duty cycle  $\leq 1\%$ .
- See SOA curve for voltage derating.
- When mounted on 1" square PCB (FR-4 material).

SPECIFICATIONS (T <sub>J</sub> = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>DS</sub> = 0 V, I <sub>D</sub> = 250 μA	200			V
Gate-Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA	2		4	
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 160 V, V <sub>GS</sub> = 0 V			1	μA
		V <sub>DS</sub> = 160 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125 °C			50	
		V <sub>DS</sub> = 160 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 175 °C			250	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> ≥ 5 V, V <sub>GS</sub> = 10 V	60			A
Drain-Source On-State Resistance <sup>a</sup>	r <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 20 A		0.064	0.078	Ω
		V <sub>GS</sub> = 10 V, I <sub>D</sub> = 20 A, T <sub>J</sub> = 125 °C			0.160	
		V <sub>GS</sub> = 10 V, I <sub>D</sub> = 20 A, T <sub>J</sub> = 175 °C			0.205	
Drain-Source on State Resistance		V <sub>GS</sub> = 6 V, I <sub>D</sub> = 15 A		0.068	0.083	Ω
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 15 V, I <sub>D</sub> = 30 A	15			S
<b>Dynamic<sup>b</sup></b>						
Input Capacitance	C <sub>iSS</sub>	V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 25 V, f = 1 MHz		2150		pF
Output Capacitance	C <sub>oss</sub>			215		
Reverse Transfer Capacitance	C <sub>rSS</sub>			90		
Total Gate Charge <sup>c</sup>	Q <sub>g</sub>	V <sub>DS</sub> = 100 V, V <sub>GS</sub> = 10 V, I <sub>D</sub> = 20 A		40	60	nC
Gate-Source Charge <sup>c</sup>	Q <sub>gs</sub>			11		
Gate-Drain Charge <sup>c</sup>	Q <sub>gd</sub>			14		
Gate Resistance	R <sub>G</sub>			2		Ω
Turn-On Delay Time <sup>c</sup>	t <sub>d(on)</sub>	V <sub>DD</sub> = 100 V, R <sub>L</sub> = 5 Ω I <sub>D</sub> ≅ 20 A, V <sub>GEN</sub> = 10 V, R <sub>G</sub> = 2.5 Ω		15	25	ns
Rise Time <sup>c</sup>	t <sub>r</sub>			35	55	
Turn-Off Delay Time <sup>c</sup>	t <sub>d(off)</sub>			40	60	
Fall Time <sup>c</sup>	t <sub>f</sub>			30	45	
<b>Source-Drain Diode Ratings and Characteristics (T<sub>C</sub> = 25 °C)<sup>b</sup></b>						
Continuous Current	I <sub>S</sub>				27	A
Pulsed Current	I <sub>SM</sub>				60	
Forward Voltage <sup>a</sup>	V <sub>SD</sub>	I <sub>F</sub> = 20 A, V <sub>GS</sub> = 0 V		1.0	1.5	V
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 50 A, di/dt = 100 A/μs		115	170	ns
Peak Reverse Recovery Current	I <sub>RM(REC)</sub>			7.5	12	A
Reverse Recovery Charge	Q <sub>rr</sub>			0.43	1.02	μC


## Notes

- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.
- Independent of operating temperature.




**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**


Output Characteristics




Transfer Characteristics




Transconductance




On-Resistance vs. Drain Current







Capacitance



Gate Charge




**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**






**THERMAL RATINGS**


Maximum Avalanche and Drain Current vs. Case Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case



Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)