




MEAN WELL

SWITCHING POWER SUPPLY

ISO-9001 CERTIFIED MANUFACTURER

SUS01M SERIES

- .UNREGULATED DC OUTPUT
- .1000VDC I/O ISOLATION
- .3000VDC ISOLATION IS AVAILABLE
- .INPUT FILTER:CAPACITOR TYPE
- .INTERNAL SMD TECHNOLOGY
- .NO EXTERNAL COMPONENTS REQUIRED
- .HIGH RELIABILITY / LOW COST
- .100% BURN-IN TEST
- .MTBF:700,000 HOURS



MODEL	SUS01M-05	SUS01M-09	SUS01M-12	SUS01M-15										
SPECIFICATION														
DC OUTPUT VOLTAGE	5V	9V	12V	15V										
OUTPUT VOLTAGE ACCURACY	±2%													
OUTPUT RATED CURRENT	200mA	111mA	84mA	67mA										
OUTPUT CURRENT RANGE	0-200mA	0-111mA	0-84mA	0-67mA										
RIPPLE & NOISE	100mVp-p (max.)													
LINE REGULATION	± 1.2% FOR 1% INPUT VARIATION													
LOAD REGULATION	± 8% @ 20%~FULL LOAD													
DC OUTPUT POWER	1W	1W	1W	1W										
EFFICIENCY	74%	79%	82%	82%										
SWITCHING FREQUENCY	100KHz min.													
INPUT VOLTAGE RANGE	12V± 10% (10.8~13.2VDC)													
INPUT CURRENT	112mA max.													
SHORT CIRCUIT PROTECTION	MOMENTARY													
OVER VOLTAGE PROTECTION	-----													
TEMP. COEFFICIENT	±0.03% / °C (0~50°C)													
ISOLATION VOLTAGE	I/P-O/P:1KVDC MIN.													
ISOLATION RESISTANCE	I/P-O/P:500VDC / 100M Ohms MIN.													
ISOLATION CAPACITANCE	80pF max.													
WORKING TEMP., HUMIDITY	-15°C~+60°C, 20%~90% RH (NO DERATING); 80% LOAD @ 71°C													
STORAGE TEMP., HUMIDITY	-25°C~+85°C, 10%~95% RH													
DIMENSION	0.89"*0.39"*0.33"													
WEIGHT	3.1g													
CASE MATERIA L	NON-CONDUCTIVE PLASTIC													
MECHANISM AND PIN CONFIGURATION	8.9 (0.39) 16 1 10 11 6 10 7 9 8 7.62 (0.30) BOTTOM VIEW 12.7 (0.50) 2.54 (0.10) 8.4 (0.33) 3.81 (0.15) 22.6 (0.89) <table><tr><th>Pin no.</th><th>Output</th></tr><tr><td>1 & 16</td><td>+Vin</td></tr><tr><td>6 & 11</td><td>-Vout</td></tr><tr><td>7 & 10</td><td>+Vout</td></tr><tr><td>8 & 9</td><td>-Vin</td></tr></table>				Pin no.	Output	1 & 16	+Vin	6 & 11	-Vout	7 & 10	+Vout	8 & 9	-Vin
	Pin no.	Output												
	1 & 16	+Vin												
	6 & 11	-Vout												
	7 & 10	+Vout												
8 & 9	-Vin													

NOTE : 1.ALL PARAMETERS ARE SPECIFIED AT RATED INPUT, RATED LOAD, 25°C 70% RH. AMBIENT.
2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
4.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD.




MEAN WELL

SWITCHING POWER SUPPLY

ISO-9001 CERTIFIED MANUFACTURER

SUS01N SERIES

- .UNREGULATED DC OUTPUT
- .1000VDC I/O ISOLATION
- .3000VDC ISOLATION IS AVAILABLE
- .INPUT FILTER:CAPACITOR TYPE
- .INTERNAL SMD TECHNOLOGY
- .NO EXTERNAL COMPONENTS REQUIRED
- .HIGH RELIABILITY / LOW COST
- .100% BURN-IN TEST
- .MTBF:700,000 HOURS



MODEL	SUS01N-05	SUS01N-09	SUS01N-12	SUS01N-15										
SPECIFICATION														
DC OUTPUT VOLTAGE	5V	9V	12V	15V										
OUTPUT VOLTAGE ACCURACY	±2%													
OUTPUT RATED CURRENT	200mA	111mA	84mA	67mA										
OUTPUT CURRENT RANGE	0-200mA	0-111mA	0-84mA	0-67mA										
RIPPLE & NOISE	100mVp-p (max.)													
LINE REGULATION	± 1.2% FOR 1% INPUT VARIATION													
LOAD REGULATION	± 8% @ 20%~FULL LOAD													
DC OUTPUT POWER	1W	1W	1W	1W										
EFFICIENCY	76%	80%	83%	83%										
SWITCHING FREQUENCY	100KHz min.													
INPUT VOLTAGE RANGE	24V± 10% (21.6~26.4VDC)													
INPUT CURRENT	55mA max.													
SHORT CIRCUIT PROTECTION	MOMENTARY													
OVER VOLTAGE PROTECTION	-----													
TEMP. COEFFICIENT	±0.03% / °C (0~50°C)													
ISOLATION VOLTAGE	I/P-O/P:1KVDC MIN.													
ISOLATION RESISTANCE	I/P-O/P:500VDC / 100M Ohms MIN.													
ISOLATION CAPACITANCE	80pF max.													
WORKING TEMP., HUMIDITY	-15°C~+60°C, 20%~90% RH (NO DERATING); 80% LOAD @ 71°C													
STORAGE TEMP., HUMIDITY	-25°C~+85°C, 10%~95% RH													
DIMENSION	0.89"*0.39"*0.33"													
WEIGHT	3.1g													
CASE MATERIA L	NON-CONDUCTIVE PLASTIC													
MECHANISM AND PIN CONFIGURATION	9.9 (0.39) 16 1 11 6 10 7 9 8 7.62 (0.30) BOTTOM VIEW 12.7 (0.50) 2.54 (0.10) 3.81 (0.15) 22.6 (0.89) 8.4 (0.33) <table><tr><th>Pin no.</th><th>Output</th></tr><tr><td>1 & 16</td><td>+Vin</td></tr><tr><td>6 & 11</td><td>-Vout</td></tr><tr><td>7 & 10</td><td>+Vout</td></tr><tr><td>8 & 9</td><td>-Vin</td></tr></table>				Pin no.	Output	1 & 16	+Vin	6 & 11	-Vout	7 & 10	+Vout	8 & 9	-Vin
	Pin no.	Output												
	1 & 16	+Vin												
	6 & 11	-Vout												
	7 & 10	+Vout												
8 & 9	-Vin													
UNIT: mm (inch)														

NOTE : 1.ALL PARAMETERS ARE SPECIFIED AT RATED INPUT, RATED LOAD, 25 $^{\circ}\text{C}$ 70% RH. AMBIENT.
2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1 μF & 47 μF CAPACITOR.
3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
4.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD.

