



SUT483J

NPN/PNP Epitaxial Planar Silicon Transistor

Description

- General purpose transistor

Feature


- Both 2SA1980 chip and 2SC5343 chip in SOT-363 package

Ordering Information

Type NO.	Marking	Package Code
SUT483J	3X	SOT-363

Outline Dimensions

unit : mm



Absolute maximum ratings (Tr1, Tr2)

Ta=25°C

Characteristic	Symbol	Ratings		Unit
		Tr1	Tr2	
Collector-Base voltage	V_{CBO}	60	-50	V
Collector-Emitter voltage	V_{CEO}	50	-50	V
Emitter-base voltage	V_{EBO}	5	-5	V
Collector current	I_C	150	-150	mA
Collector dissipation	P_C	150		mW
Junction temperature	T_j	150		°C
Storage temperature range	T_{stg}	-55~150		°C

Electrical Characteristics (Tr1 : NPN)

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	$I_C=100\mu A, I_E=0$	60	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	$I_C=1mA, I_B=0$	50	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	$I_E=10\mu A, I_C=0$	5	-	-	V
Collector cut-off current	I_{CBO}	$V_{CB}=60V, I_E=0$	-	-	0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=5V, I_C=0$	-	-	0.1	μA
DC current gain	h_{FE}	$V_{CE}=6V, I_C=2mA$	70	-	700	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=10mA$	-	-	0.25	V
Transition frequency	f_T	$V_{CE}=10V, I_C=1mA, f=100MHz$	80	-	-	MHz
Collector output capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$	-	2	3.5	pF

Electrical Characteristics (Tr2 : PNP)

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	$I_C=-100\mu A, I_E=0$	-50	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	$I_C=-1mA, I_B=0$	-50	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	$I_E=-10\mu A, I_C=0$	-5	-	-	V
Collector cut-off current	I_{CBO}	$V_{CB}=-50V, I_E=0$	-	-	-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=-5V, I_C=0$	-	-	-0.1	μA
DC current gain	h_{FE}	$V_{CE}=-6V, I_C=-2mA$	120	-	400	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C=-100mA, I_B=-10mA$	-	-	-0.3	V
Transition frequency	f_T	$V_{CE}=-10V, I_C=-1mA, f=100MHz$	80	-	-	MHz
Collector output capacitance	C_{ob}	$V_{CB}=-10V, I_E=0, f=1MHz$	-	4	7	pF

Electrical Characteristic Curves

Tr1 : NPN

Fig. 1 I_C - V_{BE}




Fig. 2 I_C - V_{CE}




Fig. 3 h_{FE} - I_C





Fig. 4 $V_{CE(sat)}$ - I_C



Tr2 : PNP

Fig. 1 I_C - V_{BE}





Fig. 2 I_C - V_{CE}



Electrical Characteristic Curves

Fig. 3 $h_{FE}-I_C$





Fig. 4 $V_{CE(sat)}-I_C$



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.