



Specifications: Stepping Motor T8LNP-60

1. Product Description

Model Number: Stepping Motor T8LNP-60



2. Motor Characteristics

Electrical Characteristics

[Measurement Conditions]

- Motor Configuration: Horizontal output shaft
- Temperature/Humidity: Measurement is, in principle, performed at $-10^{\circ}\text{C}\sim 50^{\circ}\text{C}$ and relative humidity of 30~90%. If in doubt, use the JIS standard temperature state ($25 \pm 2^{\circ}\text{C}$, $65 \pm 5\%$).
- Standard Drive Circuit: LB1836M (Sanyo)

Item	Content	Notes
Model	PM-Type Stepping Motor	
No. of Phases	2	
Number of Magnetic Poles Applied to Rotor	10	
Basic Step Angle	18° (2-phase excitation)	
Rated Voltage	DC 6.5V	
Excitation Method	2-phase bipolar excitation	
Coil Resistance	$60 \pm 10\% \Omega/\text{Phase}$	25°C conversion value
Insulation Class	E Class 115°C	
Insulation Resistance	At least $10\text{M}\Omega$ at 50V DC	
Insulation Resistance	1 min. at 50V AC	
Coil Inductance	$10.5\text{mH}/\text{Phase} \pm 20\%$ (Reference value) (at 1KHz, 1Vrms)	Temperature $25 \pm 2^{\circ}\text{C}$ Humidity $65 \pm 5\%$



Specifications: Stepping Motor T8LNP-60

Mechanical Characteristics

Item	Content	Notes
Motor Configuration	Omnidirectional	
Usage Temperature/ Humidity Range	-20~70°C	
Storage Temperature Range	-40~80°C	(Standard temperature of 20°C and relative humidity of 65% assumed)
Rotation Direction	Bi-directional Rotation	The sequence is shown in the diagram on Page 6.
Rotor Inertia	0.0093g•cm ²	Calculated Value
Pull-in Torque	At least 0.30mN• m	V = 6.5V, (between the motor terminals) 2-phase excitation, 500pps
Maximum Response Frequency	At least 2000pps (zero load)	V = 6.5V, (between the motor terminals)
Maximum Actuation Fre- quency	At least 1000pps (zero load)	2-phase excitation
Holding Torque	At least 0.6mN• m	Temperature 25 ±2°C Humidity 65 ±5% V=5.0V, (between the motor ter- minals) 2-phase excitation
Detent Torque	Less than 0.20mN• m	
Noise	Less than 55dB	V = 6.5V, (between the motor terminals) 2-phase excitation, 500pps Measurement Environment In an environment with a noise level of less than 25dB, set a noise measurement device equipped with a photocoupler to the A range, then perform mea- surement with a distance of 1cm from the photocoupler to the motor.
Vibration	Less than 6.0m/s ²	V = 6.5V, (between the motor terminals)



Specifications: Stepping Motor T8LNP-60

Reliability

Item	Conditions/Test Environment	Determination Standard
Operation Lifetime Testing	-10°C: 20,000 rotations Room Temperature: 30, 000 rotations 50°C: 20,000 rotations Operation. Filter: Open Closed Assumes a 2 second rest.	Perform testing at the conditions at left with the actual device provided by Sanyo Electric. After testing, the determination standards table should be satisfied.
Thermal Shock Test	Performed for 100 cycles with a pattern of -20°C: 30 minutes, 60°C: 30 minutes.	Should satisfy the determinations standards table after 1 hour or more placement at normal temperature and humidity.
Low Temperature Testing	Temperature: -40 ±2°C Storage Time: 72 Hours	Should satisfy the determinations standards table after 1 hour or more placement at normal temperature and humidity.
High Temperature Testing	Temperature: 80 ±2°C Storage Time: 168 Hours	Should satisfy the determinations standards table after 1 hour or more placement at normal temperature and humidity.
Humidity Resistance Testing	Temperature: 40 ±2°C Humidity: 90% Placement Time: 168 Hours	Should satisfy the determinations standards table after 1 hour or more placement at normal temperature and humidity.
Temperature Characteristics Testing	Temperature: -20 ±2°C 70°C: ±2 Placement Time: 5 Hours	Should satisfy the determination standards table under the environment at left.
Vibration Testing	Fix the motor to a jig No. of Vibrations: 1000 c.p.m. Amplitude: 3mm Direction: X, Y, Z Time: 30 minutes in each direction	Should satisfy the determination standards table.
Drop Testing	With the motor in its smallest packaging state, perform a free-fall drop once onto each of the six sides onto a concrete bed from a height of 80cm.	Should satisfy the determination standards table.
Solder Temperature Resistance	On the input terminals: Temperature: 350 °C Time: 3 sec. Solder Type: 60% eutectic solder	Should satisfy the determination standards table.
Solderability	On the input terminals: Temperature: 230 ±5°C Time: 5 sec. Solder Type: 60% eutectic solder	Should be covered by at least 95% new solder. The flux should be a rosin-type.



Specifications: Stepping Motor T8LNP-60

Reliability Determination Standards Table

Reliability Item		1 Operation Lifetime Testing	2 Thermal Shock Test	3 Low Temperature Testing	4 High Temperature Testing	5 Humidity Resistance Testing	6 Temperature Characteristics Testing	7 Vibration Testing	8 Drop Testing	9 Solder Temperature Resistance
Number	Characteristic Item									
7	Pull-in Torque	○	○	○	○	○	○	○	○	○
1	Coil Resis- tance	○	NA	NA	NA	NA	NA	NA	NA	NA
3	Insulation Resistance	○	NA	NA	NA	NA	NA	NA	NA	NA
8	Maximum Response Frequency	○	○	○	○	○	○	○	○	○
9	Maximum Actuation Frequency	○	○	○	○	○	○	○	○	○

*Note: Reliability Determination Standard 1 is determined by 5 samplings where AC = 0 and RE = 1.



