

TD62593AFN, TD62594AFN, TD62597AFN, TD62598AFN
8ch SINGLE DRIVER : COMMON EMITTER

The TD62593, 4, 7, 8AFN are comprised of eight NPN Transistor Arrays.


Applications include relay, hammer, lamp and display (LED) drivers.

FEATURES



- Package Type : SSOP18pin
- High Sustaining Voltage Output : 50V (MIN.)
- Low Saturation Voltage : $V_{CE(sat)} = 0.8V$
 $@I_{OUT} = 150mA$ Inputs Compatible with Various type Logic.

TD62593AFN, TD62597AFN : $R_{IN} = 2.7k\Omega$ TTL, 5V CMOS

TD62594AFN, TD62598AFN : $R_{IN} = 10.5k\Omega$ 6~15V PMOS, CMOS





Weight : 0.09g (Typ.)

PIN CONNECTION (TOP VIEW)


961001EBA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

SCHEMATICS (EACH DRIVER)



Note : The input and output parasitic diodes cannot be used as clamp diodes.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Emitter Voltage	V_{CEO}	50	V
Collector-Base Voltage	V_{CBO}	50	V
Clamp Diode Reverse Voltage	V_R *1	50	V
Collector Current	I_C	200	mA / ch
Input Voltage	V_{IN}	-0.5~30	V
Power Dissipation	P_D *2	0.96	W
Operating Temperature	T_{opr}	-40~85	°C
Storage Temperature	T_{stg}	-55~150	°C

*1 : Except TD62593AFN, TD62594AFN

*2 : On Glass Epoxy PCB (50×50×1.6mm Cu 40%)

RECOMMENDED OPERATING CONDITIONS (Ta = -40~85°C)

CHARACTERISTIC		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Collector-Emitter Voltage		V _{CEO}		0	—	50	V	
Collector-Base Voltage		V _{CBO}		0	—	50	V	
Collector Current		I _C		0	—	150	mA / ch	
Clamp Diode Reverse Voltage		V _R *1		7	—	50	V	
Input Voltage		V _{IN}		0	—	25	V	
Input Current		I _{IN}		0	—	10	mA	
Input Voltage (Output On)	TD62593AFN	V _{IN} (ON)		2.4	—	25	V	
	TD62597AFN							
	TD62594AFN			7.0	—	25		
	TD62598AFN							
Power Dissipation		P _D *2		—	—	0.4	W	






*1 : Except TD62593AFN, TD62594AFN

*2 : On Glass Epoxy PCB (50×50×1.6mm Cu 40%)

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Leakage Current	I_{CEX}	1	$V_{CE} = 50V, V_{IN} = 0$	—	—	10	μA
Output Saturation Voltage	$V_{CE(sat)}$	2	$I_C = 10mA, I_{IN} = 0.4mA$	—	—	0.2	V
			$I_C = 150mA, I_{IN} = 3.0mA$	—	—	0.8	
DC Current Transfer Ratio	h_{FE}	2	$V_{CE} = 10V, I_C = 10mA$	50	—	—	
Input Current	TD62593AFN TD62597AFN	3	$V_{IN} = 2.4V, I_C = 50mA$	—	—	0.9	mA
	TD62594AFN TD62598AFN		$V_{IN} = 7.0V, I_C = 50mA$	—	—	0.9	
Turn-On Delay	t_{ON}	4	$V_{OUT} = 50V, R_L = 330\Omega$	—	0.1	—	μs
Turn-Off Delay	t_{OFF}			—	3.0	—	

TEST CIRCUIT

1. I_{CEX} 2. $h_{FE}, V_{CE(sat)}$ 3. $I_{IN(ON)}$ 4. t_{ON}, t_{OFF} 

(Note 1) Pulse Width 50 μs , Duty Cycle 10%
Output Impedance 50 Ω , $t_r \leq 5ns$, $t_f \leq 10ns$

(Note 2) See below







Input Condition

Type	R_{IN}	V_{IH}
TD62593AFN, TD62597AFN	0 Ω	3V
TD62594AFN, TD62598AFN	0 Ω	10V

(Note 3) C_L includes probe and jig capacitance

PRECAUTIONS for USING


Utmost care is necessary in the design of the output line, V_{CC} and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.



OUTLINE DRAWING

SSOP18-P-225-0.65

Unit : mm



Weight : 0.09g (Typ.)

Copyright Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com