

VI TELEFILTER**Filter Specification****TFS 440A****1/5****Measurement condition**

Ambient temperature: 23 °C
 Input power level: 0 dBm
 Terminating impedances *)
 for input: 300 Ω // -0,8 pF
 for output: 300 Ω // -0,8 pF
 Coupling coil: 56 nH

Characteristics**Remark:**

Reference level for the relative attenuation a_{rel} of the TFS440A is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 1.5 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed on 440 MHz without tolerance. The given values for the relative attenuation a_{rel} and for the group delay ripple have to be reached at the frequencies given below also if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

Data		typ. value		tolerance/limit	
Insertion loss (Reference level)	$a_e = a_{min}$	-		max.	6,5 dB
Nominal frequency	f_N	-			440,00 MHz
Centre frequency	f_c	440,015	MHz		
Pass band ripple	$f_N \pm 70$ kHz	0,5	dB	max.	1,5 dB
Relative attenuation	a_{rel}				
f_N ... $f_N \pm 70$ kHz		0,5	dB	max.	1,5 dB
$f_N \pm 70$ kHz ... $f_N \pm 100$ kHz		1,2	dB	max.	3,0 dB
$f_N \pm 0,4$ MHz ... $f_N \pm 0,6$ MHz		32	dB	min.	25 dB
$f_N \pm 0,6$ MHz ... $f_N \pm 0,8$ MHz		48	dB	min.	40 dB
$f_N \pm 0,8$ MHz ... $f_N \pm 3$ MHz		63	dB	min.	50 dB
$f_N \pm 3$ MHz ... $f_N \pm 78$ MHz		64	dB	min.	50 dB
Group delay ripple	GD				
$f_N \pm 100$ kHz		0,9	µs	max.	2,0 µs
Input power level		-		max.	5 dBm
Operating temperature range					- 20 °C ... + 70 °C
Storage temperature range					- 35 °C ... + 85 °C
Temperature coefficient of frequency	TC	- 0.036	ppm/K ²		
Frequency inversion temperature		+ 25	°C		

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.


Generated:**Checked / approved:****VI TELEFILTER****Potsdamer Straße 18****14513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com****Vectron International Inc.****267 Lowell Road****Hudson, NH 03051 / USA****Tel: (603) 598-0070 Fax: (603) 598-0075****E-Mail: yti@vtinh.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.





VI TELEFILTER**Filter Specification****TFS 440A****2/5****Construction, pin configuration and 50 Ω - matching network**

(All dimensions in mm)



Pin 1	Sym. Output	Pin 5	Sym. Input
Pin 2	Sym. Output	Pin 6	Sym. Input
Pin 3	External Coil	Pin 7	Ground
Pin 4	Package Ground	Pin 8	Package ground

Date code:	Year + week
M	2000
N	2001
P	2002
...	

50 Ohm Test circuit 1**50 Ohm Test circuit 2**

VI TELEFILTER**Filter Specification****TFS 440A****3/5****Stability Characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 1,5 mm or 20g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2-14 Test N
4. Resistance to solder heat (reflow): max. 2 times reflow process;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


Packing

Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters per reel: 3000
reel of empty components at start: min 300 mm
reel of empty components at start including leader: min 500 mm
trailer: min 300 mm

Tape (all dimensions in mm)

W : 12 ± 0,3
Po : 4 ± 0,1
Do : 1,5 ± 0,1
E : 1,75 ± 0,1
F : 5,5 ± 0,05
G (min) : 0,75
P2 : 2 ± 0,05
P1 : 8 ± 0,1
D1(min) : 1,5
Ao : 4,3 ± 0,1
Bo : 4,3 ± 0,1
CT : 9,5 ± 0,1

**Reel (all dimensions in mm):**

A : 330
W1 : 12,4 ± 0,2
W2 (max) : 18,4
N (min) : 50
C : 13 ± 0,5 / -0,2



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. The marking of the filters is able to read if the view is directed on the upper side of the carrier tape with the sprocket holes on the right side of the tape.

VI TELEFILTER**Filter Specification****TFS 440A****4/5****Air reflow temperature conditions**

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


Chip-mount air reflow profile

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER**Filter Specification****TFS 440A****5/5**

History

Version	Reason of Changes	Name	Date
1.0	- Generation of specification	Dr. Wall	25.01.2001
1.1	- Add typical values and termination impedances. - Change stability characteristic.	Dr. Wall	09.11.2001
1.2	- Add comment for terminating impedances. - Correct date code and tape and reel information.	Dr. Wall	19.12.2001