

TOSHIBA

MICROWAVE SEMICONDUCTOR

TECHNICAL DATA

MICROWAVE POWER GaAs FET

TIM6472-35SL

FEATURES:

- LOW INTERMODULATION DISTORTION
IM₃ = -45 dBc at Po 35.0 dBm
- HIGH POWER
P_{1dB} = 45.5 dBm at 6.4 to 7.2 GHz
- HIGH EFFICIENCY
 η_{add} = 37% at 6.4 to 7.2 GHz
- HIGH GAIN
G_{1dB} = 8.0dB at 6.4 to 7.2 GHz
- BROAD BAND INTERNALLY MATCHED
- HERMETICALLY SEALED PACKAGE

RF PERFORMANCE SPECIFICATIONS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Output Power at 1 dB Compression Point	P _{1dB}	V _{DS} = 10V f = 6.4~7.2GHz	dBm	45.0	45.5	-
Power Gain at 1 dB Compression Point	G _{1dB}		dB	7.0	8.0	-
Drain Current	I _{DS}		A	-	8.0	9.0
Gain Flatness	ΔG		dB	-	-	± 0.8
Power Added Efficiency	η_{add}		%	-	37	-
3rd Order Intermodulation Distortion	IM ₃	Note 1	dBc	-42	-45	-
Channel Temperature Rise	ΔT_{ch}	V _{DS} × I _{DS} × R _{th(c-c)}	°C	-	-	100

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Trans-conductance	gm	V _{DS} = 3V I _{DS} = 10.5A	mS	-	6500	-
Pinch-off Voltage	V _{GSoff}	V _{DS} = 3V I _{DS} = 140mA	V	-1.0	-2.5	-4.0
Saturated Drain Current	I _{DSS}	V _{DS} = 3V V _{GS} = 0V	A	-	20	26
Gate-Source Breakdown Voltage	V _{GS0}	I _{GS} = -420 μ A	V	-5	-	-
Thermal Resistance	R _{th(c-c)}	Channel to Case	°C/W	-	1.0	1.3

Note 1: 2 tone Test Pout = 35dBm Single Carrier Level.

Recommended Gate Resistance(R_g) : R_g = R_{g1}(10 Ω) + R_{g2}(18 Ω) = 28 Ω (MAX.)

★ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.

★ The information contained herein may be changed without prior notice. It is therefore advisable to contact TOSHIBA before proceeding with the design of equipment incorporating this product.




TIM6472-35SL

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	UNIT	RATING
Drain-Source Voltage	V _{DS}	V	15
Gate-Source Voltage	V _{GS}	V	-5
Drain Current	I _{DS}	A	26
Total Power Dissipation (Tc=25°C)	P _T	W	115
Channel Temperature	T _{ch}	°C	175
Storage Temperature	T _{stg}	°C	-65~175

PACKAGE OUTLINE (2-16G1B)




HANDLING PRECAUTIONS FOR PACKAGED TYPE

Soldering iron should be grounded and the operating time should not exceed 10 seconds at 260°C.


TIM6472-35SL

RF PERFORMANCES

Output Power vs. Frequency




Output Power vs. Input Power



TIM6472-35SL

POWER DISSIPATION VS. CASE TEMPERATURE



IM₃ VS. OUTPUT POWER CHARACTERISTICS

