

# GENERAL ACCESSORIES

## Multimeters

In addition to the general accessories shown, B&K also offers a broad range of product-specific accessories. Visit individual product overview pages on our website to see available accessories.



### 40 kV High Voltage DMM Probe

Model PR 28A

For voltage measurements above the specifications of general purpose probes.

Specifications	PR 28A
Attenuation	x1000
Voltage (AC)	20 kV
Voltage (DC)	40 kV
Bandwidth	60 Hz
Input Impedance	1000 MΩ
Accuracy (AC & DC)	±3%
Cable Length	48" (1.2 m)



### Maxi-Pro DMM Kit

TL-50 Kit

Complete accessory kit for all your testing needs. Includes soft, flexible silicone lead wire for easy movement.

- IEC61010-2-031 compliant
- Silicone lead wire length 60" (1.5 m)
- Tri-fold velcro pouch

Description	TL-50		
4mm Straight to Right-Angle Silicone Leads, 1.5 m	1000V	CATIII	12 A
Probe Bodies w/Ø2 mm Tip	1000V	CATIII	36 A
Pincer Style Clips	1000V	CATIII	6 A
Alligator Clips	300V	CATI	3 A
Spade Lug Adapters	42 V (1000 V)		36 A
Banana Plug Adapters	42 V (1000 V)		36 A
Fully Insulated Alligator Clips	1000 V	CATIII	20 A



### Deluxe Test Lead Sets

TL 2A Kit

- IEC61010 1000V CATIII rating
- Silicone lead wire length 60" (1.5 m)
- Black alligator clip included
- Threaded tips fits TL 3 accessory kit items



### Probe Accessory Kit

TL 3 Kit

- Threaded accessories to fit TL 2 A probes – black and red pairs (except for alligator clip)
- Alligator clip, red only
- Spring hook clips
- 4" sharp extension tips to reach tight test points
- No. 10 spade lugs



### Special BNC Cable Assemblies

CC-21

Standard BNC to Alligator clips or Sheathed Stacking Plugs. The CC-21, black, molded strain release boots provides for long-life. RG58C/U cable with 50 Ω impedance.

Specifications	CC-21
Impedance	50Ω
Cable	RG58 C/U
Connectors	BNC m to Alligator Clips
Voltage	500 Vrms
VSWR	≤1.2
Cable Length	40" (1.0 m)



### General Purpose DMM Kit

TL 130A Kit

If you need only one basic accessory kit for your meter, this is the one. Attach probes or clips to the sheath plug to complete your test. Soft, flexible silicone leads make movement easy. Kit is voltage and current rated for electronic or electrical applications.

- IEC61010-2-031 compliant
- Silicone lead wire length 60" (1.5 m)
- Tri-fold velcro pouch

Description	TL-130A		
4mm Straight to Right-Angle Silicone Leads, 1.5 m	1000V	CATIII	12 A
Probe Bodies w/Ø2mm Tip	1000V	CATIII	36 A
Alligator Style Clips	1000V	CATIII	20 A
Alligator Clips	300V	CATI	3 A



### DC/AC Current Clamp

Model CP 3

- Converts any DMM to a current clamp
- Measures current without disconnecting circuit under test
- Measures to 400 A DC or AC
- Outputs 1 mV per Amp, operates on 2 V range of any DMM

Specifications	CP 3
(Accuracy specified at 18° to 28°C)	
Current Range	2 A to 400 A, DC or AC
Frequency Response (AC)	50 Hz - 400 Hz
Accuracy	±(2% reading + 2A)
Input Resistance	10 kΩ min.
Maximum Conductor Size	1.1" (30 mm)
Power Requirement	9 V battery, NEDA 1604
Battery Life	100 hr typical
Operating Temperature	0° to 40°C, <70% RH
Storage Temperature	-20° to + 70°C, <80% RH