



TPN3021

Application Specific Discretes
A.S.D.TM

TRIPOLAR OVERVOLTAGE PROTECTION FOR NETWORK INTERFACES

FEATURES

- TRIPLE CROWBAR PROTECTION
- PEAK PULSE CURRENT : $I_{PP} = 30\text{ A}$, $10/1000\mu\text{s}$
- VERY LOW CAPACITANCE :
 $C = 30\text{ pF}$
- PROTECTS HIGH-SPEED LINE DRIVERS / RECEIVERS


DESCRIPTION

Dedicated to dataline protection, this device provides a triple protection function. It ensures the same protection capability with the same breakdown voltage both in common mode and in differential mode.


With a stand-off voltage of 28V and a very low capacitance, this device is able to protect high-speed interfaces such as T1/E1 interface.

COMPLIES WITH THE FOLLOWING STANDARDS :

- | | | |
|------------|----------|---------------------|
| - IEC801-2 | 15kV | (air discharge) |
| - IEC801-4 | 40A | (repetitive 2.5kHz) |
| - IEC801-5 | 1.2/50μs | 4kV |
| | 8/20μs | 100A |



SCHEMATIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25^\circ\text{C}$)

Symbol	Parameter	Value	Unit
I_{pp}	Peak pulse current	30 150	A A
T_{stg} T_j	Storage temperature range Maximum junction temperature	- 40 to + 150 150	°C °C
T_L	Maximum lead temperature for soldering during 10s	260	°C


THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to ambient	170	°C/W

TPN3021

ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}\text{C}$)

Symbol	Parameter
V_{RM}	Stand-off voltage
V_{BO}	Breakover voltage
V_{BR}	Breakdown voltage
I_H	Holding current
I_{BO}	Breakover current
I_{RM}	Leakage current at V_{RM}
I_{PP}	Peak pulse current
C	Capacitance
αT	Temperature coefficient



Type	$I_{RM} @ V_{RM}$ max. note 1		$V_{BO} @ I_{BO}$ max.		I_H min. note 2	C typ. note 3	αT typ. note 4
	μA	V	V	mA			
	4	28	38	100	30	25	30


Note 1 : Between any I/Opin and Ground or between I/O1 and I/O2.

Note 2 : See the functional holding current (I_H) test circuit.

Note 3 : Between any I/Opin and GND or between I/O1 and I/O2 at 0V bias, $VRMS = 30 \text{ mV}$, $F = 1 \text{ MHz}$.

Note 4 : $\Delta V_{BO} = \alpha T \times (T_{amb} - 25) \times V_{BO}(25^{\circ}\text{C})$.

FUNCTIONAL HOLDING CURRENT (I_H) TEST CIRCUIT : GO-NO GO TEST



This is a GO-NO GO test which allows to confirm the holding current (I_H) level in a functional test circuit.

TEST PROCEDURE :

- Adjust the current level at the I_H value by short circuiting the D.U.T.
- Fire the D.U.T. with a surge current : $I_{PP} = 10\text{A}$, $10/1000 \mu\text{s}$.
- The D.U.T. will come back to the off-state within a duration of 50 ms max.

APPLICATION CIRCUIT : T1/E1 Interface Protection






Fig. 1 : Surge peak current versus overload duration.



TPN3021


ORDER CODE



Marking

Type	Marking
TPN3021	TPN302

PACKAGE MECHANICAL DATA SO8 (Plastic)



REF.	DIMENSIONS					
	Millimetres			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.75			0.069
a1	0.1		0.25	0.004		0.010
a2			1.65			0.065
b	0.35		0.48	0.014		0.019
b1	0.19		0.25	0.007		0.010
C		0.50			0.020	
c1	45°(typ)					
D	4.8		5.0	0.189		0.197
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		3.81			0.150	
F	3.8		4.0	0.15		0.157
L	0.4		1.27	0.016		0.050
M			0.6			0.024
S	8° (max)					

Packaging = Products supplied in antistatic tubes or tape and reel.

Weight = 0.08 g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1998 SGS-THOMSON Microelectronics - Printed in Italy - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Italy - Japan - Korea - Malaysia - Malta - Morocco
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.