



TR03-400T

SENSITIVE AND FAST ASYMETRICAL SCR

PRELIMINARY DATA


FEATURES

- VERY FAST SCR : $t_q = 15\mu s$ max.
- LOW GATE TRIGGER CURRENT : $I_{GT} = 1.5mA$ max.

DESCRIPTION

The TR03 brings the best compromise between a fast turn off time and a low gate trigger current for applications where fast switching and sensitive control is requested.

Packaged in TO220AB, the TR03 uses high performance planar technology.

TO220AB
(Plastic)

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
V_{DRM}	Repetitive peak off-state voltage		400	V
$I_{T(RMS)}$	RMS on-state current (180° conduction angle)	$T_c = 85^\circ C$	3.5	A
$I_{T(AV)}$	Average on-state current (180° conduction angle)	$T_c = 85^\circ C$	2	A
I_{TSM}	Non repetitive surge peak on-state current (T_j initial = 25°C)	$t_p = 10ms$	20	A
I^2t	I^2t Value for fusing	$t_p = 10ms$	2	A^2s
dI/dt	Critical rate of rise of on-state current Gate supply $I_G = 150 mA$	$dI_G/dt = 1 A/\mu s$	100	$A/\mu s$
T_{stg} T_j	Storage junction temperature range Operating junction temperature range		- 40 to + 150 - 40 to + 125	°C
T_I	Maximum lead temperature for soldering during 10s at 4.5 mm from case		260	°C

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th}(j-a)$	Junction to ambient	60	°C/WV
$R_{th}(j-c)$	Junction to case for DC	5	°C/W

TR03-400T

GATE CHARACTERISTICS (maximum values)

$P_G(AV) = 0.5\text{W}$ $P_{GM} = 2.5\text{ W}$ ($t_p = 20\ \mu\text{s}$) $I_{FGM} = 0.5\text{ A}$ ($t_p = 20\ \mu\text{s}$) $V_{RGM} = 5\text{ V}$

ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions	Type	Value	Unit	
I_{GT}	$V_D=6\text{V}$ (DC) $R_L=100\Omega$	$T_j=25^\circ\text{C}$	MAX	1.5	mA
V_{GT}	$V_D=6\text{V}$ (DC) $R_L=100\Omega$ $R_{GK} = 1\text{k}\Omega$	$T_j=25^\circ\text{C}$	MAX	1.2	V
V_{GD}	$V_D=V_{DRM}$ $R_L=3.3\text{k}\Omega$ $R_{GK} = 1\text{k}\Omega$	$T_j=125^\circ\text{C}$	MIN	0.2	V
I_H	$I_T=100\text{mA}$ Gate open	$T_j=25^\circ\text{C}$	TYP	5	mA
V_{TM}	$I_{TM}=10\text{A}$ $t_p=380\mu\text{s}$	$T_j=25^\circ\text{C}$	MAX	2.2	V
I_{DRM}	V_{DRM} rated $R_{GK} = 1\text{k}\Omega$	$T_j=25^\circ\text{C}$	MAX	0.01	mA
		$T_j=125^\circ\text{C}$	MAX	0.2	
dV/dt	$V_D=67\%V_{DRM}$ $R_{GK} = 1\text{k}\Omega$	$T_j=125^\circ\text{C}$	MIN	20	V/ μs
t_q	$I_{TM}=10\text{A}$ $dI/dt = 20\text{ A}/\mu\text{s}$ $V_D = 67\% V_{DRM}$	$T_j=85^\circ\text{C}$	MAX	15	μs

PACKAGE MECHANICAL DATA
TO220AB(Plastic)

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	10.0	10.4	0.393	0.409
B	15.2	15.9	0.598	0.626
C	13	14	0.511	0.551
D	6.2	6.6*	0.244	0.260
E	16.4 typ.		0.645 typ.	
F	3.5	4.2	0.137	0.165
G	2.65	2.95	0.104	0.116
H	4.4	4.6	0.173	0.181
I	3.75	3.85	0.147	0.151
J	1.23	1.32	0.048	0.051
K	1.27 typ.		0.050 typ.	
L	0.49	0.70	0.019	0.027
M	2.4	2.72	0.094	0.107
N	4.95	5.15	0.194	0.203
N1	2.40	2.70	0.094	0.106
O	1.14	1.70	0.044	0.067
P	0.61	0.88	0.024	0.034

Cooling method : C

Marking : Type number

Weight : 2.0g

Recommended torque value : 0.55 m.N.

Maximum torque value : 0.70 m.N.

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - Printed in Italy - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.