



TR2007SF

Rectifier Diode

APPLICATIONS

- Rectification
- Freewheel Diode
- DC Motor Control
- Power Supplies
- Welding
- Battery Chargers

KEY PARAMETERS

V_{RRM}	4000V
$I_{F(AV)}$	1225A
I_{FSM}	25000A


FEATURES

- Double Side Cooling
- High Surge Capability

VOLTAGE RATINGS

Type Number	Repetitive Peak Reverse Voltage V_{RRM} V	Conditions
TR2007SF40	4000	$V_{RSM} = V_{RRM} + 100V$
TR2007SF39	3900	
TR2007SF38	3800	
TR2007SF37	3700	
TR2007SF36	3600	
TR2007SF35	3500	


Lower voltage grades available.



Outline type code: F.
See Package Details for further information.

CURRENT RATINGS

Symbol	Parameter	Conditions	Max.	Units
Double Side Cooled				
$I_{F(AV)}$	Mean forward current	Half wave resistive load, $T_{case} = 100^{\circ}C$	1225	A
$I_{F(RMS)}$	RMS value	$T_{case} = 100^{\circ}C$	1923	A
I_F	Continuous (direct) forward current	$T_{case} = 100^{\circ}C$	1720	A
Single Side Cooled (Anode side)				
$I_{F(AV)}$	Mean forward current	Half wave resistive load, $T_{case} = 100^{\circ}C$	820	A
$I_{F(RMS)}$	RMS value	$T_{case} = 100^{\circ}C$	1287	A
	Continuous (direct) forward current	$T_{case} = 100^{\circ}C$	1050	A



TR2007SF

SURGE RATINGS

Symbol	Parameter	Conditions	Max.	Units
I_{FSM}	Surge (non-repetitive) forward current	10ms half sine; $T_{case} = 150^{\circ}C$ $V_R = 50\% V_{RRM} - 1/4$ sine	20.0	kA
I^2t	I^2t for fusing		2.0×10^6	A ² s
I_{FSM}	Surge (non-repetitive) forward current	10ms half sine; $T_{case} = 150^{\circ}C$ $V_R = 0$	25.0	kA
I^2t	I^2t for fusing		3.125×10^6	A ² s

THERMAL AND MECHANICAL DATA

Symbol	Parameter	Conditions		Min.	Max.	Units
$R_{th(j-c)}$	Thermal resistance - junction to case	Double side cooled	dc	-	0.022	$^{\circ}C/W$
		Single side cooled	Anode dc	-	0.038	$^{\circ}C/W$
			Cathode dc	-	0.052	$^{\circ}C/W$
$R_{th(c-h)}$	Thermal resistance - case to heatsink	Clamping force 19.5kN with mounting compound	Double side	-	0.004	$^{\circ}C/W$
			Single side	-	0.008	$^{\circ}C/W$
T_{vj}	Virtual junction temperature	Forward (conducting)		-	160	$^{\circ}C$
		Reverse (blocking)		-	150	$^{\circ}C$
T_{stg}	Storage temperature range			-55	175	$^{\circ}C$
-	Clamping force			18.0	22.0	kN

CHARACTERISTICS

Symbol	Parameter	Conditions	Min.	Max.	Units
V_{FM}	Forward voltage	At 3400A peak, $T_{case} = 25^{\circ}C$	-	1.6	V
I_{RRM}	Peak reverse current	At V_{RRM} , $T_{case} = 150^{\circ}C$	-	75	mA
Q_S	Total stored charge	$I_F = 2000A$, $dI_{RR}/dt = 3A/\mu s$, $T_{case} = 150C$, $V_R = 100V$	-	3500	μC
I_{RR}	Peak recovery current		-	110	A
V_{TO}	Threshold voltage	At $T_{vj} = 150C$	-	0.82	V
r_T	Slope resistance	At $T_{vj} = 150C$	-	0.29	m Ω

CURVES




Fig. 1 Maximum (limit) forward characteristics




Fig. 2 Dissipation curves




Fig. 3 Maximum total stored charge




Fig. 4 Maximum reverse recovery current




Fig. 5 Surge (non-repetitive) forward current vs time (with 50% V_{RRM} , $T_{case} = 150C$)





Fig. 6 Transient thermal impedance - junction to case - (C/W)

PACKAGE DETAILS

For further package information, please contact your local Customer Service Centre. All dimensions in mm, unless stated otherwise. DO NOT SCALE.



Nominal weight: 500g
Clamping force: $19.6 \text{ kN} \pm 10\%$

Package outline type code: F