查询MBRS320TRPBF供应商

Bulletin PD-20410 07/04

International
IOR Rectifier

MBRS320TRPbF

SCHOTTKY RECTIFIER

3 Amp

$I_{F(AV)}$ = 3.0Amp
V_R = 20V

Major Ratings and Characteristics

Characteristics	Value	Units
$I_{F(AV)}$ Rectangular waveform	3.0	A
V_{RRM}	20	V
I_{FSM} @t_p=5µs sine	820	A
V_F @3.0Apk, T_J=125°C	0.36	V
T_J range	- 65 to 150	°C

Description/ Features

The MBRS320TRPbF surface-mount Schottky rectifier has been designed for applications requiring low forward drop and small foot prints on PC boards. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Small foot print, surface mountable
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free ("PbF" suffix)

Case Styles

MBRS320TRPbF



SMC

Voltage Ratings

Part number		MBRS320PbF
V_R	Max. DC Reverse Voltage (V)	20
V_{RWM}	Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters		Value	Units	Conditions	
$I_{F(AV)}$	Max. Average Forward Current	3.0	A	50% duty cycle @ T_L = 136°C, rectangular wave form	
I_{FSM}	Max. Peak One Cycle Non-Repetitive Surge Current	820		5µs Sine or 3µs Rect. pulse	Following any rated load condition and with rated V_{RRM} applied
		80		10ms Sine or 6ms Rect. pulse	
E_{AS}	Non Repetitive Avalanche Energy	4	mJ	T_J = 25 °C, I_{AS} = 1.0A, L = 8mH	
I_{AR}	Repetitive Avalanche Current	1.0	A	Current decaying linearly to zero in 1 µsec Frequency limited by T_J max. Va = 1.5 x Vr typical	

Electrical Specifications

Parameters		Typ.	Max.	Units	Conditions	
V_{FM}	Max. Forward Voltage Drop (1)	0.41	0.45	V	@ 3A	T_J = 25 °C
		0.45	0.53	V	@ 6A	
		0.29	0.36	V	@ 3A	T_J = 125 °C
		0.35	0.46	V	@ 6A	
I_{RM}	Max. Reverse Leakage Current (1)	0.04	0.5	mA	T_J = 25 °C	V_R = rated V_R
		8.0	20	mA	T_J = 100 °C	
		23	35	mA	T_J = 125 °C	
C_T	Typical Junction Capacitance	360	-	pF	V_R = 5V_{DC} (test signal range 100kHz to 1Mhz), @ 25°C	
L_S	Typical Series Inductance	3.0	-	nH	Measured lead to lead 5mm from package body	
dv/dt	Max. Voltage Rate of Change	-	10000	V/ µs	(Rated V_R)	

(1) Pulse Width < 300µs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters		Value	Units	Conditions
T_J	Max. Junction Temperature Range (*)	- 65 to 150	°C	
T_{stg}	Max. Storage Temperature Range	- 65 to 150	°C	
R_{thJL}	Max. Thermal Resistance Junction to Lead (**)	12	°C/W	DC operation
R_{thJA}	Max. Thermal Resistance Junction to Ambient	46	°C/W	
Wt	Approximate Weight	0.24(0.008)	gr (oz)	
	Case Style	SMC		Similar DO-214AB
	Device Marking	IR32		

(*) $\frac{dPtot}{dTj} < \frac{1}{Rth(j\text{-}a)}$ thermal runaway condition for a diode on its own heatsink

(**) Mounted 1 inch square PCB



Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)



Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)



Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)



Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)



Fig. 5 - Maximum Average Forward Current Vs. Allowable Lead Temperature



Fig. 6 - Maximum Average Forward Dissipation Vs. Average Forward Current



Fig. 7 - Maximum Peak Surge Forward Current Vs. Pulse Duration

(2) Formula used: $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$;
Pd = Forward Power Loss = $I_{F(AV)} \times V_{FM}$ @ $(I_{F(AV)} / D)$ (see Fig. 6);
Pd_{REV} = Inverse Power Loss = $V_{R1} \times I_R (1 - D)$

Outline Table

Device Marking: IR32





Outline SMC

Dimensions in millimeters and (inches)

For recommended footprint and soldering techniques refer to application note #AN-994

Marking & Identification

Each device has 2 rows for identification. The first row designates the device as manufactured by International Rectifier, indicated by the letters "IR", and the Part Number (indicates the current, the voltage rating and Schottky Generation). The second row indicates the year, the week of manufacturing and the Site ID.





Tape & Reel Information



Dimensions in millimetres and (inches)

Ordering Information Table

Device Code

MBR	S	3	20	TR	PbF
1	2	3	4	5	6

1	-	Schottky MBR Series
2	-	S = SMC
3	-	Current Rating (3 = 3 A)
4	-	Voltage Rating (20 = 20V)
5	-	TR = Tape & Reel (3000 pieces)
6	-	• none = Standard Production
		• PbF = Lead-Free

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level and Lead-Free.
Qualification Standards can be found on IR's Web site.

International IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 07/04

WWW.ALLDATASHEET.COM

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com