

 TS1085 3A Low Dropout Positive Voltage Regulator	   Pin assignment: 1. Ground / Adj 2. Output 3. Input	Low Dropout Voltage 1.3V max.
General Description		


The TS1085 Series are high performance positive voltage regulators are designed for use in applications requiring low dropout performance at full rated current, additionally, the PJ1085 Series provides excellent regulation over variations due to changes in line, load and temperature. Outstanding features include low dropout performance at rated current, fast transient response, internal current limiting and thermal shutdown protection of the output device. The TS1085 Series are three terminal regulators with fixed and adjustable voltage options available in popular packages.

This series is offered in 3-pin TO-263, TO-220 and TO-252 package.

Features

- ◊ Low dropout performance 1.3V max.
- ◊ Full current rating over line and temperature.
- ◊ Fast transient response
- ◊ ±2%Total output regulation over line, load and temperature
- ◊ Adjust pin current max 90µA over temperature
- ◊ Line regulation typical 0.015%.
- ◊ Load regulation typical 0.05%.
- ◊ Fixed/adjustable output voltage
- ◊ TO-220, TO-263 and TO-252 package

Block Diagram



Ordering Information

Part No.	Operating Temp. (Ambient)	Package
TS1085CZ-xx	-20 ~ +85 °C	TO-220
TS1085CM-xx		TO-263
TS1085CP-xx		TO-252

Note: Where xx denotes voltage option, available are 5.0V, 3.3V and 2.5V. Leave blank for adjustable version. Contact factory for additional voltage options.

Absolute Maximum Rating

Input Supply Voltage	Vin	12	V
Operation Input Supply Voltage	Vin (operate)	7	V
Power Dissipation	P _D	Internally Limited	W
Operating Junction Temperature Range	T _J	-25 ~ +150	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C
Lead Soldering Temperature (260 °C)		10	S
TO-220 / TO-263 Package		5	
TO-252 Package			



Electrical Characteristics

T_a = 25 °C, unless otherwise specified. Adjustable version test with V_{out} = 2.5V.

Parameter	Conditions	Min	Typ	Max	Unit
Output Voltage	V _{out} +1.5V ≤ V _{in} ≤ 7V, I _o =10mA	0.990 V _o	5.0 / 3.3 2.5	1.010 V _o	V
	V _{out} +1.5V ≤ V _{in} ≤ 7V, I _o =3A	0.980 V _o		1.020 V _o	V
Reference Voltage	(V _{in} -out) =1.5V, I _o =10mA	0.990 V _o	1.25	1.010 V _o	V
	(V _{in} -out) =1.5V, I _o =3A	0.980 V _o		1.020 V _o	V
Input Supply Voltage		--	--	7	V
Line Regulation	V _{out} +1.5V ≤ V _{in} ≤ 7V, I _o =10mA	--	0.015	0.2	%
Load Regulation (note 1,2)	V _{in} =V _{out} +1.5V, 10mA ≤ I _o ≤ 3A	--	0.05	1.0	%
					%
Dropout Voltage	I _o =3A, ΔV _{out} =0.1%V _{out}	--	1.3	1.4	V
Minimum Load Current	V _{in} =5V	--	8	10	mA
Adjustable Pin Current		--	90	--	uA
Current Limit	V _{in} - V _{out} =3V	3.5	--	--	A
Temperature Stability	I _o =10mA	--	0.5	--	%
Ripple Rejection	F = 120Hz, I _o =3A C _{out} =25uF, V _{in} =V _{out} + 3V	--	60	70	dB

Thermal Performance

Condition	Package type	Typ	Unit
Thermal Resistance Junction to Ambient	TO-220	45	°C/W
	TO-263	45	
	TO-252	80	


Note 1: See thermal regulation specification for changes in output voltage due to heating effects. Line and load regulation are measured at a constant junction temperature by low duty cycle pulse testing. Load regulation is measured at the output lead = 1/18" from the package.

Note 2: Line and load regulation are guaranteed up to the maximum power dissipation of 15W. Power dissipation is determined by the input / output voltage difference and the output current. Guaranteed maximum power dissipation will not be available over the full input / output voltage range.


Note 3: Quiescent current is defined as the minimum output current required to maintain the regulation.



Typical Application Circuit



Fixed output voltage version



$$V_{out} = V_{ref} * (1 + R_2 / R_1)$$

* Cin is requested if regulator is located

Far from power supply filter

** Design Cout as close to Vout pin as possible

Adjustable output voltage version

Electrical Characteristics Curve

Figure 1: dropout voltage v.s. output current




Figure 2: load regulation v.s. temp.




Figure 3: output change v.s. temp.




Figure 4: line regulation




Figure 5: line transient response






Figure 6: load transient response




TO-220 Mechanical Drawing



TO-220 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	3.240	4.440	0.128	0.175
C	2.440	2.940	0.096	0.116
D	-	6.350	-	0.250
E	0.381	1.106	0.015	0.040
F	2.345	2.715	0.092	0.058
G	4.690	5.430	0.092	0.107
H	12.700	14.732	0.500	0.581
I	8.382	9.017	0.330	0.355
J	14.224	16.510	0.560	0.650
K	3.556	4.826	0.140	0.190
L	0.508	1.397	0.020	0.055
M	27.700	29.620	1.060	1.230
N	2.032	2.921	0.080	0.115
O	0.255	0.610	0.010	0.024
P	5.842	6.858	0.230	0.270


TO-263 Mechanical Drawing



TO-263 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	14.605	15.875	0.575	0.625
C	0.508	0.991	0.020	0.039
D	2.420	2.660	0.095	0.105
E	4.064	4.830	0.160	0.190
F	1.118	1.400	0.045	0.055
G	0.450	0.730	0.018	0.029
H	8.280	8.800	0.325	0.346
I	1.140	1.400	0.044	0.055
J	1.480	1.520	0.058	0.060



TO-252 Mechanical Drawing



DIM	TO-252 DIMENSION			
	MILLIMETERS	INCHES	MIN	MAX
A	6.570	0.259	6.840	0.269
B	9.250	0.364	10.400	0.409
C	0.550	0.022	0.700	0.028
D	2.560	0.101	2.670	0.105
E	2.300	0.090	2.390	0.094
F	0.490	0.019	0.570	0.022
G	1.460	0.062	1.580	0.057
H	0.520	0.022	0.570	0.020
I	5.340	0.210	5.550	0.219
J	1.460	0.065	1.640	0.057