



May 2001
Revised May 2001

FSTU16211

24-Bit Bus Switch with -2V Undershoot Protection (Preliminary)

General Description

The Fairchild Switch FSTU16211 provides 24-bits of high-speed CMOS TTL-compatible bus switching. The low On Resistance of the switch allows inputs to be connected to outputs without adding propagation delay or generating additional ground bounce noise.

The device is organized as a 12-bit or 24-bit bus switch. When \overline{OE}_1 is LOW, the switch is ON and Port 1A is connected to Port 1B. When \overline{OE}_2 is LOW, Port 2A is connected to Port 2B. The A and B Ports are protected against undershoot to support an extended range to 2.0V below ground. Fairchild's integrated Undershoot Hardened Circuit (UHC™) senses undershoot at the I/O and responds by preventing voltage differentials from developing and turning the switch on.

Features

- Undershoot hardened to -2V (A and B Ports)
- Slower output enable times to prevent signal disruption
- 4Ω switch connection between two ports
- Minimal propagation delay through the switch
- Low I_{cc}
- Zero bounce in flow-through mode
- Control inputs compatible with TTL level
- See Applications Note AN-5008 for details


Ordering Code:

Order Number	Package Number	Package Description
FSTU16211MTD	MTD56	56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

UHC™ is a trademark of Fairchild Semiconductor Corporation.

FSTU16211

Logic Diagram**Connection Diagram**

NC	1	56	\overline{OE}_1
1A ₁	2	55	\overline{OE}_2
1A ₂	3	54	1B ₁
1A ₃	4	53	1B ₂
1A ₄	5	52	1B ₃
1A ₅	6	51	1B ₄
1A ₆	7	50	1B ₅
GND	8	49	GND
1A ₇	9	48	1B ₆
1A ₈	10	47	1B ₇
1A ₉	11	46	1B ₈
1A ₁₀	12	45	1B ₉
1A ₁₁	13	44	1B ₁₀
1A ₁₂	14	43	1B ₁₁
2A ₁	15	42	1B ₁₂
2A ₂	16	41	2B ₁
V _{CC}	17	40	2B ₂
2A ₃	18	39	2B ₃
GND	19	38	GND
2A ₄	20	37	2B ₄
2A ₅	21	36	2B ₅
2A ₆	22	35	2B ₆
2A ₇	23	34	2B ₇
2A ₈	24	33	2B ₈
2A ₉	25	32	2B ₉
2A ₁₀	26	31	2B ₁₀
2A ₁₁	27	30	2B ₁₁
2A ₁₂	28	29	2B ₁₂

Truth Table

Inputs		Inputs/Outputs	
\overline{OE}_1	\overline{OE}_2	1A, 1B	2A, 2B
L	L	1A = 1B	2A = 2B
L	H	1A = 1B	Z
H	L	Z	2A = 2B
H	H	Z	Z

Pin Descriptions

Pin Name	Description
\overline{OE}_1 , \overline{OE}_2	Bus Switch Enables
1A, 2A	Bus A
1B, 2B	Bus B

Absolute Maximum Ratings (Note 1)			Recommended Operating Conditions (Note 4)				
Supply Voltage (V_{CC})	-0.5V to +7.0V		Power Supply Operating (V_{CC})	4.0V to 5.5V			
DC Switch Voltage (V_S) (Note 2)	-0.5V to +7.0V		Input Voltage (V_{IN})	0V to 5.5V			
DC Input Control			Output Voltage (V_{OUT})	0V to 5.5V			
Pin Voltage (V_{IN}) (Note 3)	-0.5V to +7.0V		Input Rise and Fall Time (t_r, t_f)				
DC Input Diode Current (I_{IK}) $V_{IN} < 0V$	-50 mA		Switch Control Input	0 ns/V to 5 ns/V			
DC Output Current (I_{OUT})	128 mA		Switch I/O	0 ns/V to DC			
DC V_{CC}/GND Current (I_{CC}/I_{GND})	+/- 100 mA		Free Air Operating Temperature (T_A)	-40 °C to +85 °C			
Storage Temperature Range (T_{STG})	-65°C to +150 °C						
<p>Note 1: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum rating. The "Recommended Operating Conditions" table will define the conditions for actual device operation.</p> <p>Note 2: V_S is the voltage observed/applied at either the A or B Ports across the switch.</p> <p>Note 3: The input and output negative voltage ratings may be exceeded if the input and output diode current ratings are observed.</p> <p>Note 4: Unused control inputs must be held HIGH or LOW. They may not float.</p>							
DC Electrical Characteristics							
Symbol	Parameter	V_{CC} (V)	$T_A = -40^\circ C$ to $+85^\circ C$				
			Min	Typ (Note 5)	Max	Units	Conditions
V_{IK}	Clamp Diode Voltage	4.5			-1.2		
V_{IH}	HIGH Level Input Voltage	4.0–5.5	2.0			V	
V_{IL}	LOW Level Input Voltage	4.0–5.5			0.8	V	
I_I	Input Leakage Current	5.5			± 1.0	μA	$0 \leq V_{IN} \leq 5.5V$
		0			10	μA	$V_{IN} = 5.5V$
I_{OZ}	OFF-STATE Leakage Current	5.5			± 1.0	μA	$0 \leq A, B \leq V_{CC}$
R_{ON}	Switch On Resistance (Note 6)	4.5		4	7	Ω	$V_{IN} = 0V, I_{IN} = 64$ mA
		4.5		4	7	Ω	$V_{IN} = 0V, I_{IN} = 30$ mA
		4.5		8	12	Ω	$V_{IN} = 2.4V, I_{IN} = 15$ mA
		4.0		11	20	Ω	$V_{IN} = 2.4V, I_{IN} = 15$ mA
I_{CC}	Quiescent Supply Current	5.5			3	μA	$V_{IN} = V_{CC}$ or GND, $I_{OUT} = 0$
ΔI_{CC}	Increase in I_{CC} per Input	5.5			2.5	mA	One Input at 3.4V Other Inputs at V_{CC} or GND
V_{IKU}	Voltage Undershoot	5.5			-2.0	V	0.0 mA $\geq I_{IN} \geq -50$ mA $OE_{1,2} = 5.5V$

Note 5: Typical values are at $V_{CC} = 5.0V$ and $T_A = +25^\circ C$

Note 6: Measured by the voltage drop between A and B pins at the indicated current through the switch. On Resistance is determined by the lower of the voltages on the two (A or B) pins.

FSTU16211

AC Electrical Characteristics

Symbol	Parameter	$T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, $C_L = 50\text{pF}$, $R_U = RD = 500\Omega$				Units	Conditions	Figure Number			
		$V_{CC} = 4.5 - 5.5\text{V}$		$V_{CC} = 4.0\text{V}$							
		Min	Max	Min	Max						
t_{PHL}, t_{PLH}	Propagation Delay Bus to Bus (Note 7)		0.25		0.25	ns	$V_I = \text{OPEN}$	Figures 2, 3			
t_{PZH}, t_{PZL}	Output Enable Time	7.0	30.0		35.0	ns	$V_I = 7\text{V}$ for t_{PZL} $V_I = \text{OPEN}$ for t_{PZH}	Figures 2, 3			
t_{PHZ}, t_{PLZ}	Output Disable Time	1.5	7.0		7.2	ns	$V_I = 7\text{V}$ for t_{PLZ} $V_I = \text{OPEN}$ for t_{PHZ}	Figures 2, 3			

Note 7: This parameter is guaranteed by design but is not tested. The bus switch contributes no propagation delay other than the RC delay of the typical On Resistance of the switch and the 50pF load capacitance, when driven by an ideal voltage source (zero output impedance).

Capacitance (Note 8)

Symbol	Parameter	Typ	Max	Units	Conditions
C_{IN}	Control Pin Input Capacitance	3		pF	$V_{CC} = 5.0\text{V}$
$C_{I/O}$	Input/Output Capacitance	6		pF	$V_{CC}, \overline{OE} = 5.0\text{V}$

Note 8: $T_A = +25^{\circ}\text{C}$, $f = 1\text{ MHz}$, Capacitance is characterized but not tested.

Undershoot Characteristic

Symbol	Parameter	Min	Typ	Max	Units	Conditions
V_{OUTU}	Output Voltage During Undershoot	2.5	$V_{OH} - 0.3$		V	

Note 9: This test is intended to characterize the device's protective capabilities by maintaining output signal integrity during an input transient voltage undershoot event.






FIGURE 1.

Device Test Conditions

Parameter	Value	Units
V_{IN}	see Waveform	V
$R_1 = R_2$	100K	Ω
V_{TR1}	11.0	V
V_{CC}	5.5	V

Transient Input Voltage (V_{IN}) Waveform

AC Loading and Waveforms



Note: Input driven by $50\ \Omega$ source terminated in $50\ \Omega$

Note: C_L includes load and stray capacitance

Note: Input PRR = 1.0 MHz, t_W = 500 ns

FIGURE 2. AC Test Circuit





FIGURE 3. AC Waveforms

Physical Dimensions inches (millimeters) unless otherwise noted

56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide
Package Number MTD56

MTD56 (REV B)

Technology Description

The Fairchild Switch family derives from and embodies Fairchild's proven switch technology used for several years in its 74LVX3L384 (FST3384) bus switch product.

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com