

# uA709C, uA709M, uA709AM GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS096 – D942, FEBRUARY 1971 – REVISED MAY 1988

- **Common-Mode Input Range . . .  $\pm 10$  V Typical**
- **Designed to Be Interchangeable With Fairchild  $\mu$ A709A,  $\mu$ A709, and  $\mu$ A709C**
- **Maximum Peak-to-Peak Output Voltage Swing . . . 28-V Typical With 15-V Supplies**


## description

These circuits are general-purpose operational amplifiers, each having high-impedance differential inputs and a low-impedance output. Component matching, inherent with silicon monolithic circuit-fabrication techniques, produces an amplifier with low-drift and low-offset characteristics. Provisions are incorporated within the circuit whereby external components may be used to compensate the amplifier for stable operation under various feedback or load conditions. These amplifiers are particularly useful for applications requiring transfer or generation of linear or nonlinear functions.


The uA709A circuit features improved offset characteristics, reduced input-current requirements, and lower power dissipation when compared to the uA709 circuit. In addition, maximum values of the average temperature coefficients of offset voltage and current are specified for the uA709A.

The uA709C is characterized for operation from 0°C to 70°C. The uA709AM and uA709M are characterized for operation over the full military temperature range of -55°C to 125°C.


uA709AM, uA709M . . . J OR W PACKAGE  
(TOP VIEW)



uA709AM, uA709M . . . JG PACKAGE  
uA709C . . . D, JG, OR P PACKAGE  
(TOP VIEW)




uA709AM, uA709M . . . U FLAT PACKAGE  
(TOP VIEW)



NC – No internal connection

## symbol



## AVAILABLE OPTIONS

T <sub>A</sub>	V <sub>IO</sub> max AT 25°C	PACKAGE					
		SMALL OUTLINE (D)	CERAMIC (J)	CERAMIC DIP (JG)	PLASTIC DIP (P)	FLAT PACK (U)	FLAT PACK (W)
0°C to 70°C	7.5 mV	uA709CD	—	uA709CJG	uA709CP	—	—
-55°C to 125°C	5 mV 2 mV	—	uA709MJ uA709AMJ	uA709MJG uA709AMJG	—	uA709MU uA709AMU	uA709MW uA709AMW


The D package is available taped and reeled. Add the suffix R to the device type when ordering, (e.g., uA709CDR).



# uA709C, uA709M, uA709AM GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS096 – D942, FEBRUARY 1971 – REVISED MAY 1988

## schematic



Component values shown are nominal.

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

	uA709C	uA709M uA709AM	UNIT
Supply voltage, $V_{CC+}$ (see Note 1)	18	18	V
Supply voltage, $V_{CC-}$ (see Note 1)	-18	-18	V
Differential input voltage (see Note 2)	$\pm 5$	$\pm 5$	V
Input voltage (either input, see Notes 1 and 3)	$\pm 10$	$\pm 10$	V
Duration of output short circuit (see Note 4)	5	5	s
Continuous total power dissipation	See Dissipation Rating Table		
Operating free-air temperature range	0 to 70	-55 to 125	$^{\circ}\text{C}$
Storage temperature range	-65 to 150	-65 to 150	$^{\circ}\text{C}$
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds	J, JG, U, or W package	300	$^{\circ}\text{C}$
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	D or P package	260	$^{\circ}\text{C}$

NOTES: 1. All voltage values, unless otherwise noted, are with respect to the midpoint between  $V_{CC+}$  and  $V_{CC-}$ .

2. Differential voltages are at the noninverting input terminal with respect to the inverting input terminal.

3. The magnitude of the input voltage must never exceed the magnitude of the supply voltage or 10 V, whichever is less.

4. The output may be shorted to ground or either power supply.

**uA709C, uA709M, uA709AM**  
**GENERAL-PURPOSE OPERATIONAL AMPLIFIERS**

SLOS096 – D942, FEBRUARY 1971 – REVISED MAY 1988

**DISSIPATION RATING TABLE**

<b>PACKAGE</b>	<b>T<sub>A</sub> ≤ 25°C</b> <b>POWER RATING</b>	<b>DERATING</b> <b>FACTOR</b>	<b>DERATE</b> <b>ABOVE T<sub>A</sub></b>	<b>T<sub>A</sub> = 70°C</b> <b>POWER RATING</b>	<b>T<sub>A</sub> = 125°C</b> <b>POWER RATING</b>
D	300 mW	N/A	N/A	300 mW	N/A
J (uA709_M)	300 mW	11.0 mW/°C	123°C	300 mW	275 mW
JG (uA709_M)	300 mW	8.4 mW/°C	114°C	300 mW	210 mW
JG (uA709C)	300 mW	N/A	N/A	300 mW	N/A
P	300 mW	N/A	N/A	300 mW	N/A
U	300 mW	5.4 mW/°C	94°C	300 mW	135 mW
W	300 mW	8.0 mW/°C	113°C	300 mW	200 mW

# uA709M, uA709AM GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS096 – D942, FEBRUARY 1971 – REVISED MAY 1988

electrical characteristics at specified free-air temperature,  $V_{CC} \pm = \pm 9\text{ V to } \pm 15\text{ V}$  (unless otherwise noted)

PARAMETER	TEST CONDITION†	$T_A$ ‡	uA709AMC			uA709M			UNIT
			MIN	TYP§	MAX	MIN	TYP§	MAX	
$V_{IO}$ Input offset voltage	$V_O = 0$ , $R_S \leq 10\text{ k}\Omega$	25°C	0.6	2		1	5	mV	
		Full range			3		6		
$\alpha_{VIO}$ Average temperature coefficient of input offset voltage	$V_O = 0$ , $R_S = 50\ \Omega$	Full range	1.8	10		3	$\mu\text{V}/^\circ\text{C}$		
	$V_O = 0$ , $R_S = 10\text{ k}\Omega$	Full range	4.8	25		6			
$I_{IO}$ Input offset current	$V_O = 0$	25°C	10	50		50	200	nA	
		–55°C	40	250		100	500		
		125°C	3.5	50		20	200		
$\alpha_{VIO}$ Average temperature coefficient of input offset voltage	$V_O = 0$	–55°C to 25°C	0.45	2.8			nA/°C		
		25°C to 125°C	0.08	0.5					
$I_{IB}$ Input bias current	$V_O = 0$	25°C	0.1	0.2		0.2	0.5	$\mu\text{A}$	
		–55°C	0.3	0.6		0.5	1.5		
$V_{ICR}$ Common-mode input voltage range	$V_{CC} \pm = \pm 15\text{ V}$	25°C	$\pm 8$	$\pm 10$		$\pm 8$	$\pm 10$	V	
		Full range	$\pm 8$			$\pm 8$			
$V_{O(PP)}$ Maximum peak-to-peak output voltage swing	$V_{CC} \pm = \pm 15\text{ V}$ , $R_L \geq 10\text{ k}\Omega$	25°C	24	28		24	28	V	
		Full range	24			24			
		$V_{CC} \pm = \pm 15\text{ V}$ , $R_L = 2\text{ k}\Omega$	25°C	20	26		20		26
$A_{VD}$ Large-signal differential voltage amplification	$V_{CC} \pm = \pm 15\text{ V}$ , $R_L \geq 2\text{ k}\Omega$ , $V_O = \pm 10\text{ V}$	25°C		45		45	V/mV		
		Full range	25		70	25		70	
$r_i$ Input resistance		25°C	350	750		150	400	$\text{k}\Omega$	
		–55°C	85	185		40	100		
$r_o$ Output resistance	$V_O = 0$ , See Note 5	25°C		150		150	$\Omega$		
CMRR Common-mode rejection ratio	$V_{IC} = V_{ICRmin}$	25°C	80	110		70	90	dB	
		Full range	80			70			
$k_{SVS}$ Power supply sensitivity ( $\Delta V_{IO} / \Delta V_{CC}$ )	$V_{CC} = \pm 9\text{ V to } \pm 15\text{ V}$	25°C	40	100		25	150	$\mu\text{V}/\text{V}$	
		Full range		100			150		
$I_{CC}$ Supply current	$V_{CC} \pm = \pm 15\text{ V}$ , No load, $V_O = 0$	25°C	2.5	3.6		2.6	5.5	mA	
		–55°C	2.7	4.5					
		125°C	2.1	3					
$P_D$ Total power dissipation	$V_{CC} \pm = \pm 15\text{ V}$ , No load, $V_O = 0$	25°C	75	108		78	165	mW	
		–55°C	81	135					
		125°C	63	90					

† All characteristics are specified under open-loop with zero common-mode input voltage unless otherwise specified.

‡ Full range for uA709C is 0°C to 70°C. Full range for uA709AM and uA709M is –55°C to 125°C.

§ All typical values are at  $V_{CC} \pm = \pm 15\text{ V}$ .

NOTE 5: This typical value applies only at frequencies above a few hundred hertz because of the effects of drift and thermal feedback.

# uA709C, uA709M, uA709AM GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS096 – D942, FEBRUARY 1971 – REVISED MAY 1988

**electrical characteristics at specified free-air temperature (unless otherwise noted  $V_{CC} \pm = \pm 15\text{ V}$ )**

PARAMETER	TEST CONDITIONS†	$T_A$ ‡	uA709C			UNIT
			MIN	TYP	MAX	
$V_{IO}$ Input offset voltage	$V_{CC\pm} = \pm 9\text{ V}$ to $\pm 15\text{ V}$ , $V_O = 0$	25°C		2	7.5	mV
		Full range			10	
$I_{IO}$ Input offset current	$V_{CC\pm} = \pm 9\text{ V}$ to $\pm 15\text{ V}$ , $V_O = 0$	25°C		100	500	nA
		Full range			750	
$I_{IB}$ Input bias current	$V_{CC\pm} = \pm 9\text{ V}$ to $\pm 15\text{ V}$ , $V_O = 0$	25°C		0.3	1.5	$\mu\text{A}$
		Full range			2	
$V_{ICR}$ Common-mode input voltage range		25°C	$\pm 8$	$\pm 10$		V
$V_{O(PP)}$ Maximum peak-to-peak output voltage swing	$R_L \geq 10\text{ k}\Omega$	25°C	24	28	V	
		Full range	24			
	$R_L = 2\text{ k}\Omega$	25°C	20	26		
$A_{VD}$ Large-signal differential voltage amplification	$R_L \leq 2\text{ k}\Omega$ , $V_O = \pm 10\text{ V}$	25°C	15	45	V/mV	
		Full range	12			
$r_i$ Input resistance		25°C	50	250	$\text{k}\Omega$	
		Full range	35			
$r_o$ Output resistance	$V_O = 0$ , See Note 5	25°C	150		$\Omega$	
CMRR Common-mode rejection ratio	$V_{IC} = V_{ICR}\text{ min}$	25°C	65	90	dB	
$k_{SVS}$ Supply voltage sensitivity	$V_{CC} = \pm 9\text{ V}$ to $\pm 15\text{ V}$	25°C	25	200	$\mu\text{V/V}$	
$P_D$ Total power dissipation	$V_O = 0$ , No load	25°C	80	200	mW	

† All characteristics are specified under open-loop operation with zero volts common-mode voltage unless otherwise specified.

‡ Full range for uA709C is 0°C to 70°C. Full range for uA709AM and uA709M is -55°C to 125°C.

NOTE 5: This typical value applies only at frequencies above a few hundred hertz because of the effects of drift and thermal feedback.

**operating characteristics,  $V_{CC} \pm = \pm 9\text{ V}$  to  $\pm 15\text{ V}$ ,  $T_A = 25^\circ\text{C}$**

PARAMETER	TEST CONDITIONS†	uA709C uA709M uA709AM			UNIT
		MIN	TYP	MAX	
$t_r$ Rise time	$V_I = 20\text{ mV}$ , $R_L = 2\text{ k}\Omega$ , See Figure 1	$C_L = 0$	0.3	1	$\mu\text{s}$
Overshoot factor		$C_L = 100\text{ pF}$	6%	30%	

## PARAMETER MEASUREMENT INFORMATION




Figure 1. Rise Time and Slew Rate Test Circuit

## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.