

M.C.C.

Micro Commercial Components
21201 Itasca Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

**UF4001GP
THRU
UF4007GP**

Features

- High Surge Capability
- Low Leakage
- Low Forward Voltage Drop
- Ultra Fast Switching Speed For High Efficiency

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance 40°C/W

MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
UF4001GP	---	50V	35V	50V
UF4002GP	---	100V	70V	100V
UF4003GP	---	200V	140V	200V
UF4004GP	---	400V	280V	400V
UF4005GP	---	600V	420V	400V
UF4006GP	---	800V	560V	800V
UF4007GP	---	1000V	700V	1000V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	1 A	$T_A = 55^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	30A	8.3ms, half sine
Maximum Instantaneous Forward Voltage UF4001GP-4003GP UF4004GP UF4005GP-4007GP	V_F	1.0 V 1.3 V 1.7 V	$I_{FM} = 1.0\text{A};$ $T_A = 25^\circ\text{C}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	5 uA 100uA	$T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$
Maximum Reverse Recovery Time UF4001GP-4004GP UF4005GP-4007GP	T_{rr}	50ns 75ns	$I_F=0.5\text{A}, I_R=1.0\text{A},$ $I_{rr}=0.25\text{A}$
Typical Junction Capacitance UF4001GP-4004GP UF4005GP-4007GP	C_J	20pF 10pF	Measured at 1.0MHz, $V_R=4.0\text{V}$


*Pulse Test: Pulse Width 300µsec, Duty Cycle 1%

**1 Amp Glass
Passivated Ultra Fast
Recovery Rectifier
50 to 1000 Volts**

DO-41



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.166	.205	4.10	5.20	
B	.080	.107	2.00	2.70	
C	.028	.034	.70	.90	
D	1.000	---	25.40	---	



UF4001GP thru UF4007GP

