



查询UF4001G供应商

捷多邦, 专业PCB打样工厂, 24小时加急出货

UF4001G THRU UF4007G

1.0 AMP. GLASS PASSIVATED ULTRA FAST RECTIFIERS

FEATURES

- * Low forward voltage drop
- * High current capability
- * High reliability
- * High surge current capability

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V - 0 rate flame retardant
- * Lead: Axial leads, solderable per MIL - STD - 202, method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting Position: Any
- * Weight: 0.34 grams


VOLTAGE RANGE

50 to 800 Volts

CURRENT

1.0 Amperes

DO-41



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	UF 4001G	UF 4002G	UF 4003G	UF 4004G	UF 4005G	UF 4006G	UF 4007G	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum D. C Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .375" (9.5mm) lead length @ $T_A = 50^{\circ}\text{C}$	$I_F(\text{AV})$	1.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	30							A
Maximum Instantaneous Forward Voltage at 1.0A	V_F	1.1				1.4			V
Maximum D. C Reverse Current @ $T_A = 25^{\circ}\text{C}$ at Rated D. C Blocking Voltage @ $T_A = 125^{\circ}\text{C}$	I_R	5.0 150							μA μA
Maximum Reverse Recovery Time (Note 1)	T_{RR}	50				75			nS
Typical Junction Capacitance (Note 2)	C_J	20				15			pF
Operating and Storage Temperature Range	T_J, T_{STG}	- 65 to + 150							$^{\circ}\text{C}$

NOTES: 1. Reverse Recovery Test Conditions: $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$.

2. Measured at 1 MHz and applied reverse voltage of 4.0V D. C.

RATINGS AND CHARACTERISTIC CURVES (UF4001G THRU UF4007G)

FIG. 1 – TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTICS




FIG. 2 – TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 – TYPICAL REVERSE CHARACTERISTICS




FIG. 4 – TYPICAL FORWARD CHARACTERISTICS




FIG. 5 – MAXIMUM NON - REPETITIVE FORWARD SURGE CURRENT




FIG. 6 – TYPICAL JUNCTION CAPACITANCE

