



UHBS15-2

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI UHBS15-2 is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	2.0 A
V_{CB0}	55 V
V_{CEO}	28 V
V_{CES}	55 V
V_{EBO}	4.0 V
P_{DISS}	50 W @ $T_C = 25^\circ C$
T_J	$-65^\circ C$ to $+200^\circ C$
T_{STG}	$-65^\circ C$ to $+150^\circ C$
θ_{JC}	$3.0^\circ C/W$

PACKAGE STYLE .230 6L FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.355 / 9.02	.365 / 9.27
B	.115 / 2.92	.125 / 3.18
C	.075 / 1.91	.085 / 2.16
D	.225 / 5.72	.235 / 5.97
E	.090 / 2.29	.110 / 2.79
F	.720 / 18.29	.730 / 18.54
G	.970 / 24.64	.980 / 24.89
H	.355 / 9.02	.365 / 9.27
I	.004 / 0.10	.006 / 0.15
J	.120 / 3.05	.130 / 3.30
K	.160 / 4.06	.180 / 4.57
L	.230 / 5.84	.260 / 6.60

ORDER CODE: ASI10669

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	$I_C = 50$ mA	28			V
BV_{CES}	$I_C = 50$ mA $R_{BE} = 10 \Omega$	55			V
BV_{EBO}	$I_E = 10$ mA	4.0			V
I_{CBO}	$V_{CB} = 15$ V			2.5	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 1.0$ A	30		200	---
C_{ob}	$V_{CB} = 24$ V $f = 1.0$ MHz			25	pF
P_G η_c	$V_{CE} = 24$ V $P_{OUT} = 15$ W $f = 960$ GHz	9.5	50		dB %

