


4-BIT DUAL-SUPPLY BUS TRANSCEIVER  
WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS


SCE577A – JUNE 2004 – REVISED APRIL 2005

- Control Inputs  $V_{IH}/V_{IL}$  Levels are Referenced to  $V_{CCA}$  Voltage
- Fully Configurable Dual-Rail Design Allows Each Port to Operate Over the Full 1.2-V to 3.6-V Power-Supply Range
- I/Os Are 4.6-V Tolerant
- $I_{off}$  Supports Partial-Power-Down Mode Operation
- Bus Hold on Data Inputs Eliminates the Need for External Pullup/Pulldown Resistors
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
  - 8000-V Human-Body Model (A114-A)
  - 200-V Machine Model (A115-A)
  - 1000-V Charged-Device Model (C101)

D, DGV, OR PWP PACKAGE  
(TOP VIEW)



RGY PACKAGE  
(TOP VIEW)



description/ordering information

This 4-bit noninverting bus transceiver uses two separate configurable power-supply rails. The A port is designed to track  $V_{CCA}$ .  $V_{CCA}$  accepts any supply voltage from 1.2 V to 3.6 V. The B port is designed to track  $V_{CCB}$ .  $V_{CCB}$  accepts any supply voltage from 1.2 V to 3.6 V. The SN74AVCH4T245 is optimized to operate with  $V_{CCA}/V_{CCB}$  set at 1.4 V to 3.6 V. It is operational with  $V_{CCA}/V_{CCB}$  as low as 1.2 V. This allows for universal low-voltage bidirectional translation between any of the 1.2-V, 1.5-V, 1.8-V, 2.5-V, and 3.3-V voltage nodes.

The SN74AVCH4T245 is designed for asynchronous communication between data buses. The device transmits data from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the direction-control (DIR) input. The output-enable ( $\overline{OE}$ ) input can be used to disable the outputs so the buses are effectively isolated.

The SN74AVCH4T245 is designed so that the control pins (1DIR, 2DIR,  $1\overline{OE}$ , and  $2\overline{OE}$ ) are supplied by  $V_{CCA}$ .

This device is fully specified for partial-power-down applications using  $I_{off}$ . The  $I_{off}$  circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2005, Texas Instruments Incorporated

# SN74AVCH4T245

## 4-BIT DUAL-SUPPLY BUS TRANSCEIVER

### WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS

SCES577A – JUNE 2004 – REVISED APRIL 2005

#### description/ordering information (continued)

#### ORDERING INFORMATION

| TA            | PACKAGE†    |               | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---------------|-------------|---------------|-----------------------|------------------|
| -40°C to 85°C | QFN – RGY   | Tape and reel | SN74AVCH4T245RGYR     | WS245            |
|               | SOIC – D    | Tube          | SN74AVCH4T245D        | AVCH4T245        |
|               |             | Tape and reel | SN74AVCH4T245DR       |                  |
|               | TSSOP – PW  | Tube          | SN74AVCH4T245PW       | WS245            |
|               |             | Tape and reel | SN74AVCH4T245PWR      |                  |
|               | TVSOP – DGV | Tape and reel | SN74AVCH4T245DGV      | WS245            |

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).

The  $V_{CC}$  isolation feature ensures that if either  $V_{CC}$  input is at GND, then both ports are in the high-impedance state. The bus-hold circuitry on the powered-up side always stays active.


Active bus-hold circuitry holds unused or undriven inputs at a valid logic state. Use of pullup or pulldown resistors with the bus-hold circuitry is not recommended.

To ensure the high-impedance state during power up or power down,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

FUNCTION TABLE  
(each 4-bit section)

| INPUTS          |     | OPERATION       |
|-----------------|-----|-----------------|
| $\overline{OE}$ | DIR |                 |
| L               | L   | B data to A bus |
| L               | H   | A data to B bus |
| H               | X   | All output Hi-Z |

#### logic diagram (positive logic)



**SN74AVCH4T245**  
**4-BIT DUAL-SUPPLY BUS TRANSCEIVER**  
**WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS**

SCE577A – JUNE 2004 – REVISED APRIL 2005

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†**

|   |                             |
|---|-----------------------------|
| Supply voltage range, $V_{CCA}$ and $V_{CCB}$ .....   | -0.5 V to 4.6 V             |
| Input voltage range, $V_I$ (see Note 1): I/O ports (A port) .....   | -0.5 V to 4.6 V             |
| I/O ports (B port) .....  | -0.5 V to 4.6 V             |
| Control inputs .....  | -0.5 V to 4.6 V             |
| Voltage range applied to any output in the high-impedance or power-off state, $V_O$<br>(see Note 1): (A port) ..... | -0.5 V to 4.6 V             |
| (B port) .....  | -0.5 V to 4.6 V             |
| Voltage range applied to any output in the high or low state, $V_O$<br>(see Notes 1 and 2): (A port) .....          | -0.5 V to $V_{CCA} + 0.5$ V |
| (B port) .....  | -0.5 V to $V_{CCB} + 0.5$ V |
| Input clamp current, $I_{IK}$ ( $V_I < 0$ ) .....   | -50 mA                      |
| Output clamp current, $I_{OK}$ ( $V_O < 0$ ) .....  | -50 mA                      |
| Continuous output current, $I_O$ .....  | $\pm 50$ mA                 |
| Continuous current through $V_{CCA}$ , $V_{CCB}$ , or GND .....   | $\pm 100$ mA                |
| Package thermal impedance, $\theta_{JA}$ (see Note 3): D package .....  | 73°C/W                      |
| (see Note 3): DGV package .....   | 120°C/W                     |
| (see Note 3): PW package .....  | 108°C/W                     |
| (see Note 4): RGY package .....   | 39°C/W                      |
| Storage temperature range, $T_{stg}$ .....  | -65°C to 150°C              |

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input voltage and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.  
2. The output positive-voltage rating may be exceeded up to 4.6 V maximum if the output current rating is observed.  
3. The package thermal impedance is calculated in accordance with JESD 51-7.  
4. The package thermal impedance is calculated in accordance with JESD 51-5.



# SN74AVCH4T245

## 4-BIT DUAL-SUPPLY BUS TRANSCEIVER

### WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS

SCES577A – JUNE 2004 – REVISED APRIL 2005

#### recommended operating conditions (see Notes 5 through 7)

|                  |                                    | V <sub>CCI</sub>   | V <sub>CCO</sub> | MIN                     | MAX              | UNIT |
|------------------|------------------------------------|--|------------------|-------------------------|------------------|------|
| V <sub>CCA</sub> | Supply voltage                     |  |                  | 1.2                     | 3.6              | V    |
| V <sub>CCB</sub> | Supply voltage                     |  |                  | 1.2                     | 3.6              | V    |
| V <sub>IH</sub>  | High-level input voltage           | Data inputs<br>(see Note 8)                              | 1.2 V to 1.95 V  | V <sub>CCI</sub> × 0.65 |                  | V    |
|                  |                                    |  | 1.95 V to 2.7 V  | 1.6                     |                  |      |
|                  |                                    |  | 2.7 V to 3.6 V   | 2                       |                  |      |
| V <sub>IL</sub>  | Low-level input voltage            | Data inputs<br>(see Note 8)                              | 1.2 V to 1.95 V  | V <sub>CCI</sub> × 0.35 |                  | V    |
|                  |                                    |  | 1.95 V to 2.7 V  | 0.7                     |                  |      |
|                  |                                    |  | 2.7 V to 3.6 V   | 0.8                     |                  |      |
| V <sub>IH</sub>  | High-level input voltage           | DIR<br>(referenced to V <sub>CCA</sub> )<br>(see Note 9) | 1.2 V to 1.95 V  | V <sub>CCA</sub> × 0.65 |                  | V    |
|                  |                                    |  | 1.95 V to 2.7 V  | 1.6                     |                  |      |
|                  |                                    |  | 2.7 V to 3.6 V   | 2                       |                  |      |
| V <sub>IL</sub>  | Low-level input voltage            | DIR<br>(referenced to V <sub>CCA</sub> )<br>(see Note 9) | 1.2 V to 1.95 V  | V <sub>CCA</sub> × 0.35 |                  | V    |
|                  |                                    |  | 1.95 V to 2.7 V  | 0.7                     |                  |      |
|                  |                                    |  | 2.7 V to 3.6 V   | 0.8                     |                  |      |
| V <sub>I</sub>   | Input voltage                      |  |                  | 0                       | 3.6              | V    |
| V <sub>O</sub>   | Output voltage                     | Active state   |                  | 0                       | V <sub>CCO</sub> | V    |
|                  |                                    | 3-state  |                  | 0                       | 3.6              | V    |
| I <sub>OH</sub>  | High-level output current          |  | 1.2 V            | -3                      |                  | mA   |
|                  |                                    |  | 1.4 V to 1.6 V   | -6                      |                  |      |
|                  |                                    |  | 1.65 V to 1.95 V | -8                      |                  |      |
|                  |                                    |  | 2.3 V to 2.7 V   | -9                      |                  |      |
|                  |                                    |  | 3 V to 3.6 V     | -12                     |                  |      |
| I <sub>OL</sub>  | Low-level output current           |  | 1.2 V            | 3                       |                  | mA   |
|                  |                                    |  | 1.4 V to 1.6 V   | 6                       |                  |      |
|                  |                                    |  | 1.65 V to 1.95 V | 8                       |                  |      |
|                  |                                    |  | 2.3 V to 2.7 V   | 9                       |                  |      |
|                  |                                    |  | 3 V to 3.6 V     | 12                      |                  |      |
| Δt/Δv            | Input transition rise or fall rate |  |                  |                         | 5                | ns/V |
| T <sub>A</sub>   | Operating free-air temperature     |  |                  | -40                     | 85               | °C   |

- NOTES:
- V<sub>CCI</sub> is the V<sub>CC</sub> associated with the data input port.
  - V<sub>CCO</sub> is the V<sub>CC</sub> associated with the output port.
  - All unused data inputs of the device must be held at V<sub>CCI</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.
  - For V<sub>CCI</sub> values not specified in the data sheet, V<sub>IH(min)</sub> = V<sub>CCI</sub> × 0.7 V, V<sub>IL(max)</sub> = V<sub>CCI</sub> × 0.3 V.
  - For V<sub>CCI</sub> values not specified in the data sheet, V<sub>IH(min)</sub> = V<sub>CCA</sub> × 0.7 V, V<sub>IL(max)</sub> = V<sub>CCA</sub> × 0.3 V.



**SN74AVCH4T245**  
**4-BIT DUAL-SUPPLY BUS TRANSCEIVER**  
**WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS**

SCES577A – JUNE 2004 – REVISED APRIL 2005

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted) (see Note 10)

| PARAMETER                      | TEST CONDITIONS |  | V <sub>CCA</sub> | V <sub>CCB</sub> | T <sub>A</sub> = 25°C |        |       | -40°C to 85°C            |     | UNIT |
|--------------------------------|-----------------|--|------------------|------------------|-----------------------|--------|-------|--------------------------|-----|------|
|                                |                 |  |                  |                  | MIN                   | TYP    | MAX   | MIN                      | MAX |      |
| V <sub>OH</sub>                |                 | V <sub>I</sub> = V <sub>IH</sub>         | 1.2 V to 3.6 V   | 1.2 V to 3.6 V   |                       |        |       | V <sub>CCO</sub> - 0.2 V |     | V    |
|                                |                 |  | 1.2 V            | 1.2 V            | 0.95                  |        |       |                          |     |      |
|                                |                 |  | 1.4 V            | 1.4 V            |                       |        |       | 1.05                     |     |      |
|                                |                 |  | 1.65 V           | 1.65 V           |                       |        |       | 1.2                      |     |      |
|                                |                 |  | 2.3 V            | 2.3 V            |                       |        |       | 1.75                     |     |      |
|                                |                 |  | 3 V              | 3 V              |                       |        |       | 2.3                      |     |      |
| V <sub>OL</sub>                |                 | V <sub>I</sub> = V <sub>IL</sub>         | 1.2 V to 3.6 V   | 1.2 V to 3.6 V   |                       |        |       | 0.2                      |     | V    |
|                                |                 |  | 1.2 V            | 1.2 V            | 0.15                  |        |       |                          |     |      |
|                                |                 |  | 1.4 V            | 1.4 V            |                       |        |       | 0.35                     |     |      |
|                                |                 |  | 1.65 V           | 1.65 V           |                       |        |       | 0.45                     |     |      |
|                                |                 |  | 2.3 V            | 2.3 V            |                       |        |       | 0.55                     |     |      |
|                                |                 |  | 3 V              | 3 V              |                       |        |       | 0.7                      |     |      |
| I <sub>I</sub>                 | DIR input       | V <sub>I</sub> = V <sub>CCA</sub> or GND | 1.2 V to 3.6 V   | 1.2 V to 3.6 V   |                       | ±0.025 | ±0.25 |                          | ±1  | μA   |
| I <sub>BHL</sub> <sup>†</sup>  |                 |  | 1.2 V            | 1.2 V            | 25                    |        |       |                          |     | μA   |
|                                |                 |  | 1.4 V            | 1.4 V            |                       |        |       | 15                       |     |      |
|                                |                 |  | 1.65 V           | 1.65 V           |                       |        |       | 25                       |     |      |
|                                |                 |  | 2.3 V            | 2.3 V            |                       |        |       | 45                       |     |      |
|                                |                 |  | 3.3 V            | 3.3 V            |                       |        |       | 100                      |     |      |
| I <sub>BHH</sub> <sup>‡</sup>  |                 |  | 1.2 V            | 1.2 V            | -25                   |        |       |                          |     | μA   |
|                                |                 |  | 1.4 V            | 1.4 V            |                       |        |       | -15                      |     |      |
|                                |                 |  | 1.65 V           | 1.65 V           |                       |        |       | -25                      |     |      |
|                                |                 |  | 2.3 V            | 2.3 V            |                       |        |       | -45                      |     |      |
|                                |                 |  | 3.3 V            | 3.3 V            |                       |        |       | -100                     |     |      |
| I <sub>BHLO</sub> <sup>§</sup> |                 | V <sub>I</sub> = 0 to V <sub>CCI</sub>   | 1.2 V            | 1.2 V            | 50                    |        |       |                          |     | μA   |
|                                |                 |  | 1.6 V            | 1.6 V            |                       |        |       | 125                      |     |      |
|                                |                 |  | 1.95 V           | 1.95 V           |                       |        |       | 200                      |     |      |
|                                |                 |  | 2.7 V            | 2.7 V            |                       |        |       | 300                      |     |      |
|                                |                 |  | 3.6 V            | 3.6 V            |                       |        |       | 500                      |     |      |
| I <sub>BHHO</sub> <sup>¶</sup> |                 | V <sub>I</sub> = 0 to V <sub>CCI</sub>   | 1.2 V            | 1.2 V            | -50                   |        |       |                          |     | μA   |
|                                |                 |  | 1.6 V            | 1.6 V            |                       |        |       | -125                     |     |      |
|                                |                 |  | 1.95 V           | 1.95 V           |                       |        |       | -200                     |     |      |
|                                |                 |  | 2.7 V            | 2.7 V            |                       |        |       | -300                     |     |      |
|                                |                 |  | 3.6 V            | 3.6 V            |                       |        |       | -500                     |     |      |

<sup>†</sup> The bus-hold circuit can sink at least the minimum low sustaining current at V<sub>IL</sub> max. I<sub>BHL</sub> should be measured after lowering V<sub>IN</sub> to GND and then raising it to V<sub>IL</sub> max.

<sup>‡</sup> The bus-hold circuit can source at least the minimum high sustaining current at V<sub>IH</sub> min. I<sub>BHH</sub> should be measured after raising V<sub>IN</sub> to V<sub>CC</sub> and then lowering it to V<sub>IH</sub> min.

<sup>§</sup> An external driver must source at least I<sub>BHLO</sub> to switch this node from low to high.

<sup>¶</sup> An external driver must sink at least I<sub>BHHO</sub> to switch this node from high to low.

NOTE 10: V<sub>CCO</sub> is the V<sub>CC</sub> associated with the output port.



# SN74AVCH4T245

## 4-BIT DUAL-SUPPLY BUS TRANSCEIVER

### WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS

SCES577A – JUNE 2004 – REVISED APRIL 2005

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted) (see Notes 11 and 12) (continued)

| PARAMETER                           | TEST CONDITIONS                          | V <sub>CCA</sub>   | V <sub>CCB</sub> | T <sub>A</sub> = 25°C |      |      | -40°C to 85°C |     | UNIT |
|-------------------------------------|--|--|------------------|-----------------------|------|------|---------------|-----|------|
|                                     |  |  |                  | MIN                   | TYP  | MAX  | MIN           | MAX |      |
| I <sub>off</sub>                    | A port                                   | V <sub>I</sub> or V <sub>O</sub> = 0 to 3.6 V                                      | 0 V              | 0 to 3.6 V            | ±0.1 | ±1   | ±5            |     | μA   |
|                                     | B port                                   |  | 0 to 3.6 V       | 0 V                   | ±0.1 | ±1   | ±5            |     |      |
| I <sub>OZ</sub> <sup>†</sup>        | A or B port                              | V <sub>O</sub> = V <sub>CCO</sub> or GND, V <sub>I</sub> = V <sub>CCI</sub> or GND | 3.6 V            | 3.6 V                 | ±0.5 | ±2.5 | ±5            |     | μA   |
|                                     | B port                                   | V <sub>O</sub> = V <sub>CCO</sub> or GND, V <sub>I</sub> = V <sub>CCI</sub> or GND | 0 V              | 3.6 V                 |      |      | ±5            |     |      |
|                                     | A port                                   |  | 3.6 V            | 0 V                   |      |      | ±5            |     |      |
| I <sub>CCA</sub>                    | V <sub>I</sub> = V <sub>CCI</sub> or GND | I <sub>O</sub> = 0   | 1.2 V to 3.6 V   | 1.2 V to 3.6 V        |      |      | 8             |     | μA   |
|                                     |  |  | 0 V              | 3.6 V                 |      |      | -2            |     |      |
|                                     |  |  | 3.6 V            | 0 V                   |      |      | 8             |     |      |
| I <sub>CCB</sub>                    | V <sub>I</sub> = V <sub>CCI</sub> or GND | I <sub>O</sub> = 0   | 1.2 V to 3.6 V   | 1.2 V to 3.6 V        |      |      | 8             |     | μA   |
|                                     |  |  | 0 V              | 3.6 V                 |      |      | 8             |     |      |
|                                     |  |  | 3.6 V            | 0 V                   |      |      | -2            |     |      |
| I <sub>CCA</sub> + I <sub>CCB</sub> | V <sub>I</sub> = V <sub>CCI</sub> or GND | I <sub>O</sub> = 0   | 1.2 V to 3.6 V   | 1.2 V to 3.6 V        |      |      | 16            |     | μA   |
| C <sub>i</sub>                      | Control inputs                           | V <sub>I</sub> = 3.3 V or GND  | 3.3 V            | 3.3 V                 | 3.5  |      | 4.5           |     | pF   |
| C <sub>io</sub>                     | A or B ports                             | V <sub>O</sub> = 3.3 V or GND  | 3.3 V            | 3.3 V                 | 6    |      | 7             |     | pF   |

<sup>†</sup> For I/O ports, the parameter I<sub>OZ</sub> includes the input leakage current.

NOTES: 11. V<sub>CCO</sub> is the V<sub>CC</sub> associated with the output port.

12. V<sub>CCI</sub> is the V<sub>CC</sub> associated with the input port.

switching characteristics over recommended operating free-air temperature range, V<sub>CCA</sub> = 1.2 V (see Figure 11)

| PARAMETER        | FROM (INPUT)    | TO (OUTPUT) | V <sub>CCB</sub> = 1.2 V | V <sub>CCB</sub> = 1.5 V ± 0.1 V | V <sub>CCB</sub> = 1.8 V ± 0.15 V | V <sub>CCB</sub> = 2.5 V ± 0.2 V | V <sub>CCB</sub> = 3.3 V ± 0.3 V | UNIT |
|------------------|-----------------|-------------|--------------------------|----------------------------------|-----------------------------------|----------------------------------|----------------------------------|------|
|                  |                 |             | TYP                      | TYP                              | TYP                               | TYP                              | TYP                              |      |
| t <sub>PLH</sub> | A               | B           | 3.4                      | 2.9                              | 2.7                               | 2.6                              | 2.8                              | ns   |
| t <sub>PHL</sub> |                 |             | 3.4                      | 2.9                              | 2.7                               | 2.6                              | 2.8                              |      |
| t <sub>PLH</sub> | B               | A           | 3.6                      | 3.1                              | 2.8                               | 2.6                              | 2.6                              | ns   |
| t <sub>PHL</sub> |                 |             | 3.6                      | 3.1                              | 2.8                               | 2.6                              | 2.6                              |      |
| t <sub>PZH</sub> | $\overline{OE}$ | A           | 5.6                      | 4.7                              | 4.3                               | 3.9                              | 3.7                              | ns   |
| t <sub>PZL</sub> |                 |             | 5.6                      | 4.7                              | 4.3                               | 3.9                              | 3.7                              |      |
| t <sub>PZH</sub> | $\overline{OE}$ | B           | 5                        | 4.3                              | 3.9                               | 3.6                              | 3.6                              | ns   |
| t <sub>PZL</sub> |                 |             | 5                        | 4.3                              | 3.9                               | 3.6                              | 3.6                              |      |
| t <sub>PHZ</sub> | $\overline{OE}$ | A           | 6.2                      | 5.2                              | 5.2                               | 4.3                              | 4.8                              | ns   |
| t <sub>PLZ</sub> |                 |             | 6.2                      | 5.2                              | 5.2                               | 4.3                              | 4.8                              |      |
| t <sub>PHZ</sub> | $\overline{OE}$ | B           | 5.9                      | 5.1                              | 5                                 | 4.7                              | 5.5                              | ns   |
| t <sub>PLZ</sub> |                 |             | 5.9                      | 5.1                              | 5                                 | 4.7                              | 5.5                              |      |



**SN74AVCH4T245**  
**4-BIT DUAL-SUPPLY BUS TRANSCEIVER**  
**WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS**

SCES577A – JUNE 2004 – REVISED APRIL 2005

switching characteristics over recommended operating free-air temperature range,  
 $V_{CCA} = 1.5 \text{ V} \pm 0.1 \text{ V}$  (see Figure 11)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ |      | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ |      | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ |      | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ |      | UNIT |
|-----------|-----------------|-------------|---------------------------|---|------|--|------|---|------|---|------|------|
|           |                 |             | TYP                       | MIN   | MAX  | MIN  | MAX  | MIN   | MAX  | MIN   | MAX  |      |
| $t_{PLH}$ | A               | B           | 3.2                       | 0.3   | 6.3  | 0.3  | 5.2  | 0.4   | 4.2  | 0.4   | 4.2  | ns   |
| $t_{PHL}$ |                 |             | 3.2                       | 0.3   | 6.3  | 0.3  | 5.2  | 0.4   | 4.2  | 0.4   | 4.2  |      |
| $t_{PLH}$ | B               | A           | 3.3                       | 0.7   | 6.3  | 0.5  | 6    | 0.4   | 5.7  | 0.3   | 5.6  | ns   |
| $t_{PHL}$ |                 |             | 3.3                       | 0.7   | 6.3  | 0.5  | 6    | 0.4   | 5.7  | 0.3   | 5.6  |      |
| $t_{PZH}$ | $\overline{OE}$ | A           | 4.9                       | 1.4   | 9.6  | 1.1  | 9.5  | 0.7   | 9.4  | 0.4   | 9.4  | ns   |
| $t_{PZL}$ |                 |             | 4.9                       | 1.4   | 9.6  | 1.1  | 9.5  | 0.7   | 9.4  | 0.4   | 9.4  |      |
| $t_{PZH}$ | $\overline{OE}$ | B           | 4.5                       | 1.4   | 9.6  | 1.1  | 7.7  | 0.9   | 5.8  | 0.9   | 5.6  | ns   |
| $t_{PZL}$ |                 |             | 4.5                       | 1.4   | 9.6  | 1.1  | 7.7  | 0.9   | 5.8  | 0.9   | 5.6  |      |
| $t_{PHZ}$ | $\overline{OE}$ | A           | 5.6                       | 1.8   | 10.2 | 1.5  | 10.2 | 1.3   | 10.2 | 1.6   | 10.2 | ns   |
| $t_{PLZ}$ |                 |             | 5.6                       | 1.8   | 10.2 | 1.5  | 10.2 | 1.3   | 10.2 | 1.6   | 10.2 |      |
| $t_{PHZ}$ | $\overline{OE}$ | B           | 5.2                       | 1.9   | 10.3 | 1.9  | 9.1  | 1.4   | 7.4  | 1.2   | 7.6  | ns   |
| $t_{PLZ}$ |                 |             | 5.2                       | 1.9   | 10.3 | 1.9  | 9.1  | 1.4   | 7.4  | 1.2   | 7.6  |      |

switching characteristics over recommended operating free-air temperature range,  
 $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$  (see Figure 11)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CCB} = 1.2 \text{ V}$ | $V_{CCB} = 1.5 \text{ V} \pm 0.1 \text{ V}$ |     | $V_{CCB} = 1.8 \text{ V} \pm 0.15 \text{ V}$ |     | $V_{CCB} = 2.5 \text{ V} \pm 0.2 \text{ V}$ |     | $V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$ |     | UNIT |
|-----------|-----------------|-------------|---------------------------|---|-----|--|-----|---|-----|---|-----|------|
|           |                 |             | TYP                       | MIN   | MAX | MIN  | MAX | MIN   | MAX | MIN   | MAX |      |
| $t_{PLH}$ | A               | B           | 2.9                       | 0.1   | 6   | 0.1  | 4.9 | 0.1   | 3.9 | 0.3   | 3.9 | ns   |
| $t_{PHL}$ |                 |             | 2.9                       | 0.1   | 6   | 0.1  | 4.9 | 0.1   | 3.9 | 0.3   | 3.9 |      |
| $t_{PLH}$ | B               | A           | 3                         | 0.6   | 5.3 | 0.5  | 4.9 | 0.3   | 4.6 | 0.3   | 4.5 | ns   |
| $t_{PHL}$ |                 |             | 3                         | 0.6   | 5.3 | 0.5  | 4.9 | 0.3   | 4.6 | 0.3   | 4.5 |      |
| $t_{PZH}$ | $\overline{OE}$ | A           | 4.4                       | 1   | 7.4 | 1  | 7.3 | 0.6   | 7.3 | 0.4   | 7.2 | ns   |
| $t_{PZL}$ |                 |             | 4.4                       | 1   | 7.4 | 1  | 7.3 | 0.6   | 7.3 | 0.4   | 7.2 |      |
| $t_{PZH}$ | $\overline{OE}$ | B           | 4.1                       | 1.2   | 9.2 | 1  | 7.4 | 0.8   | 5.3 | 0.8   | 4.6 | ns   |
| $t_{PZL}$ |                 |             | 4.1                       | 1.2   | 9.2 | 1  | 7.4 | 0.8   | 5.3 | 0.8   | 4.6 |      |
| $t_{PHZ}$ | $\overline{OE}$ | A           | 5.4                       | 1.6   | 8.6 | 1.8  | 8.7 | 1.3   | 8.7 | 1.6   | 8.7 | ns   |
| $t_{PLZ}$ |                 |             | 5.4                       | 1.6   | 8.6 | 1.8  | 8.7 | 1.3   | 8.7 | 1.6   | 8.7 |      |
| $t_{PHZ}$ | $\overline{OE}$ | B           | 5                         | 1.7   | 9.9 | 1.6  | 8.7 | 1.2   | 6.9 | 1   | 6.9 | ns   |
| $t_{PLZ}$ |                 |             | 5                         | 1.7   | 9.9 | 1.6  | 8.7 | 1.2   | 6.9 | 1   | 6.9 |      |

# SN74AVCH4T245

## 4-BIT DUAL-SUPPLY BUS TRANSCEIVER

### WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS

SCES577A – JUNE 2004 – REVISED APRIL 2005

switching characteristics over recommended operating free-air temperature range,  
 $V_{CCA} = 2.5\text{ V} \pm 0.2\text{ V}$  (see Figure 11)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CCB} = 1.2\text{ V}$ | $V_{CCB} = 1.5\text{ V} \pm 0.1\text{ V}$ |     | $V_{CCB} = 1.8\text{ V} \pm 0.15\text{ V}$ |     | $V_{CCB} = 2.5\text{ V} \pm 0.2\text{ V}$ |     | $V_{CCB} = 3.3\text{ V} \pm 0.3\text{ V}$ |     | UNIT |
|-----------|-----------------|-------------|--------------------------|---|-----|--|-----|---|-----|---|-----|------|
|           |                 |             | TYP                      | MIN                                       | MAX | MIN  | MAX | MIN                                       | MAX | MIN                                       | MAX |      |
| $t_{PLH}$ | A               | B           | 2.8                      | 0.1                                       | 5.7 | 0.1  | 4.6 | 0.2                                       | 3.5 | 0.1                                       | 3.6 | ns   |
| $t_{PHL}$ |                 |             | 2.8                      | 0.1                                       | 5.7 | 0.1  | 4.6 | 0.2                                       | 3.5 | 0.1                                       | 3.6 |      |
| $t_{PLH}$ | B               | A           | 2.7                      | 0.6                                       | 4.2 | 0.4  | 3.9 | 0.2                                       | 3.4 | 0.2                                       | 3.3 | ns   |
| $t_{PHL}$ |                 |             | 2.7                      | 0.6                                       | 4.2 | 0.4  | 3.9 | 0.2                                       | 3.4 | 0.2                                       | 3.3 |      |
| $t_{PZH}$ | $\overline{OE}$ | A           | 4                        | 0.7                                       | 6.5 | 0.7  | 5.2 | 0.6                                       | 4.8 | 0.4                                       | 4.8 | ns   |
| $t_{PZL}$ |                 |             | 4                        | 0.7                                       | 6.5 | 0.7  | 5.2 | 0.6                                       | 4.8 | 0.4                                       | 4.8 |      |
| $t_{PZH}$ | $\overline{OE}$ | B           | 3.8                      | 0.9                                       | 8.8 | 0.8  | 7   | 0.6                                       | 4.8 | 0.6                                       | 4   | ns   |
| $t_{PZL}$ |                 |             | 3.8                      | 0.9                                       | 8.8 | 0.8  | 7   | 0.6                                       | 4.8 | 0.6                                       | 4   |      |
| $t_{PHZ}$ | $\overline{OE}$ | A           | 4.7                      | 1   | 8.4 | 1  | 8.4 | 1   | 6.2 | 1   | 6.6 | ns   |
| $t_{PLZ}$ |                 |             | 4.7                      | 1   | 8.4 | 1  | 8.4 | 1   | 6.2 | 1   | 6.6 |      |
| $t_{PHZ}$ | $\overline{OE}$ | B           | 4.5                      | 1.5                                       | 9.4 | 1.3  | 8.2 | 1.1                                       | 6.2 | 0.9                                       | 5.2 | ns   |
| $t_{PLZ}$ |                 |             | 4.5                      | 1.5                                       | 9.4 | 1.3  | 8.2 | 1.1                                       | 6.2 | 0.9                                       | 5.2 |      |

switching characteristics over recommended operating free-air temperature range,  
 $V_{CCA} = 3.3\text{ V} \pm 0.3\text{ V}$  (see Figure 11)

| PARAMETER | FROM (INPUT)    | TO (OUTPUT) | $V_{CCB} = 1.2\text{ V}$ | $V_{CCB} = 1.5\text{ V} \pm 0.1\text{ V}$ |     | $V_{CCB} = 1.8\text{ V} \pm 0.15\text{ V}$ |     | $V_{CCB} = 2.5\text{ V} \pm 0.2\text{ V}$ |     | $V_{CCB} = 3.3\text{ V} \pm 0.3\text{ V}$ |     | UNIT |
|-----------|-----------------|-------------|--------------------------|---|-----|--|-----|---|-----|---|-----|------|
|           |                 |             | TYP                      | MIN                                       | MAX | MIN  | MAX | MIN                                       | MAX | MIN                                       | MAX |      |
| $t_{PLH}$ | A               | B           | 2.9                      | 0.1                                       | 5.6 | 0.1  | 4.5 | 0.1                                       | 3.3 | 0.1                                       | 2.9 | ns   |
| $t_{PHL}$ |                 |             | 2.9                      | 0.1                                       | 5.6 | 0.1  | 4.5 | 0.1                                       | 3.3 | 0.1                                       | 2.9 |      |
| $t_{PLH}$ | B               | A           | 2.6                      | 0.6                                       | 4.2 | 0.4  | 3.4 | 0.2                                       | 3   | 0.1                                       | 2.8 | ns   |
| $t_{PHL}$ |                 |             | 2.6                      | 0.6                                       | 4.2 | 0.4  | 3.4 | 0.2                                       | 3   | 0.1                                       | 2.8 |      |
| $t_{PZH}$ | $\overline{OE}$ | A           | 3.8                      | 0.6                                       | 8.7 | 0.6  | 5.2 | 0.6                                       | 3.8 | 0.4                                       | 3.8 | ns   |
| $t_{PZL}$ |                 |             | 3.8                      | 0.6                                       | 8.7 | 0.6  | 5.2 | 0.6                                       | 3.8 | 0.4                                       | 3.8 |      |
| $t_{PZH}$ | $\overline{OE}$ | B           | 3.7                      | 0.8                                       | 8.7 | 0.6  | 6.8 | 0.5                                       | 4.7 | 0.5                                       | 3.8 | ns   |
| $t_{PZL}$ |                 |             | 3.7                      | 0.8                                       | 8.7 | 0.6  | 6.8 | 0.5                                       | 4.7 | 0.5                                       | 3.8 |      |
| $t_{PHZ}$ | $\overline{OE}$ | A           | 4.8                      | 0.7                                       | 9.3 | 0.7  | 8.3 | 0.7                                       | 5.6 | 0.7                                       | 6.6 | ns   |
| $t_{PLZ}$ |                 |             | 4.8                      | 0.7                                       | 9.3 | 0.7  | 8.3 | 0.7                                       | 5.6 | 0.7                                       | 6.6 |      |
| $t_{PHZ}$ | $\overline{OE}$ | B           | 5.3                      | 1.4                                       | 9.3 | 1.2  | 8.1 | 1   | 6.4 | 0.8                                       | 6.2 | ns   |
| $t_{PLZ}$ |                 |             | 5.3                      | 1.4                                       | 9.3 | 1.2  | 8.1 | 1   | 6.4 | 0.8                                       | 6.2 |      |





**SN74AVCH4T245**  
**4-BIT DUAL-SUPPLY BUS TRANSCEIVER**  
**WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS**

SCE5577A – JUNE 2004 – REVISED APRIL 2005

operating characteristics,  $T_A = 25^\circ\text{C}$

| PARAMETER         |        |                  | TEST CONDITIONS   | $V_{CCA} =$<br>$V_{CCB} = 1.2\text{ V}$ | $V_{CCA} =$<br>$V_{CCB} = 1.5\text{ V}$ | $V_{CCA} =$<br>$V_{CCB} = 1.8\text{ V}$ | $V_{CCA} =$<br>$V_{CCB} = 2.5\text{ V}$ | $V_{CCA} =$<br>$V_{CCB} = 3.3\text{ V}$ | UNIT |
|-------------------|--------|------------------|---|---|---|---|---|---|------|
|                   |        |                  |   | TYP                                     | TYP                                     | TYP                                     | TYP                                     | TYP                                     |      |
| $C_{pdA}^\dagger$ | A to B | Outputs Enabled  | $C_L = 0,$<br>$f = 10\text{ MHz},$<br>$t_r = t_f = 1\text{ ns}$ | 1                                       | 1                                       | 1                                       | 1.5                                     | 2                                       | pF   |
|                   |        | Outputs Disabled |   | 1                                       | 1                                       | 1                                       | 1                                       | 1                                       |      |
|                   | B to A | Outputs Enabled  |   | 12                                      | 12.5                                    | 13                                      | 14                                      | 15                                      |      |
|                   |        | Outputs Disabled |   | 1                                       | 1                                       | 1                                       | 1                                       | 1                                       |      |
| $C_{pdB}^\dagger$ | A to B | Outputs Enabled  | $C_L = 0,$<br>$f = 10\text{ MHz},$<br>$t_r = t_f = 1\text{ ns}$ | 12                                      | 12.5                                    | 13                                      | 14                                      | 15                                      | pF   |
|                   |        | Outputs Disabled |   | 1                                       | 1                                       | 1                                       | 1                                       | 1                                       |      |
|                   | B to A | Outputs Enabled  |   | 1                                       | 1                                       | 1                                       | 1                                       | 2                                       |      |
|                   |        | Outputs Disabled |   | 1                                       | 1                                       | 1                                       | 1                                       | 1                                       |      |

$^\dagger$  Power dissipation capacitance per transceiver


# SN74AVCH4T245

## 4-BIT DUAL-SUPPLY BUS TRANSCEIVER

### WITH CONFIGURABLE VOLTAGE TRANSLATION AND 3-STATE OUTPUTS

SCES577A – JUNE 2004 – REVISED APRIL 2005




#### PARAMETER MEASUREMENT INFORMATION



LOAD CIRCUIT

| TEST              | S1                 |
|-------------------|--------------------|
| $t_{pd}$          | Open               |
| $t_{PLZ}/t_{PZL}$ | $2 \times V_{CCO}$ |
| $t_{PHZ}/t_{PZH}$ | GND                |

| $V_{CCO}$          | $C_L$ | $R_L$        | $V_{TP}$ |
|--------------------|-------|--------------|----------|
| 1.2 V              | 15 pF | 2 k $\Omega$ | 0.1 V    |
| 1.5 V $\pm$ 0.1 V  | 15 pF | 2 k $\Omega$ | 0.1 V    |
| 1.8 V $\pm$ 0.15 V | 15 pF | 2 k $\Omega$ | 0.15 V   |
| 2.5 V $\pm$ 0.2 V  | 15 pF | 2 k $\Omega$ | 0.15 V   |
| 3.3 V $\pm$ 0.3 V  | 15 pF | 2 k $\Omega$ | 0.3 V    |



- NOTES:
- $C_L$  includes probe and jig capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
  - All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10$  MHz,  $Z_O = 50 \Omega$ ,  $dv/dt \geq 1$  V/ns.
  - The outputs are measured one at a time, with one transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
  - $V_{CCI}$  is the  $V_{CC}$  associated with the input port.
  - $V_{CCO}$  is the  $V_{CC}$  associated with the output port.

Figure 1. Load Circuit and Voltage Waveforms

**PACKAGING INFORMATION**

| Orderable Device  | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|-------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| 74AVCH4T245DGVRE4 | ACTIVE                | TVSOP        | DGV             | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| 74AVCH4T245PWRE4  | ACTIVE                | TSSOP        | PW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| 74AVCH4T245PWTE4  | ACTIVE                | TSSOP        | PW              | 16   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| 74AVCH4T245RGYRG4 | ACTIVE                | QFN          | RGY             | 16   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1YEAR           |
| SN74AVCH4T245D    | ACTIVE                | SOIC         | D               | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DE4  | ACTIVE                | SOIC         | D               | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DGVR | ACTIVE                | TVSOP        | DGV             | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DR   | ACTIVE                | SOIC         | D               | 16   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DRE4 | ACTIVE                | SOIC         | D               | 16   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DT   | ACTIVE                | SOIC         | D               | 16   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245DTE4 | ACTIVE                | SOIC         | D               | 16   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245PW   | ACTIVE                | TSSOP        | PW              | 16   | 90          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245PWE4 | ACTIVE                | TSSOP        | PW              | 16   | 90          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245PWR  | ACTIVE                | TSSOP        | PW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245PWT  | ACTIVE                | TSSOP        | PW              | 16   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| SN74AVCH4T245RGYR | ACTIVE                | QFN          | RGY             | 16   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1YEAR           |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

DGV (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE

24 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15 per side.  
 D. Falls within JEDEC: 24/48 Pins – MO-153  
 14/16/20/56 Pins – MO-194

D (R-PDSO-G16)


PLASTIC SMALL-OUTLINE PACKAGE





- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
  - D. Falls within JEDEC MS-012 variation AC.

RGY (R-PQFP-N16)

PLASTIC QUAD FLATPACK



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. QFN (Quad Flatpack No-Lead) package configuration.
  -  The package thermal pad must be soldered to the board for thermal and mechanical performance.
  -  Pin 1 identifiers are located on both top and bottom of the package and within the zone indicated. The Pin 1 identifiers are either a molded, marked, or metal feature.
  - F. Package complies to JEDEC MO-241 variation BB.

PW (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



4040064/F 01/97

- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-153



## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>  |  | <b>Applications</b> |  |
|------------------|--|---------------------|--|
| Amplifiers       | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters  | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP              | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Interface        | <a href="http://interface.ti.com">interface.ti.com</a>             | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Logic            | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt       | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
|                  |  | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
|                  |  | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                  |  | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)