查询HD74LVCZ240A供应商 捷多邦，专业PCB打样工厂，24小时加急出货

HD74LVCZ240A

Octal Buffers / Line Drivers with 3–state Outputs

HITACHI

ADE-205-229A (Z)
2nd. Edition
February 1999

Description

The HD74LVCZ240A has eight inverter drivers with three state outputs in a 20 pin package. This device is a inverting buffer and has two active low enables ($1\overline{G}$ and $2\overline{G}$). Each enable independently controls four buffers.

When V_{CC} is between 0 and 1.5 V, the device is in the high impedance state during power up or power down.

Low voltage and high speed operation is suitable at battery drive product (note type personal computer) and low power consumption extends the life of a battery for long time operation.

Features

- V_{CC} = 2.7 to 5.5 V
- All inputs V_{IH} (Max) = 5.5 V (@V_{CC} = 0 to 5.5 V)
- All outputs V_O (Max) = 5.5 V (@V_{CC} = 0 V or output off state)
- Typical V_{OL} ground bounce < 0.8 V (@V_{CC} = 3.3 V, Ta = 25°C)
- Typical V_{OH} undershoot > 2.0 V (@V_{CC} = 3.3 V, Ta = 25°C)
- High impedance state during power up and power down
- Power off disables outputs, permitting live insertion
- High output current ±24 mA (@V_{CC} = 3.0 to 5.5 V)

找PDF 维库一下 pdf.dzsc.com

Function Table

Inputs		Output $\overline{Y}$
$\overline{G}$	A	
H	X	Z
L	H	L
L	L	H

H : High level
L : Low level
X : Immaterial
Z : High impedance

Pin Arrangement



(Top view)

Absolute Maximum Ratings

Item	Symbol	Ratings	Unit	Conditions
Supply voltage	V_{CC}	–0.5 to 7.0	V	
Input voltage	V_I	–0.5 to 7.0	V	
Output voltage	V_O	–0.5 to 7.0	V	Output “Z” or V_{CC} : OFF
		–0.5 to V_{CC}+0.5		Output “H” or “L”
Input diode current	I_{IK}	–50	mA	$V_I < 0$
Output diode current	I_{OK}	–50	mA	$V_O < 0$
Output current	I_O	±50	mA	
V_{CC}, GND current	I_{CC} or I_{GND}	±100	mA	
Storage temperature	Tstg	–65 to 150	°C	

Note: The absolute maximum ratings are values which must not individually be exceeded, and furthermore, no two of which may be realized at the same time.

Recommended Operating Conditions

Item	Symbol	Ratings	Unit	Conditions
Supply voltage	V_{CC}	2.7 to 5.5	V	At operation
Input voltage	V_I	0 to 5.5	V	
Output voltage	V_O	0 to 5.5	V	Output “Z” or V_{CC} : OFF
		0 to V_{CC}		Output “H” or “L”
Output current	I_{OH}	–12	mA	V_{CC} = 2.7 V
		–24 [*1]		V_{CC} = 3.0 to 5.5 V
	I_{OL}	12		V_{CC} = 2.7 V
		24 [*1]		V_{CC} = 3.0 to 5.5 V
Input rise / fall time	t_r, t_f	0 to 6	ns / V	
Operating temperature	Ta	–40 to +85	°C	

Note: 1. Duty cycle ≤ 50%

Logic Diagram



Electrical Characteristics (Ta = –40 to 85°C)

Item	Symbol	V_{CC} (V)	Min	Typ	Max	Unit	Test Conditions
Input voltage	V_{IH}	2.7 to 3.6	2.0	—	—	V	
		4.5 to 5.5	V_{CC}×0.7	—	—		
	V_{IL}	2.7 to 3.6	—	—	0.8		
		4.5 to 5.5	—	—	V_{CC}×0.3		
Output voltage	V_{OH}	2.7 to 5.5	V_{CC}–0.2	—	—	V	I_{OH} = –100 µA
		2.7	2.2	—	—		I_{OH} = –12 mA
		3.0	2.4	—	—		
		3.0	2.2	—	—		I_{OH} = –24 mA
		4.5	3.8	—	—		
	V_{OL}	2.7 to 5.5	—	—	0.2		I_{OL} = 100 µA
		2.7	—	—	0.4		I_{OL} = 12 mA
		3.0	—	—	0.55		I_{OL} = 24 mA
		4.5	—	—	0.55		
Input current	I_{IN}	0 to 5.5	—	—	±5	µA	V_{IN} = 0 to 5.5 V
Off state output current	I_{OZ}	2.7 to 5.5	—	—	±5	µA	V_{OUT} = 0 to 5.5 V
	I_{OZPU}	0 to 1.5	—	—	±5		V_{OUT} = 0.5 to 5.5 V,
	I_{OZPD}	1.5 to 0	—	—	±5		Output enable = don't care
Output leak current	I_{OFF}	0	—	—	±5	µA	V_{IN} or V_O = 5.5 V
Quiescent supply current	I_{CC}	2.7 to 3.6	—	—	225	µA	V_{IN} = 3.6 to 5.5 V [*1], I_O = 0
		2.7 to 5.5	—	—	350		V_{IN} = V_{CC} or GND
	ΔI_{CC}	2.7 to 3.6	—	—	500		V_{IN} = one input at (V_{CC}–0.6) V, other inputs at V_{CC} or GND
Input capacitance	C_{IN}	3.3	—	3.4	—	pF	V_{IN} = V_{CC} or GND
Output capacitance	C_O	3.3	—	7.5	—	pF	V_{OUT} = V_{CC} or GND

Note: 1. This applies in the disabled state only.

Switching Characteristics (Ta = –40 to 85°C)

Item	Symbol	V_{cc} (V)	Min	Typ	Max	Unit	FROM (Input)	TO (Output)
Propagation delay time	t_{PLH}	2.7	—	—	7.5	ns	A	$\overline{Y}$
	t_{PHL}	3.3±0.3	1.3	—	6.5			
		5.0±0.5	—	—	5.0			
Output enable time	t_{ZH}	2.7	—	—	9.0	ns	$\overline{G}$	$\overline{Y}$
	t_{ZL}	3.3±0.3	1.1	—	8.0			
		5.0±0.5	—	—	6.5			
Output disable time	t_{HZ}	2.7	—	—	8.0	ns	$\overline{G}$	$\overline{Y}$
	t_{LZ}	3.3±0.3	1.4	—	7.0			
		5.0±0.5	—	—	6.0			
Between output pin skew *1	t_{OSLH}	2.7	—	—	—	ns		
	t_{OSHL}	3.3±0.3	—	—	1.0			
		5.0±0.5	—	—	1.0			

Note : 1. This parameter is characterized but not tested.
$t_{OSLH} = |t_{PLHm} – t_{PLHn}|$, $t_{OSHL} = |t_{PHLm} – t_{PHLn}|$

Test Circuit



Symbol	S1	
	Vcc=2.7V, 3.3±0.3V	Vcc=5.0±0.5V
t_{PLH} / t_{PHL}	OPEN	OPEN
t_{ZH} / t_{HZ}	GND	GND
t_{ZL} / t_{LZ}	6 V	2×V_{CC}

Note: 1. C_L includes probe and jig capacitance.

• **Waveforms – 1**



• **Waveforms – 2**



TEST	Vcc=2.7V, 3.3±0.3V	Vcc=5.0±0.5V
V_{IH}	2.7 V	V_{CC}
V_{ref}	1.5 V	50%V_{CC}
V_{OH1}	3 V	V_{CC}
V_{OL1}	GND	GND

Notes: 1. Input waveform : PRR = 10 MHz, duty cycle 50%, t_r = 2.5 ns, t_f = 2.5 ns
2. Waveform – A shows input conditions such that the output is “L” level when enabled by the output control.
3. Waveform – B shows input conditions such that the output is “H” level when enabled by the output control.

Power up / down Characteristics



Package Dimensions

Unit : mm



Hitachi Code	FP-20DA
JEDEC	—
EIAJ	Conforms
Weight (reference value)	0.31 g



Dimension including the plating thickness
Base material dimension

Hitachi Code	TTP-20DA
JEDEC	—
EIAJ	—
Weight (reference value)	0.07 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.
Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL
NorthAmerica : http:semiconductor.hitachi.com/
Europe : http://www.hitachi-eu.com/hel/ecg
Asia (Singapore) : http://www.has.hitachi.com.sg/grp3/sicd/index.htm
Asia (Taiwan) : http://www.hitachi.com.tw/E/Product/SICD_Frame.htm
Asia (HongKong) : http://www.hitachi.com.hk/eng/bo/grp3/index.htm
Japan : http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose,CA 95134
Tel: <1> (408) 433-1990
Fax: <1>(408) 433-0223

Hitachi Europe GmbH
Electronic components Group
Dornacher Straße 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 049318
Tel: 535-2100
Fax: 535-1533

Hitachi Asia Ltd.
Taipei Branch Office
3F, Hung Kuo Building. No.167,
Tun-Hwa North Road, Taipei (105)
Tel: <886> (2) 2718-3666
Fax: <886> (2) 2718-8180

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower, World Finance Centre,
Harbour City, Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
Tel: <852> (2) 735 9218
Fax: <852> (2) 730 0281
Telex: 40815 HITEC HX

Copyright ' Hitachi, Ltd., 1999. All rights reserved. Printed in Japan.