



Electronics

a vital part of your world

Find Answers:

Sunday, 20 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Circuit Breakers

↳ Thermal Circuit Breakers



W28-XQ1A-0.25 Active

Not ELV or RoHS Compliant

(Tyco Electronics P/N: 1-1393250-9)

Search for Compliant (RoHS/ELV)

Alternates

Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> General Info Sales Info 	<ul style="list-style-type: none"> Pricing Product Availability 	<ul style="list-style-type: none"> Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo	Schematic	Panel Cutout
-------------------------------	---------------------------	------------------------------

Searchable Features:

Brand:	Potter & Brumfield
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Series:	W28
Actuator Style:	Push to Reset
Number of Poles:	1
Current Rating (Amps.):	0.25
Button Color:	Black
Bezel Color:	Black with White Rate Marking
Circuit Function:	Series Trip
Operating Voltage, Max.:	32 VDC, 250 VAC
Trip Time at 200%:	4.5 to 28 Seconds

Other Properties:

Approved Standards:	UL Recognized, CSA Certified, SEV Approved, Demko Approved, VDE Approved
Panel Thickness (mm [in]):	0.81 – 1.57 [0.032 – 0.062]
Circuit Breaker Style:	Fuseholder Type

Interrupt Capacity:	1,000 A @ 32 VDC or 250 VAC
Mounting Options:	Snap-In Panel Mount
Termination Type:	6.35 [.250] Straight Quick Connect Tab
Mounting Bushing:	None

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]