



Electronics

a vital part of your world

Find Answers:

Sunday, 6 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter  
**SUBSCRIBE NOW!**  
 click here

Circuit Breakers

↳ Thermal Circuit Breakers



W28-XQ1A-1 Active

[Not ELV or RoHS Compliant](#)

(Corporate P/N: 2-1393250-3)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>➤ <a href="#">General Info</a></li> <li>➤ <a href="#">Sales Info</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Pricing &amp; Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Tooling</a></li> </ul>

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

[Schematic](#)

[Panel Cutout](#)

Searchable Features:

<b>Brand:</b>	Potter & Brumfield
<b>RoHS/ELV Compliance:</b>	Not ELV/RoHS compliant
<b>Lead Free Solder Processes:</b>	Not relevant for lead free process
<b>Series:</b>	W28
<b>Actuator Style:</b>	Push to Reset
<b>Number of Poles:</b>	1
<b>Current Rating (Amps.):</b>	1
<b>Button Color:</b>	Black
<b>Bezel Color:</b>	Black with White Rate Marking
<b>Circuit Function:</b>	Series Trip
<b>Operating Voltage, Max.:</b>	32 VDC, 250 VAC

Other Properties:

<b>Approved Standards:</b>	UL Recognized, CSA Certified, SEV Approved, Demko Approved, VDE Approved
<b>Panel Thickness (mm [in]):</b>	0.81 – 1.57 [0.032 – 0.062]
<b>Circuit Breaker Style:</b>	Fuseholder Type

<b><u>Trip Time at 200%:</u></b>	4.5 to 28 Seconds
<b><u>Interrupt Capacity:</u></b>	1,000 A @ 32 VDC or 250 VAC
<b><u>Mounting Options:</u></b>	Snap-In Panel Mount
<b><u>Termination Type:</u></b>	6.35 [.250] Straight Quick Connect Tab
<b><u>Mounting Bushing:</u></b>	None

[Copyright and Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]

▪