



Electronics

a vital part of your world

Find Answers:

Sunday, 6 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Circuit Breakers

↳ Thermal Circuit Breakers



W51-A122B1-15 Active

Not ELV or RoHS Compliant

(Corporate P/N: 1-1423673-3)

Search for Compliant (RoHS/ELV)

Alternates

Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> General Info Sales Info 	<ul style="list-style-type: none"> Pricing & Availability 	<ul style="list-style-type: none"> Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo	Schematic	Panel Cutout
-------------------------------	---------------------------	------------------------------

Searchable Features:

Brand:	Potter & Brumfield
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Not relevant for lead free process
Series:	W51
Actuator Style:	Rocker
Number of Poles:	1
Current Rating (Amps.):	15
Rocker Color:	Red (Translucent)
Circuit Function:	Trip Free - Switchable
Operating Voltage, Max.:	250 VAC
Illuminated:	Yes
Trip Time at 200%:	4 to 40 Seconds

Other Properties:

Panel Thickness (mm [in]):	0.75 – 3.00 [0.030 – 0.118]
Panel Cutout:	28.5 mm x 13.5 mm [1.122 x .531]
RESET/OFF Marking:	RESET/OFF Printed

<u>Interrupt Capacity:</u>	1,000 A @ 250 VAC
<u>Termination Type:</u>	6.35 [.250] Straight Quick Connect Tab

Copyright and Privacy Statement
Visit Tyco International Ltd.

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

