

a vital part of your world

Text Search:

Thursday, 8 December, 2005

**CATALOG**

→ Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- Part Number Search
- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

**Home**

e-bulletin newsletter  
**SUBSCRIBE NOW!**  
click here

**Circuit Breakers**  
↳ **Thermal Circuit Breakers**



**W54-XB1A4A10-5** [Active](#)

**Directive 2002/95/EC Compliant**

[RoHS Compliant](#)

**(Corporate P/N: 1423674-2)**

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

**Related Part Information**

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>➤ <a href="#">General Info</a></li> <li>➤ <a href="#">Sales Info</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Pricing &amp; Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

[Schematic](#)

**Searchable Features:**

<b>Brand:</b>	Potter & Brumfield
<b>RoHS/ELV Compliance:</b>	RoHS compliant, ELV compliant
<b>Lead Free Solder Processes:</b>	Not relevant for lead free process
<b>Series:</b>	W54
<b>Actuator Style:</b>	Push to Reset
<b>Number of Poles:</b>	1
<b>Current Rating (Amps.):</b>	5
<b>Button Color:</b>	White with Red Rate Marking (Vertical)
<b>Circuit Function:</b>	Series Trip
<b>Operating Voltage, Max.:</b>	250 VAC
<b>Trip Time at 200%:</b>	5 to 40 Seconds
<b>Interrupt Capacity:</b>	1,000 A @ 250 VAC
<b>Mounting Options:</b>	Knurled Nut/Hex Nut
<b>Mounting Hardware Packaging:</b>	Assembled to Bushing
<b>Termination Type:</b>	6.35 [.250] Straight Quick Connect Tab

**Other Properties:**

<b>RoHS/ELV Compliance History:</b>	Always was RoHS compliant
-------------------------------------	---------------------------

[Mounting Bushing:](#)

9.8 mm x 12.6 mm Long,  
Metal

[Copyright and Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]